September 18, 2015 BOARD OF COUNTY COMMISSIONERS ORANGE COUNTY, FLORIDA Y15-7016-MM / ADDENDUM #2 ORANGE COUNTY CONVENTION CENTER PHASES I - V AUDIO HEAD END EQUIPMENT REPLACEMENT

Revised Bid Opening Date: October 8, 2015

This addendum is hereby incorporated into the bid documents of the project referenced above. The following items are clarifications, corrections, additions, deletions and/or revisions to and shall take precedence over the original documents. <u>Underlining</u> indicates additions, deletions are indicated by <u>strikethrough</u>.

- A. The Bid Opening Date is changed from October 1, 2015 at 2:00 P.M. to October 8, 2015 at 2:00 P.M.
- B. General Note to Bidders:

The Owner will consider approved equals/substitutions providing the request follows the process described in Substitution Procedures, Section 01 25 00 – Addendum #2."

C. CHANGES TO SPECIFICATIONS:

The following are changes to the Specifications. DELETE only the specifications listed below, in their entirety, and ADD the following attached revised specifications:

- 1. Table of Contents (2 pages)
- 2. 01 25 00 Substitution Procedure (4 pages)
- 3. 27 05 07 Submittals for Communications Systems (8 pages)
- 4. 27 41 31 Communications System (Paging) (26 pages)
- 5. Attachment in back of specification manual: Audio System Matrix (44 pages)
- D. CHANGES TO DRAWINGS

SYSTEMS

- ITEM NO. 1. DRAWING SHEET NO. E.7-05 RENO RACKS SYSTEMS A. Changed notes to add for equipment that is to be owner provided. ITEM NO. 2. DRAWING SHEET NO. E.7-06 RENO RACKS SYSTEMS A. Changed notes to add for equipment that is to be owner provided. ITEM NO. 3. DRAWING SHEET NO. E.7-07 RENO RACKS SYSTEMS
 - A. Changed notes to add for equipment that is to be owner provided.

- ITEM NO. 4. DRAWING SHEET NO. E.7-08 RENO RACKS SYSTEMS
 - A. Changed notes to add for equipment that is to be owner provided.
- ITEM NO. 5. DRAWING SHEET NO. E.7-09 RENO RACKS SYSTEMS
 - A. Changed notes to add for equipment that is to be owner provided.
 - B. Changed model number of (4) channel amplifiers in racks.
- ITEM NO. 6. DRAWING SHEET NO. ED-W-3.4.26 DEMO PLAN SYSTEMS
 - A. Changed note from "Alternate #1" to "Additive #2"
- ITEM NO. 7. DRAWING SHEET NO. E-W-3.4.25 PARTIAL PLANS SYSTEMS
 - A. Changed note from "Alternate #1" to "Additive #2"
 - B. Changed hex note #1, added speaker installation details.
- ITEM NO. 8. DRAWING SHEET NO. E-W-3.4.26 PARTIAL PLANS SYSTEMS
 - A. Changed note from "Alternate #1" to "Additive #2"
 - B. Changed hex note #1, added speaker installation details.
- ITEM NO. 9. DRAWING SHEET NO. E-W-3.4.27 PARTIAL PLANS SYSTEMS
 - A. Changed note from "Alternate #1" to "Additive #2"
 - B. Changed hex note #1, added speaker installation details.
- ITEM NO. 10. DRAWING SHEET NO. E-W-3.4.28 PARTIAL PLANS SYSTEMS
 - A. Changed note from "Alternate #1" to "Additive #2"
 - B. Changed hex note #1, added speaker installation details.
- ITEM NO. 11. DRAWING SHEET NO. E-W-3.1.03 PARTIAL PLANS SYSTEMS
 - A. Changed note from "Alternate #2" to "Additive #1"
- E. The following are questions/responses/clarifications:
 - **Question 1**: Is this an invitation only project?
 - **Response 1:** No. This IFB is open to any Bidder that meets the requirements outlined in the IFB package and addendums.
 - **Question 2:** Is this a sole source project?
 - **Response 2:** No. QSC was the basis for design however two additional systems have been named as approved equals and an approved equal/substitution process has been included within the revised specifications included in this addendum.
 - Question 3: DRAWING SHEET NO. E.7-07 RENO RACKS SYSTEMS With regards to Alt #1 and Alt #2 pricing, are we to include the pricing for only the speakers and install of speakers? The reason that I ask is because Drawing E-7.07 is NOT Defined as to what equipment is "ALT" and what equipment is "BASE BID". Are we to include the RACK Equipment (Patch Bays, amplifiers and installation of Rack Equipment) required for the Alt #1 & ALT #2 in the BASE Bid or the ALT Pricing?

Response 3: The details for what is considered Base Bid and now "Bid Additive" is described in the Audio System Spreadsheet, which is a part of the bid package documentation. In the spreadsheet, each amplifier, I/O and peripheral device is clearly marked and should be self-explanatory that the additional speakers would also require additional amplifiers and accessory devices to make them operational. The rack elevations for the spaces mentioned are shown including the bid additive for the ability of the existing racks to have the sufficient space available for the additional amplifiers required for that choice.

Question 4:

Drawings reference QSC part number CX 1204. Is CX 1204 a valid QSC part number? If no, please provide correct part number?

Response 4: The correct model number should have been CX 204V. It has been corrected on the drawings and is included in this submittal.

Question 5:

Spec 27 41 13 -14, Communication System (Paging) "E" UPS discusses using one (1) Liebert #GTX4-10000RT208 with PD2-108 Power Distribution Box to supply UPS power to more than two (2) PDU's using only the L6-30R connectors. According to the manufacture this is not possible with specified equipment because the PD2-108 can only power a maximum of 2 equipment PDU's. Please advise the design intent and listing of all need equipment to meet the design spec?

Response 5: A single PDU is not necessary for each cabinet. The (2) PDU's can be housed in a primary cabinet and the necessary power cabling can be terminated into those (2) primary PDU's and distributed to the equipment specified to receive the power cabling from the PDU's location. Ordering pre-terminated power cabling in the lengths necessary would be preferable for a cleaner install.

F. ATTACHMENTS:

Drawings (revised):

E-7.05

E-7.06

E-7.07

E-7.08

E-7.09

ED-W-3.4.26

E-W-3.4.25

E-W-3.4.26

E-W-3.4.27

E-W-3.4.28

E-W-3.1.03

Specs (revised):

01 25 00 - ADD #2

27 05 07 – ADD #2

27 41 13 – ADD #2

Table of Contents (revised) – ADD #2 Audio System Matrix (revised) – ADD #2

G. All other terms and conditions of the IFB remain the same.

The Proposer shall acknowledge receipt of this addendum by completing the applicable section in the solicitation or by completion of the acknowledgement information on the addendum. Either form of acknowledgement must be completed and returned not later than the date and time for receipt of the proposal.

Receipt acknowledged by:		
Authorized Signature	Date Signed	
Title		
Name of Firm		

TABLE OF CONTENTS MPE 2014-095

DIVISION 01 01 11 00 01 25 00 01 26 00 01 29 00 01 31 00 01 31 19 01 32 33 01 33 00 01 73 29 01 77 00	GENERAL REQUIREMENTS Summary of Work Substitution Procedures Contract Modification Procedures Payment Procedures Project Management and Coordination Project Meetings Photograph Documentation Submittal Procedures Cutting and Patching Closeout Procedures
01 78 00 01 80 00	Warranties and Bonds OC BCC Standard Summary w/attachment
DIVISION 02 02 41 13 02 41 19	EXISTING CONDITIONS Selective Demolition Demolition and Alterations
DIVISION 03	CONCRETE - NOT USED
DIVISION 04	MASONRY - NOT USED
DIVISION 05	METALS - NOT USED
DIVISION 06	WOOD, PLASTICS, AND COMPOSITES - NOT USED
DIVISION 07 07 62 00	THERMAL AND MOISTURE PROTECTION Sheet Metal Flashing and Trim Firestopping
07 84 00 07 84 13 07 92 00	Through-Penetration Firestop System Joint Sealant
07 84 13	
07 84 13 07 92 00	Joint Sealant
07 84 13 07 92 00 DIVISION 08 DIVISION 09 09 55 10 09 90 00	Joint Sealant OPENINGS – NOT USED FINISHES Acoustical Ceilings
07 84 13 07 92 00 DIVISION 08 DIVISION 09 09 55 10 09 90 00 DIVISION 10	Joint Sealant OPENINGS – NOT USED FINISHES Acoustical Ceilings Painting
07 84 13 07 92 00 DIVISION 08 DIVISION 09 09 55 10 09 90 00 DIVISION 10 DIVISION 11	Joint Sealant OPENINGS – NOT USED FINISHES Acoustical Ceilings Painting SPECIALTIES – NOT USED
07 84 13 07 92 00 DIVISION 08 DIVISION 09 09 55 10 09 90 00 DIVISION 10 DIVISION 11 DIVISION 12	Joint Sealant OPENINGS – NOT USED FINISHES Acoustical Ceilings Painting SPECIALTIES – NOT USED EQUIPMENT – NOT USED
07 84 13 07 92 00 DIVISION 08 DIVISION 09 09 55 10 09 90 00 DIVISION 10 DIVISION 11 DIVISION 12 DIVISION 13	Joint Sealant OPENINGS – NOT USED FINISHES Acoustical Ceilings Painting SPECIALTIES – NOT USED EQUIPMENT – NOT USED FURNISHINGS – NOT USED

DIVISIONS 15 THRU 20 - NOT USED

DIVISION 21 FIRE SUPPRESSION – NOT USED

DIVISION 22 PLUMBING - NOT USED

DIVISION 23 HEATING, VENTILATING, AND AIR CONDITIONING – NOT USED

DIVISION 25 - INTEGRATED AUTOMATION - NOT USED

DIVISION 26 26 05 09 26 05 10 26 05 11 26 05 26 26 05 29 26 05 33 26 05 34 26 05 35 26 05 36 26 05 37 26 05 38	ELECTRICAL Reference Standards and Regulatory Requirements Electrical Symbols and Abbreviations Alternates Grounding and Bonding Hangers and Supports Conduit Outlet Boxes Pull and Junction Boxes Cable Trays Surface Raceways Floor Boxes
26 05 53	Identification for Electrical Systems
DIVICION 27	COMMUNICATIONS
DIVISION 27	
27 01 00	Operation and Maintenance Manuals for Communications Systems
27 01 00 27 01 05	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems
27 01 00 27 01 05 27 05 00	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications
27 01 00 27 01 05 27 05 00 27 05 07	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10 27 05 13	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems Building Wire and Cable for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10 27 05 13 27 05 26	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems Building Wire and Cable for Communications Systems Grounding and Bonding for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10 27 05 13 27 05 26 27 05 29	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems Building Wire and Cable for Communications Systems Grounding and Bonding for Communications Systems Hangers and Supports for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10 27 05 13 27 05 26 27 05 29 27 05 33	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems Building Wire and Cable for Communications Systems Grounding and Bonding for Communications Systems Hangers and Supports for Communications Systems Conduit and Backboxes for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10 27 05 13 27 05 26 27 05 29 27 05 33 27 05 35	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems Building Wire and Cable for Communications Systems Grounding and Bonding for Communications Systems Hangers and Supports for Communications Systems Conduit and Backboxes for Communications Systems Pull and Junction Boxes for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10 27 05 13 27 05 26 27 05 29 27 05 33 27 05 35 27 05 53	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems Building Wire and Cable for Communications Systems Grounding and Bonding for Communications Systems Hangers and Supports for Communications Systems Conduit and Backboxes for Communications Systems Pull and Junction Boxes for Communications Systems Identification for Communications Systems
27 01 00 27 01 05 27 05 00 27 05 07 27 05 10 27 05 13 27 05 26 27 05 29 27 05 33 27 05 35	Operation and Maintenance Manuals for Communications Systems Investigation of Existing Communications Systems Common Work Results for Communications Submittals for Communications Systems Symbols and Abbreviations for Communications Systems Building Wire and Cable for Communications Systems Grounding and Bonding for Communications Systems Hangers and Supports for Communications Systems Conduit and Backboxes for Communications Systems Pull and Junction Boxes for Communications Systems

Attachment:

27 10 01

27 41 31

OCCC Audio System Matrix

Premise Distribution Wiring System Communication System (Paging)

END OF TABLE OF CONTENTS

SECTION 01 25 00 - SUBSTITUTION PROCEDURES

PART 1 - GENERAL

1.01 RELATED DOCUMENTS

A. Drawings and general provisions of Contract, including General and Supplementary conditions and other Division-01 Specification Sections, apply to this Section.

1.02 SUMMARY

- A. This Section specifies administrative and procedural requirements for handling request for substitutions made during bidding and after award of the Contract.
- B. The Contractor's Installation Schedule and the Schedule of Submittals are included under Section 01 33 00 Submittal Procedures.

1.03 DEFINITIONS

- A. Definitions used in this Article are not intended to change or modify the meaning of other terms used in the Contract Documents.
- B. Substitutions: The Contract will be awarded based on the design, methods, materials and/or equipment as addressed in the Contract Drawings and/or described in the Contract Specifications. Addressing, describing or naming an item is intended to establish the type, function, characteristics and quality required in order to establish a base for bidding.
 - During bid as well as after contract award, the Contractor may submit for approval, substitutes for any equipment and/or material. In addition to the product documents, a written certification shall accompany the documentation indicating that the proposed substitute will have the same characteristics, will perform in accordance with the design requirements and that complies with all the requirements set for in the Contract. Any additional information required by the Owner or County Representative shall be provided by the Contractor. Rejection of any proposed substitute will be considered final and the Contractor shall not get into any agreement with manufacturers or providers until the submittal has been finally approved.
 - 2. The basis design shall establish the minimum standard of quality.
 - 3. Any substitution requested made after contract award will not be considered.

1.04 SUBMITTALS

- A. Substitution Request Submittal: Request for substitution shall be considered and reviewed if substitution submittal is received within parameters set forth in section 01 25 00 B to allow for adequate review period by OCCC and Engineer.
 - 1. Submit three (3) copies of each request for substitution for consideration. Submit requests in the form and in accordance with procedures required for Change Order proposals.
 - 2. Identify the product, or the fabrication or installation method to be replaced in each request. Include related Specification Section and Drawing numbers.

Provide complete documentation showing compliance with the requirements for substitution, and the following information, as appropriate:

- Product Data, including Drawings, and descriptions of products, fabrication and installation procedures.
- b. Samples, where applicable or requested.
- A detailed comparison of significant qualities of the proposed substitution with those of the Work specified. Significant qualities may include elements such as size, weight, durability, performance and visual effect.
- d. Coordination information, including a list of changes or modifications needed to other parts of the Work and to construction performed by the Owner and separate Contractors that will become necessary to accommodate the proposed substitution.
- e. Contract Time:
 - a. After award: A statement indicating the substitution's effect on the Contractor's construction schedule compared to the schedule without approval of the substitution.
 - b. Bid Period: Indicate the effect of the proposed substitution on overall Contract Time.
- f. After award: Cost information, including a proposal of the net change, if any in the Contract Sum.
- g. Certification by the Contractor that the Substitution proposed is equal-to or better in every significant respect to that required by the Contract Documents, and that it will perform adequately in the application indicated. Include the contractor's waiver of rights to additional payment or time that may subsequently become necessary because of the failure of the substitution to perform adequately.
- h. Any other additional information required in other sections of these specifications.
- 3. After award: Engineer's Action: Within two weeks of receipt of the request for substitution, the Engineer will request additional information or documentation necessary for evaluation of the request if needed. Within two (2) weeks of receipt of the request, or one week of receipt of the additional information or documentation, which ever is later, the Engineer will notify the Contractor of acceptance or rejection of the proposed substitution. If a decision on use of a proposed substitute cannot be made or obtained within the time allocated, use the project specified equipment. Decision on the use of a product substitution or its rejection by the Engineer is considered final. Acceptance will be in the form of a Change Order.

PART 2 - PRODUCTS

2.01 SUBSTITUTIONS

A. Conditions: The Contractor's substitution request will be received and considered by the Engineer when one or more of the following conditions are satisfied, as determined by

the Engineer; otherwise request will be returned without action except to record noncompliance with these requirements.

- Extensive revisions to Contract Documents are not required.
- 2. Proposed changes are in keeping with the general intent of Contract Documents.
- 3. The request is timely, fully documented and properly submitted.
- 4. The specified product or method of construction cannot be provided within the Contract Time. The request will not be considered if the product or method cannot be provided as a result of failure to pursue the work promptly or coordinate activities properly.
- 5. The specified product or method of construction cannot receive necessary approval by a governing authority, and the requested substitution can be approved.
- 6. A substantial advantage is offered to the Owner, in terms of cost, time, energy conservation or other considerations of merit, after deducting offsetting responsibilities the Owner may be required to bear. Additional responsibilities for the Owner may include additional compensation to the Engineer for redesign and evaluation services, increased cost of other construction by the Owner or separate Contractors, and similar consideration.
- 7. The specified product or method of construction cannot be provided in a manner that is compatible with other materials, and where the Contractor certifies that the substitution will overcome the incompatibility.
- 8. The specified product or method of construction cannot be coordinated with other materials, and where the Contractor certifies that the proposed substitution can be coordinated.
- 9. The specified product or method of construction cannot provide a warranty required by the Contract Documents and where the Contractor certifies that the proposed substitution provide the required warranty.
- B. After award: The Contractor's submittal and Project Manager's acceptance of Shop Drawings, Product Data or Samples that relate to construction activities not complying with the Contract Documents does not constitute an acceptable or valid request for substitution, nor does it constitute approval.
- C. Substitution request constitutes a representation that the Contractor:
 - 1. Has investigated proposed product and determined that it meets or exceeds, in all respects, specified product.
 - Will provide the same warranty for substitution as for specified product.
 - Will coordinate installation and make other changes which may be required for work to be complete in all respects.
 - 4. Waives claims for additional costs which may subsequently become apparent. All costs associated with the substitution will be paid by the Contractor regardless of approvals given, and regardless of subsequent difficulties experienced as a result of substitutions.

PART 3 – EXECUTION (NOT USED)

END OF SECTION

SECTION 27 05 07 - SUBMITTALS FOR COMMUNICATIONS SYSTEMS

PART 1- GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Requirements for submittals specifically applicable to Division 27 Sections, in addition to Division 01 General Requirements and any supplemental requirements/conditions.
- B. See Section Substitutions for additional requirements when submittal consists of accepted substitution equipment.

1.3 SUBMITTAL OF "ACCEPTED SUBSTITUTE" EQUIPMENT/PRODUCT

- A. Refer to section 01 25 00 Substitution Procedures.
- B. Substitutions that cannot meet space requirements or other requirements of these Specifications, whether accepted or not, shall be replaced at the Contractor's expense with no additional time added to the Contract.

1.4 SUBMITTALS

- A. Submittals shall consist of a minimum of one (or if required) two hard cover view type 3-ring binder(s) White, sized to hold 8-1/2" x 11" sheets; one (1) for "ELECTRICAL SUBMITTALS" (Power and Lighting); one (1) for "SYSTEMS SUBMITTALS" Where "SYSTEMS SUBMITTALS" is not applicable, only one (1) binder is required.
 - 1. Binder is to be adequately sized to comfortably hold required submittals. Minimum spline size to be 1", maximum spline size to be 3" (provide additional binders if 3" size is not sufficient to properly hold submittals).
 - 2. Binder cover and spline to have outer clear vinyl pockets. Provide correct designation of project in each pocket; see Binder Examples for Submittals included at end of this Section. Description sheet is to be white with black letters, minimum of 11" high and full width of pocket. Description is to describe project and match project drawing/project manual description. Description to include submittal type, i.e., "ELECTRICAL SUBMITTALS" for Power and Lighting, (and if required) "SYSTEMS SUBMITTALS."

B. Submittals Binders to include:

- 1. First sheet shall be prepared and filled out by Contractor and shall list project addresses, telephones, etc.; see "PROJECT ADDRESSES" Form included at end of this section.
- Second sheet in binder shall be a photocopy of the Electrical Index pages in Specifications.
- 3. Provide reinforced separation sheets tabbed with the appropriate specification reference number and typed index for each section in the Systems Schedule.
- 4. Submittals consisting of marked catalog sheets or shop drawings shall be inserted in the binder in proper order. Submittal data shall be presented in a clear and thorough manner. Clearly mark each copy to identify pertinent products or models applicable to this project. Indicate all optional equipment and delete non-pertinent data. Markings shall be made with arrows or circles (highlighting is not acceptable).
- 5. Shop Drawings: Drawings to include identification of project and names of Architect, Engineer, General Contractor, subcontractor and supplier, data, number sequentially and indicate the following:

- Fabrication and erection dimensions.
- b) Arrangements and sectional views.
- Necessary details, including complete information for making connections with other work.
- d) Kinds of materials and finishes.
- e) Descriptive names of equipment.
- f) Modifications and options to standard equipment required by the work.
- g) Leave blank area, size approximately 4 by 2 1/2 inches, near title block (for A/E's stamp imprint).
- h) In order to facilitate review of drawings, insofar as practicable, they shall be noted, indicating by cross reference the contract drawings, note, and specification paragraph numbers where items occur in the Contract Documents.
- i) Conduit/raceway rough-in drawings.
- j) Items requiring shop drawings include (but not limited to):
 - 1. Premise Distribution System
 - 2. UPS systems
 - 3. Communications System (Paging)
- k) See specific sections of Specifications for further requirements.
- Product Data: Technical data is required for all items as called for in the Specifications regardless if item furnished is as specified.
 - a) Submit technical data verifying that the item submitted complies with the requirements of the Specifications. Technical data shall include manufacturer's name and model number, dimensions, weights, electrical characteristics, and clearances required. Indicate all optional equipment and changes from the standard item as called for in the Specifications. Furnish drawings, or diagrams, dimensioned and in correct scale, covering equipment, showing arrangement of components and overall coordination.
 - b) In order to facilitate review of product data, insofar as practicable, they shall be noted, indicating by cross reference the contract drawings, note, and/or specification paragraph numbers where and/or what item(s) are used for and where item(s) occur in the contract documents.
 - c) See specific sections of Specifications for further requirements.
- C. PDS System Submittals
 - Typical wiring diagrams and risers. The Project Design Team shall include in the project drawings a PDS riser diagram showing originations, destinations, and type of pathways to be installed for all cabling. A copy of the As-built of this riser shall be submitted.
 - 2. Shop Drawings: Submit plan of building(s) and site showing pathways with all installed cables and pathways noted.
 - Detailed floor plan layouts and riser diagrams showing system components and their location, interconnections, wiring/cabling, and interface and connection with other disciplines.
 - Submit typical outlet wiring diagram, plan of building(s) and site showing pathways with cable noted, detail drawings of each of the facilities terminal

boards/cabinets, and equipment rack elevations to include all MDF and IDF locations

- 3. Coordination Drawings in accordance with the requirements of Division
- 4. Detailed data as requested by designer/OAR.
- Product Data: Submittals shall include manufactures cut sheets for all proposed equipment including, but not limited to, the following:
 - a) All wire and cable.
 - b) All connectors and required tooling.
 - c) All termination system components for each cable type.
 - d) All IDF equipment frame types, hardware and LAN equipment if part of this project.
 - All cable suspension j-hooks, cable fasteners, CAT6 cable suspension components.
 - f) All grounding and surge suppression system components for the systems portion of the project.
 - g) All outlets, devices and accessories.
 - h) Detail drawings of each of the facilities terminal boards/cabinets, and equipment rack elevations for all MDF and IDF locations.
- 4. Manufacturer's Certificate: Certify that products meet or exceed specified requirements.
- Test Equipment: Submit a letter, signed by an officer of the company, that indicates what
 test equipment the company owns and shall use for accomplishment of the test
 procedures required in these specifications.
- 6. Submit labeling scheme and sample of label.
- 7. Contractor shall submit test reports, manufacturer's specification sheets and any other information necessary to determine compliance with material and equipment specifications described herein.
- D. Communications System Submittals
 - Shop Drawings: Submit plan of building(s) and site showing pathways with all installed cables and pathways noted.
 - a) Narrative of operation of System as provided. (Submittal will not be reviewed by the A/E without this narrative.)
 - b) Detailed floor plan layouts and riser diagrams showing system components and their location, interconnections, wiring/cabling, and interface and connection with other disciplines.
 - c) Coordination Drawings in accordance with the requirements of Division
 - d) Detailed data as requested by designer/OAR.
 - e) Manufacturer's data on all products, including but not limited to:
 - 1. Catalog cut sheets.
 - 2. Roughing-in diagrams.
 - Installation instructions. Indicate application conditions and limitations of use stipulated by product testing agency. Include instructions for storage,

handling, protection, examination, preparation, installation, and starting of product.

- 4. Operation and maintenance manuals.
- 5. Typical wiring diagrams and risers.
- f) Point to point wiring diagrams with UCI (unique cable identifier) for all cables associated with communications system. Utilize existing cable numbers where available on cable being reused and re terminated.
- g) Updated equipment rack elevations reflecting exact equipment location and designations.
- h) Updated audio system matrix reflecting final equipment connections.
- The Contractor shall submit the following documentation within 30 calendar days after Notice to Proceed:
 - a) Shop drawings
 - b) Manufacturer product data cut sheets on all equipment cabling and products.
 - c) Overall system description and analysis.
 - d) Contractor shall develop with the Owner, a microphone/zone assignment table. Contractor shall provide initial draft for review and continue to develop table for final approval.
- The Contractor shall submit the following documentation within 30 calendar days after Notice to Proceed:
 - a) Cutover plan
- 4. Test plans and procedures shall be submitted for the following tests:
 - Contractor's Initial Field Tests of field devices and cabling.
 - b) Performance Verification tests.
 - c) Submit 45 days before testing.
- E. Grounding for Communications Systems
 - 1. SUBMITTALS
 - a) Submit catalog cut sheet showing brand and selection for all conductors, test wells, components, etc., as specified herein showing that all materials are UL listed and labeled as applicable and manufactured in the United States.
 - b) Product data shall prove compliance with Contract Documents, National Electrical Code, Underwriters Laboratories, manufacturers' specifications, manufacturers' written installation data and compliance with all performance criteria.
 - c) Include instructions for storage, handling, protection, examination, preparation, operation and installation of product.
 - d) Indicate application conditions and limitations of use stipulated by product testing agency specified under regulatory requirements.
 - e) Show all dimensions, colors, configurations, covers and applicable labeling/stamping.
 - f) Record actual locations of grounding electrodes on red lined as-built documents.

Submit test results of each ground rod. See Section 16090 Tests and Performance Verification.

1.5 PROCESSING SUBMITTALS

- A. Submit under provisions of the General Requirements of the Contract and this section of the Specifications, whichever is the most strict.
- B. Quantity of submittals with marking on each copy shall be submitted under provisions of General Requirements of the Contract, Division 1, and this and other sections of the Specifications. Original submittal must contain 3-ring binders with:
 - 1. Project Addresses
 - 2. Index
 - 3. Separation Sheets
 - 4. Basic Materials
 - 5. Panelboards
 - 6. Light Fixtures
 - 7. Long Lead Items
 - 8. Systems Product Data
- C. Remainder of submittals are to be submitted no later then 60 days after award of contract or 60 days prior to Request for Substantial Completion whichever is earlier.
- D. The Contractor shall review all submittals before submitting to the A/E. No request for payment will be considered until the submittals have been reviewed and submitted for approval.
- E. Product Data: For standard manufactured materials, products and items, submit one (1) copy or sets of data (per binder). If submittal is rejected, resubmittal shall contain same quantity of new data.
- F. Shop Drawings: For custom fabricated items and systems shop drawings, initially submit a transparency (suitable for reproduction) together with two (2) prints made therefrom. When submittal is acceptable, furnish one (1) print per binder made from the accepted transparency.
- G. Shop Drawing Review Notation.

	Action	<u>Description</u>
1.	No Exception Noted	No exceptions taken. Resubmittal not required.
2.	Rejected	Not in compliance with Contract Documents. Resubmit.
3.	Submit Specific Item	Resubmit item as specified.
4.	Make Corrections Noted	Make corrections noted, resubmittal not required.
5.	Revise and Resubmit	Make corrections noted, resubmittal is required
6.	Review not Required	Not required for review. No action taken. Copy retained for reference.

H. Acceptance: When returned to Contractor, submittals will be marked with A/E's stamp. If box marked "Rejected" "Revise and Resubmit" or "Submit Specific Item" is checked, submittal is not accepted and Contractor is to correct and resubmit as noted, otherwise submittal is accepted and Contractor is to comply with notation making necessary corrections on submittal. Review comments will generally not be on each individual submittal sheet, and will be on a separate sheet attached to shop drawing transmittal, submittal as a whole or each

submittal section.

Note that the acceptance of shop drawings or other information submitted in accordance with the requirements specified above, does not assure that the Engineer, Architect, or any other Owner's Representative, attests to the dimensional accuracy or dimensional suitability of the material or equipment involved, the ability of the material or equipment involved or the Mechanical/Electrical performance of equipment. Acceptance of shop drawings does not invalidate the plans and Specifications if in conflict, unless a letter requesting such change is submitted and accepted on the Engineer's letterhead.

1.6 PROJECT RECORD DOCUMENTS

- A. Submit in accordance with Section 27 05 00 Common Work Results for Communications and Section 27 01 00 Operation and Maintenance Manuals for Communications.
- B. In addition to the requirements above, the Contractor shall submit:
 - 1. Record actual locations and sizes of pathways, terminal blocks, etc.
 - 2. Record actual type and size of cables installed.
 - 3. Record "to and from" locations coordinated with cable labeling for all cables at each terminal block or cabinet.
 - 4. Cross-connects "to and from location" terminations for each cable connection.
 - 5. Provide detailed documentation of the distribution system to facilitate system administration, system maintenance and future system changes. This requirement includes as-built drawings, detailed cable drawings, with all cables and terminations identified, a bill of materials of all installed equipment and wiring, rack and backboard equipment layouts showing placement of support equipment, and model and serial numbers of all installed equipment (cables, connectors, secondary clocks, etc.). A clear and consistent nomenclature scheme is to be defined and used on the documentation and the cable labeling which facilitates locating and identifying each cable.
 - Cable Route Diagram: Provide locations and routes of "as-built" cable system and include:
 - a) End points.
 - b) Cable routing.
 - c) Splice points.
 - d) Terminations (connector type).
 - e) Cable lengths (include slack).
- C. Drawings required herein are in addition to those required under Operation and Maintenance Data.

1.7 DELAYS

A. Contractor is responsible for delays in job progress accruing directly or indirectly from late submissions or resubmissions of shop drawings, or product data.

1.8 RE-SUBMITTALS

A. The A/E shall be reimbursed for all costs to review resubmittals subsequent to the second submission for the same product. Cost will be billed to Contractor at Engineer's standard hourly rate.

PART 2 - PRODUCTS - Not Used

PART 3 - EXECUTION - Not Used

SUBMITTALS
FOR COMMUNICATIONS SYSTEMS - ADDENDUM #2

END OF SECTION

PROJECT ADDRESSES

OWNER:	
ARCHITECT:	
ENGINEER:	Matern Professional Engineering, P.A.
	130 Candace Drive Maitland, Florida 32751 Telephone No.: (407) 740-5020 Fax No.: (407) 740-0365
GENERAL CONTRACTOR:	
SUBCONTRACTOR:	

SECTION 27 41 31 - COMMUNICATIONS SYSTEM (PAGING)

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

A. Drawings and general provisions of the contract, including general and Supplementary Conditions and Division 01 Specification Sections, apply to this section.

1.2 GENERAL

- A. The work described herein and on the drawings consists of all labor, materials, equipment, and services necessary and required to provide and test a Local Area Sound System(s) (hereinafter referred to as "system" or "sound system). Any material not specifically mentioned in this specification or not shown on the drawings but required for proper performance and operation shall be provided.
- B. The drawings and specifications herein comply to the best of the Engineer's knowledge with all applicable codes at the time of design. However, it is this Contractor's responsibility to coordinate/verify (prior to bid) the requirements of the Authority Having Jurisdiction over this project and bring any discrepancies to the Engineer's attention at least seven (7) days prior to bid. No changes in contract cost will be acceptable, after the bid, for work and/or equipment required to comply with the Authority Having Jurisdiction.
- C. The Contractor is advised that circuit routing for this system is not shown on the project drawings. The Contractor shall provide and install all raceways, wiring and cabling required for a complete and fully functional system as intended by these specifications. Contractor shall provide and install a properly sized, flush mounted outlet box for every device with appropriate raceway to accessible location above ceiling. Contractor shall size and route raceways to accommodate the proper installation of the system cabling. In locations where raceway and/or conduit is not accessible after completion of the project, and in non-ceiling areas, and in exposed locations, cabling shall be installed in appropriate raceway system complete to concealed/accessible location and/or termination equipment. Connect each device as required to perform requirement specified herein and/or on the drawings. Contractor shall properly terminate each device according to the manufacturer's recommendations. Provide and install firestopping where penetrations are made through rated walls and floors.

1.3 BID ADDITIVES

A. Additive #1:

Includes replacement of existing exterior ceiling speakers. Contractor shall reuse all
existing wiring and rework speaker mounting as require to install the new speaker.

B. Additive #2

- Includes demolition of existing hall d speaker cluster and installation of new distributed speakers system with associated support, conduit, cabling, and additional I/O frames and amps.
- Refer to Audio System Matrix attachment for additional information.

1.4 DESCRIPTION OF SYSTEM

- A. The Contractor shall furnish and install a complete replacement Sound System(s) capable of receiving signals from any system input (mic, line, content), and broadcast to individual rooms, paging zones, or entire campus. The system shall include but not be limited to:
 - 1. Core processors

- 2. I/O Frames
- Power amps
- 4. Audio Patch Panels
- Output provisions of 70.7V constant voltage lines.
- 6. Volume controls
- 7. Microphone and line input / output outlets.
- 8. Paging Stations
- Surge suppression equipment on power source
- 10. Raceway/outlet system, wire, cable, etc., complete with all basic materials
- 11. Wire and cable labeling
- 12. Terminal blocks
- 13. Terminations
- 14. Grounding
- 15. Surge suppression
- 16. UPS
- 17. Firestopping
- 18. Network Electronics
- 19. Telephone interface
- 20. Rack/cabinet cooling equipment
- B. The system is to include all equipment, materials, and labor as required to provide, install and test a complete system as described herein.
- C. System is to provide for distribution to local speakers all paging and/or emergency all-call signals originated from DTMF type telephone system, by zone (to be coordinated with existing paging zone designations).
- D. System is to provide for distribution to all speakers all local microphones and/or input signals.
- E. System to be controlled by two main control rooms. Each capable of controlling entire campus.
- F. Special Requirements for Cable Routing and Installation:
 - The majority of speaker wiring within buildings will be installed above ceilings. All cabling
 used throughout this project shall comply with the requirements as outlined in the
 National Electrical Code (NEC). All cabling shall bear CMP and/or appropriate markings
 for the environment in which they are installed.
 - 2. Sealing of openings between floors, through rated fire and smoke walls, existing or created by this Contractor for cable pass through shall be the responsibility of the Contractor. Sealing material and application of this material shall be accomplished in such a manner which is acceptable to the fire and building Authorities Having Jurisdiction over this work. Creation of such openings as are necessary for cable passage between locations as shown on the drawings shall be the responsibility of the Contractor's work. Any openings created by or for this Contractor and left unused shall also be sealed as part of this work.
 - 3. The Contractor shall be responsible for any damage to any surfaces or work disrupted as

- a result of his work. Repair of surfaces, including painting, shall be included as necessary.
- Maintain proper separation between system cables and all power and/or unshielded cables, as required to prevent noise, crosstalk, etc.

G. Surge Suppression:

- Provide and install all materials, labor and auxiliaries required to furnish and install
 complete surge suppression for the protection of building electronic equipment systems
 from the effects of induced transient voltage surge and lightning discharge as indicated
 on drawings or specified in this section.
- 2. See Specification Section 26 05 26 Surge Protective Devices for surge suppression equipment required for 120 VAC and above circuits.

1.5 STANDARDS, CODES, REFERENCES, AND REGULATORY REQUIREMENTS

- A. Reference Section Reference Standards and Regulatory Requirements.
- B. The equipment and installation shall comply with the current or applicable provisions of the following standards:
 - 1. All requirements of EIA/TIA.
 - 2. All requirements of Federal Communications Commission.
 - 3. National Fire Protection Association Standards NFPA 70 National Electrical Code
 - 4. UL 13 Power-Limited Circuit Cables
 - 5. UL 444 Communications Cables
 - 6. UL 1449 3rd Edition Standard for Safety for Surge Protective Devices
- C. Furnish products listed and classified by Underwriters Laboratories, Inc. as suitable for purpose specified and show.

D. Surge Suppression

- Equipment Certification: When available by any one manufacturer, all surge suppression equipment shall be listed by Underwriters' Laboratories, shall bear the UL seal and be marked in accordance with referenced standard. Such surge suppression equipment shall be UL listed and labeled for intended use.
- 2. Comply with all standards and guides as listed under "References" above.

1.6 RELATED SECTIONS/DIVISIONS/DOCUMENTS

- A. All applicable sections of Division 0 and Division 1.
- B. All applicable sections of Division 26 & 27

1.7 QUALITY ASSURANCE

- A. Manufacturer: Company specializing in manufacturing the products specified in this section with minimum ten (10) consecutive years experience and with service facilities within 50 miles of Project.
- B. Supplier: Authorized distributor of amplifier/control equipment manufacturer.
- C. Installer:
 - Company specializing in installing the products specified in this section with minimum 10 years experience.
 - 2. The installing Contractor shall be a direct sales division of, or the authorized and

designated distributor for the amplifier system manufacturer.

- Installer shall have staff on site which have completed the highest level factory installer training provided for the system being installed.
- 4. Installing Contractor shall maintain a local staff of specialists, including a Superintendent, for planning, installation, and service.
- 5. The installing Contractor shall maintain an office within fifty (50) miles of the project with capability to provide emergency service. The installing Contractor shall have been actively engaged in the business of selling, installing and servicing sound systems of similar scope for at least ten (10) consecutive years going back from date of bid.

D. Surge Suppression

- All surge suppression devices shall be manufactured by a company normally engaged in the design, development, and manufacture of such devices for electronics/communications systems equipment.
- 2. The surge suppressor manufacturer shall offer technical assistance through support by a factory representative and local stocking distributor.
- 3. Coordination/Project Conditions
 - a) Verify proper grounding is in place.
 - b) Verify proper clearances, space, etc. is available for surge suppressor.
- E. To establish the type and operating characteristics of the Local Area Sound System(s), the equipment specified herein is used as a guide in determining the functions of the system. Other equipment will be considered for acceptance provided the following is submitted in writing by the system installer to the Engineer (See Section Substitutions):
 - 1. Contractor qualifications (as listed above).
 - 2. Complete lists, descriptions and drawings of materials to be used.
 - A complete drawing showing conduit, conduit sizes, backboxes, number of wires and wire sizes.
 - 4. A complete riser diagram of the Local Area Sound System(s).

1.8 SUBMITTALS

 Submit in accordance with Section 27 05 00 Common Work Results and Section 27 05 07 Submittals.

1.9 PROJECT RECORD DOCUMENTS

A. Submit in accordance with Section 27 05 00 Common Work Results and Section 27 01 00 Operation and Maintenance Manuals.

1.10 WARRANTY

- A. The Contractor shall warrant the equipment to be new and free from defects in material and workmanship, and will, within one year from date of acceptance by owner, repair or replace any equipment found to be defective.
 - 1. No charges shall be made by the installer for any labor, equipment, or transportation during this period to maintain functions.
 - 2. Respond to trouble call within twenty-four (24) hours after receipt of such a call.
- B. The Contractor shall guarantee all wiring and raceways to be free from inherent mechanical or electrical defects for one (1) year from date of final acceptance of the system.

- C. The Manufacturer shall warrantee the new Communications System for a period of 5 years
- D. Surge Suppression
 - 1. All surge suppression devices shall be warranted to be free from defects in materials and workmanship for a period of five (5) years.
 - Any suppressor which shows evidence of failure or incorrect operation during the warranty period shall be repaired or replaced by the manufacturer and installer at no cost to the owner.

1.11 MAINTENANCE SERVICE

- A. Furnish service and maintenance of Local Area Sound System(s) for one (1) year from date of Substantial Completion.
 - No charge shall be made by the installer and/or Contractor for any labor, equipment, or transportation during this period to maintain functions.
 - 2. Respond to trouble call within twenty-four (24) hours after receipt of such call.

1.12 SPARE PARTS

- A. The following spare parts shall be provided:
 - 1. (5) of each type of I/O card
 - 2. (5) 70V Amplifiers
 - 3. (2) Paging Stations
 - 4. (4) Amp Patch Bays
 - 5. (4) 1/4" Patch Bays
 - 6. (2) each type of I/O frame

1.13 OWNER'S INSTRUCTION:

- A. Training of OCCC personnel (a minimum of 10) shall be provided.
 - 1. OCCC select personnel shall be factory certified and trained on system being installed.
- B. Training to cover the operation, location, nomenclature, documentation, documentation maintenance procedures, a "walk-through" for location and labeling orientation, operation of equipment installed as part of the contract, test documentation, and troubleshooting of the system.
- C. Provide instruction to the Owner's designated personnel upon completion of the system installation.

PART 2 - PRODUCTS

2.1 GENERAL EQUIPMENT AND MATERIAL REQUIREMENTS

- A. All equipment shall be new and unused. All components and systems shall be designed for uninterrupted duty. All equipment, materials, accessories, devices, and other facilities covered by this specification or noted on the contract drawings shall be the best suited for the intended use and shall be provided by a single manufacturer.
- B. Provide all components, equipment, parts, accessories and associated quantities required for complete installations. All components may not be specified herein.
- C. All devices/components/products shall be suitable for use intended, and meet all stated performance requirements for Sound System(s) specified in this section.
- D. All audio equipment shall be from the same manufacturer. No exceptions noted.

- E. System shall operate on Layer-3 TCP/IP Network
- F. Coordinate with owner for all assignment of IP address information for configuration of the system components.
- G. Manufacturers:
 - 1. Basis of Design:
 - a) QSC Qsys System or Approved Substitution as noted below
 - 2. Approved Substitutions
 - General: When submitting on approved substitution contractor must provide additional information as noted in section 27 05 07 Submittals for Communications Systems.
 - b) Approved System Substitutions
 - 1. IED (Innovative Electronic Designs) GLOBALCOM System
 - 2. BiAMP Tesira System

2.2 RACEWAYS

- A. General:
 - All raceways (conduit, wireways, pullboxes, outlet boxes, etc.) shall comply with applicable requirements of sections within Divisions 26 & 27 of these specifications.
- B. Conduit: Comply with Section 26 05 33 Conduit except as noted below:
 - 1. Pull Cords: Install pull cords in all raceway runs that are installed without cable.
 - 2. Size: Minimum size shall be 3/4" conduit.
- C. Bridle Rings
 - 1. Provide size as required for cables, with a maximum fill of 50% cross-area.
 - 2. Provide mounting/fastener type as required for installation.
 - 3. Manufacturers: Caddy Series #2B/4B or acceptable substitution.
- D. Boxes:
 - 1. All outlet boxes, junction boxes, pull boxes, etc. shall comply with applicable section of these specifications.
 - Boxes shall be sized as required by the system manufacturer and NEC for cables and/or device installed.

2.3 WIRE AND CABLE

A. Where existing cabling is required to be extended to terminate at new equipment contractor shall match existing cable type and size. All termination shall be at terminal blocks.

2.4 POWER AMPLIFIERS

- A. 4 channel amp 70V
 - 1. The amplifier shall contain all solid-state circuitry, using complementary silicon output devices. The amplifier shall operate from 50–60 Hz AC power and shall draw 925 VA or less when driven with random program material at 1/8 of rated power into 4-ohm loads. The amplifier shall have a 320-C19 16A IEC mains connector and shall be equipped with a removable power cord having a standard NEMA AC plug. The amplifier shall operate safely from a 15A 120V AC outlet, and shall comply with FCC part 15 Class B

requirements.

- 2. The amplifier shall have internal heat sinks cooled by forced air, driven by a 24-volt DC fan whose speed shall vary in response to heat sink temperatures to minimize acoustic noise. The fan's speed shall be controlled by a drive voltage ranging from approximately 9 volts when cool to approximately 24 volts when at the upper ranges of its operating temperature. Air flow shall be from rear to front to avoid temperature rise inside equipment racks; rack mounting of multiple amplifiers shall be possible without clearance for ventilation. The amplifier shall be capable of continuous operation at 1/3 of rated power into 4-ohm loads, in ambient temperatures up to 104° F (40° C).
- 3. The amplifier shall contain four independent amplifier channels powered by a low-impedance switching power supply. All amplifier protection systems shall be synchronized and self-resetting upon removal of fault. Each channel shall have circuitry to protect against short circuits or mismatched loads. Each channel shall independently monitor heat sink temperature and shall trigger fan speed boost, and if necessary, signal muting to prevent excessive temperature rise. Both channels shall have synchronized on-off muting, acting for three seconds after turn-on, and within ¼ second after turn-off or loss of AC power. Each channel shall have DC fault protection for the load, consisting of a shutdown of the power supply. Each channel shall have an independent and defeatable clip limiter and a 12 dB per octave high-pass filter. The corner frequency of the filter shall be selectable between 50 Hz and 75 Hz.
- 4. The front panel shall contain these features: an AC power switch; LED status indicators for power (green), bridged mono (yellow), and parallel inputs (yellow); independent LED output metering indicators for each channel for signal present or −30 dB (green), -20 dB (green), -10 dB (green), and clip (red); and a recessed, detented gain control for each channel with 21 attenuation settings. From 0 to 14 dB, the attenuation steps shall be 1-dB increments. The labeled attenuation settings shall be 0, 2, 4, 6, 8, 10, 12, 14, 18, 24, and ∞ dB. The 0 dB attenuation settings shall also be labeled with the amplifier's equivalent voltage gain in dB. A removable security panel shall be provided for covering and preventing unauthorized access to the gain controls, when needed.
- 5. The output connectors for all channels shall be barrier strips located on the rear panel, with screw terminals and a safety shroud. One barrier strip shall be used for channels 1 and 2, and the other for channels 3 and 4. The terminals shall be arranged to facilitate bridged mono connection.
- 6. The inputs shall be located on the rear panel, and shall consist of a 3-pin detachable terminal block and a 3-pin XLR connector for each channel. The XLR input shall be wired with pin 2 high. Inputs shall be electronically balanced, with a minimum impedance of 12 kilohms balanced and 6 kilohms unbalanced, and a common mode rejection of at least 50 dB from 20 Hz to 20 kHz.
- 7. For each pair of sequentially numbered channels, a high-density 15-pin DataPort connector shall be provided for carrying both audio and amplifier operational status signals to and from a QSControl network. The DataPort shall also accommodate plug-in crossover filters and other such accessories.
- Also for each sequentially numbered channel pair, a set of DIP switches shall be provided on the rear panel for: setting bridged mono and parallel-input operation; selecting clip limiters; and selecting high-pass filters and setting their frequencies.
- 9. Each channel shall be capable of driving directly a 70-volt line at rated power, without requiring an output transformer. Each channel shall be capable of meeting the following performance criteria with all channels driven: Sine wave output power of 200 watts, 20 Hz to 20 kHz at <0.05% THD, with both channels driven at 70 volts; and 220 watts, 1 kHz at <0.1% THD with one channel driven at 70 Volts. Frequency response (with filters not</p>

engaged) at 3 dB below rated power shall be 20 Hz to 20 kHz ±0.2 dB. The voltage gain shall be 56.6x, equivalent to 35.0 dB, and the input sensitivity shall be 1.26 Vrms (+4.2 dBu). The unweighted signal to noise ratio over the range of 20 Hz to 20 kHz shall exceed 106 dB, referenced to full output. IHF damping factor shall exceed 500.

- 10. The amplifier chassis shall occupy two rack spaces and have provisions for securing the rear corners. Depth from mounting surface to tips of rear supports shall be 14 in. (35.6 cm). The amplifier's weight shall not exceed 21.0 lb. (9.5 kg).
- 11. Provide (2) 15-pin DataPort cable per connector on amplifier. (1) between amp and amp patch panel and (1) between amp patch panel and I/O Frame.
- 12. The amplifier basis of design: QSC Audio Products CX204V or approved substitution.

2.5 AV WALL PLATES

- Refer to details for additional information
- B. All existing cabling being reused shall be re-terminated on new wall outlet jacks.
- C. Basis of Design: FSR or approved substitution

2.6 VOLUME CONTROL

- A. Wall mounted volume controls:
 - 1. Provides volume adjustment via an optical rotary encoder with LED indicators.
 - 2. 0-10V Output for system integration.
 - 3. Shall be Brushed Stainless Steel.
 - 4. Shall install in a standard single gang decora outlet
 - 5. Basis of design: RDL #DS-RCX10R or approved substitution
- B. Volume control power supply
 - 1. Output Voltage: 24VDC
 - 2. Input Voltage: 115VAC
 - 3. (16) Class 2 rated PTC protected power limited outputs
 - 4. Removable terminal blocks with locking screw flange.
 - 5. Short Circuit and Thermal overload protection.
 - Filtered and regulated outputs.
 - 7. Provide with 3U rack mount chassis.
 - 8. (2) volume controls per output.
 - Basis of Design: Altronix #R1224DC16CB or approved substitution.

2.7 PAGING MICROPHONES

- A. Desktop Paging Mic:
 - Locations:
 - a) Security Offices (2)
 - b) Audio Control Rooms (2)
 - c) Marketing / Admin (1)
 - d) Mobile (2)

- Capacitive touch, programmable keypad and 240 x 64 graphics LCD for flexible customization
- 3. 16 fully programmable buttons
- 4. Fully compatible with all basis of design selection systems.
- 5. Second microphone input and GPIO allow one Page Station to serve two locations
- 6. Dual Ethernet connections support network redundancy
- 7. May use Power over Ethernet (PoE) or local power supply
- 8. Gooseneck desktop configuration
- 9. Basis of Design: QSC #PS-1650G or approved substitution

2.8 PATCH PANELS

- A. Patch Bay (AMP)
 - 1. 24 Channel Insertion Panel
 - 2. Front Connections: (24) 1/4" TRS Jacks
 - 3. Rear Connections: (24) HD15 Jacks
 - a) (12) Inputs from I/O Frame
 - b) (12) Outputs to Amps
 - 4. Normal mode shall allow all audio to pass thru patch panel.
 - 5. Bypass mode shall allow the input of a external signal thru the front TRS jacks to be transmitted to the associated power amp, disconnecting the input from the I/O Frame.
 - Basis of Design: Whirlwind #Custom (contact whirlwind sales rep) or approved substitution
- B. Patch Bay (1/4" TRS)
 - 1. 48 Port Patch Bay
 - 2. Front Connections: (48) 1/4" TRS Jacks
 - 3. Rear Connections: (48) wire terminals
 - 4. Match existing patch cable type for all front jacks.
 - 5. All inputs and output jacks with corresponding I/O Frame Inputs/Outputs shall be Half-Normal.
 - 6. All others shall be No Normal's
 - 7. Basis of Design: Whirlwind #ADC Pro Patch Patchbay or approved substitution

2.9 HEAD END EQUIPMENT

- A. General Requirements
 - 1. Equipment must have dual, fully redundant network connection on devices.
 - 2. DSP must use latest Intel multi-core processor chipsets
 - 3. Core processors shall automatically fail over upon a core failure.
 - 4. Shall operate on a fully layer 3 network protocol.

- 5. Must be manufactured in the USA.
- 6. All component firmware shall be monitored by the core processors. Individual update of firmware on every device shall not be required by the user.
- All paging functionality must be an iatrical part of the system components and shall not require addition add on hardware. Stand alone paging system with interface shall not be permitted.
- 8. All active components of the audio system shall be from same manufacturer.

B. Core Processor

- 1. The central core device of the network audio system shall perform all control, monitoring, and processing functions. It shall be based on the Intel® Xeon® processor platform and shall transfer audio data to and from the network's I/O devices. It shall manage control devices such as the modules and other control interfaces, recall snapshots, provide logic functions, and execute scripted commands.
- 2. The core device shall accommodate up to 256 input and 256 output network audio channel streams, as well as 512 network audio input channels and 512 network audio output channels. It shall offer up to 192 channels of automatic echo cancelation. On its rear panel shall be one slot for a Type 2 I/O card, capable of up to 64 input and 64 output channels, depending on the particular card installed.
- 3. The rear panel shall also have a DE-9 RS-232 port, an HD15 video output, two aux USB ports, two GPIO ports on DA-15 connectors, two RJ45 connectors for Network LAN A and LAN B, and two more RJ45 connectors for auxiliary non-QLAN networks. The power switch and IEC connector shall also be on the rear, and it shall operate on AC power ranging from 100 to 240 volts, 50 to 60 Hz.
- 4. The front panel shall have these indicators: a blue "Power" LED, a tri-color "Device Status" LED, and a 400 × 240 pixel True Color LCD graphics display. The front panel controls shall comprise a next-page and a previous-page button, a momentary device ID button, and a recessed "clear settings" switch.
- 5. The core device's enclosure shall mount in a standard 19-inch equipment rack, and it shall be 4 rack units (7 inches) high and 17.875 inches (454 mm) deep.
- 6. Provide with maximum storage to accommodate pre recorded messaging.
- 7. Basis of Design: QSC Q-Sys Core 3100 or approved substitution.

C. I/O Frame 1U

- 1. The I/O Frame is the system audio input and output device. The system shall operate on a native gigabit Ethernet network, employing DiffServ quality of service, IEEE 1588 audio clock synchronization, UDP/IP data transport, and floating-point format audio data representation. The overall system latency from analog input to synchronized analog output(s) shall be 2.5 ms or less. For routed networks, the end to end system latency shall be 3.2 ms or less.
- 2. The I/O Frame shall have the capability of being redundant. The I/O Frame can have a backup that has the same input source as the primary. The outputs of the backup are disconnected by relays, until a failover occurs, at which time the primary outputs are disconnected. Each I/O Frame shall have redundant "hot" network connections for seamless audio stream failover.
- 3. The I/O capacity shall be up to 16 analog input and/or output channels using any combination of the following: Mic/Line Input card (High Performance or Standard), Line Output card, DataPort Output card. The I/O capacity shall be up to 32 digital channels

using the AES-3 Input/Output card.

- 4. The I/O Frame shall have the following front panel controls and indicators: LCD page forward momentary switch, Unit ID momentary switch, Clear settings momentary switch, Power on blue LED, Device status tri-color LED, audio signal five tri-color LEDs per I/O card slot, 240 x 64 monochrome LCD graphics display.
- The I/O Frame shall have the following rear panel connectors: RS232 DE-9 (male 9-pin D shell connector), GPIO DA-15 (female 15-pin D shell connector), Network LAN A and LAN B RJ45 1000 MBps only, line voltage connection for 100 VAC 240 VAC, 47 63 Hz.
- 6. The I/O Frame dimensions shall be: (HWD) 1.75" x 19" x 15" (44.45 mm x 482.6 mm x 381 mm
- Basis of Design: QSC Q-Sys 1U I/O Frame or approved substitution.

D. I/O Frame 2U

- The I/O Frame is the system audio input and output device. The system shall operate on a native gigabit Ethernet network, employing DiffServ quality of service, IEEE 1588 audio clock synchronization, UDP/IP data transport, and floating-point format audio data representation. The overall system latency from analog input to synchronized analog output(s) shall be 2.5 ms or less. For routed networks, the end to end system latency shall be 3.2 ms or less.
- 2. The I/O Frame shall have the capability of being redundant. The I/O Frame can have a backup that has the same input source as the primary. The outputs of the backup are disconnected by relays, until a failover occurs, at which time the primary outputs are disconnected. Each I/O Frame shall have redundant "hot" network connections for seamless audio stream failover.
- 3. The I/O capacity shall be up to 16 analog input and/or output channels using any combination of the following: Mic/Line Input card (High Performance or Standard), Line Output card, DataPort Output card. The I/O capacity shall be up to 32 digital channels using the AES-3 Input/Output card.
- 4. The I/O Frame shall have the following front panel controls and indicators: LCD page forward momentary switch, Unit ID momentary switch, Clear settings momentary switch, Power on blue LED, Device status tri-color LED, audio signal five tri-color LEDs per I/O card slot, 240 x 64 monochrome LCD graphics display.
- The I/O Frame shall have the following rear panel connectors: RS232 DE-9 (male 9-pin D shell connector), (2) GPIO DA-15 (female 15-pin D shell connector), Network LAN A and LAN B RJ45 1000 MBps only, line voltage connection for 100 VAC 240 VAC, 47 63 Hz.
- 6. The I/O Frame dimensions shall be: (HWD) 1.75" x 19" x 15" (44.45 mm x 482.6 mm x 381 mm
- 7. Basis of Design: QSC Q-Sys 2U I/O Frame 8s or approved substitution.

E. I/O Cards

- Mic/Line Input Card
 - a) Four channels of microphone / line-level analog audio input with 48V phantom power and high performance pre-amplifiers
 - b) Four 3-Terminal Euro-style detachable connector terminal blocks.
 - c) Basis of Design: QSC Qsys #CIML4-HP or approved substitution

Line Output Card

- a) Four Channels of balanced, line level analog outputs
- b) Four 3-Terminal Euro-style detachable connector terminal blocks
- c) Basis of Design: QSC Qsys #CLO4 or approved substitution
- 3. DataPort (AMP) Output card
 - a) Four audio output channels (2 Data Ports) for connection to DataPort equipped amplifiers.
 - b) Two 15-Pin HD15 connectors
 - c) Basis of Design: QSC Qsys #CODP4 or approved substitution

F. IO 22 (Mobile IO)

- 1. Provide (2) for owners use
- 2. Shall be configured to connect to any active county LAN outlet allowing transmission and reception of net work audio.
- 3. Mobile IO allowing for:
 - a) (2) mic/line inputs
 - b) (2) Line outputs
 - c) (2) GPIO
 - d) Dual LAN GBit Ports
 - e) Basis of Design: QSC Qsys #I/O-22 or approved substitution

2.10 Network Electronics

A. Network Switches

- Provide 48 Port POE network switch for dedicated A/V system network LAN A and LAN B (as required).
- Uplink medium to be SM fiber and be routed to respective building core switch.
- System network tie to campus building systems LAN to be provided by contractor.
 - a) Coordination with OCCC IT / Smart City will be required for exact requirements and termination locations.
- 4. All network switches will be provided by the county and installed by the contractor.

B. Workstations (Control)

- 1. Provide workstations for system control at the following locations:
 - a) Audio Main Control rooms (2)
- 2. Workstation minimum requirements:
 - a) Core i7 Processor
 - b) 16GB DDR3 Ram
 - c) Graphics Card with 1GB Dedicated Video Memory and DVI output
 - d) 1TB SATA-III Hard Drive
 - e) Sound Card

- f) Gigabit Network Card
- System shall have (1) 32" computer monitor with multi-touch capabilities and a minimum WQHD (2560 X 1440 native) resolution.
- 4. Shall be provided with desktop speakers for monitoring of audio system.
- Provide desktop gooseneck microphone for workstation computer for pre-recorded messaging recording.
- Computer shall be configured to provide owner with the capability to record, review, and schedule messages. Including which areas the messages will be heard.
- Workstation shall be configured to provide owner with the capability to view and control
 any aspect of the campus audio system. Each workstation shall be capable of switching
 between respective buildings for control.
- Workstation only will be provided by the owner and installed by the contractor. All other
 peripheral devices shall be provided and installed by the contractor.

C. Workstations (Messaging)

- 1. Provide workstations for system paging / messaging recording and scheduling at the following locations:
 - a) Admin / Marketing (1)
- 2. Workstation minimum requirements:
 - a) Core i7 Processor
 - b) 8GB DDR3 Ram
 - c) Graphics Card with 512GB Dedicated Video Memory and DVI output
 - d) 1TB SATA-III Hard Drive
 - e) Sound Card
 - f) Gigabit Network Card
- System shall have (1) 24" computer monitor 1080P (1920 x 1080 native) resolution.
- 4. Shall be provided with desktop speakers for monitoring of messages.
- 5. Provide desktop gooseneck microphone for workstation computer for pre-recorded messaging recording.
- Computer shall be configured to provide owner with the capability to record, review, and schedule messages. Including which areas the messages will be heard.
- 7. Workstation only will be provided by the owner and installed by the contractor. All other peripheral devices shall be provided and installed by the contractor.

2.11 EQUIPMENT CABINETS

- A. All equipment racks will be provided by the PDS system installer.
- B. All rack accessories will be provided by this contractor.
- C. Ventilation
 - 1. Provide new ventilation fans as indicated on rack elevations for all existing cabinets
 - 2. 2U Fan Unit
 - a) 100 CFM @ 27 dB

- b) Intelligent thermostatic proportional control
- c) Local and remote over temp notification, with local temperature display
- d) Connect to always on outlet of fan controller listed below.
- e) Basis of Design:
 - 1. 120V Model Middle Atlantic UQFP-4D or approved substitution
- 3. 10" Cabinet Exhaust fan
 - a) 10" 825 CFM @ 60 dB
 - b) Long life ball bearing design
 - c) Fan to be installed in the top of existing cabinets as indicated. Modify existing cabinets if required for fan installation.
 - d) Connect to controlled outlet on fan controller listed below.
 - e) Basis of Design:
 - 1. 120V Model Middle Atlantic BMF-FAN10 or approved substitution
- Fan Controller
 - a) Provide in all cabinets with 10" fan
 - b) (2) controlled fan outputs
 - c) (2) Always on convenience outlets
 - d) Proportional speed thermostatic control based on enclosure temp.
 - e) Basis of Design:
 - 1. 120V Model Middle Atlantic FC-2-215-1CA or approved substitution
- D. KVM Switch / UI
 - 1. 17" Hi-Res Monitor with keyboard and mouse
 - 2. Built-in 16 channel KVM switch
 - 3. Accessories:
 - a) Rack mounting kit
 - b) Server Adapters (1) per CPU being connected. Provide length as required.
 - 4. Basis of Design:
 - a) Network Technologies Incorporated #RACKMUX-D17HR-N-16DVIHD (provided by owner and installed by contractor)
- E. UPS
 - 1. 10KVA UPS
 - a) Input Voltage: 208V
 - b) Output Voltage: 208V
 - c) Provide web card with network connection and configuration to UPS for remote monitoring of status
 - d) Basis of Design:
 - 1. Liebert #GTX4-10000RT208 with PD2-108 Power Distribution Box (provided

by owner and installed by contractor)

e) PDU

- 1. Provide PDU (1) PDU in each cabinet with I/O Frames.
- 2. Shall be Zero-U full rack height with minimum (20) IEC320 outlets.
- 3. Provide IEC cables as required to connect equipment in cabinet.
- 4. Provide cable extension if required to reach UPS location in adjacent cabinet.
- 5. Connect PDU to 30A 208V output of UPS via L6-30R

2. Remote Management Software

- a) Provide manufacturer's software for remote monitoring of all UPS's associated with the audio system.
- b) Install software and configure for automatic e-mail alerts at both audio control workstations.
- c) Coordinate with OCCC for all e-mail alert recipients.
- d) Configure software to allow the operator to check the status of all UPS connected to monitoring software.

F. EXHIBIT HALL SPEAKERS

- 12" High-output Ceiling Loudspeaker System
- 2. 150W 70V transformer
- 3. 300W Power Rating
- 4. 1.75" Titanium Compression driver
- 5. 93 db SPL sensitivity
- 6. Provide all require mounting hardware.
- 7. Basis of Design:
 - a) QSC #AD-C1200 with AD-C1200BB enclosure or approved substitution

G. EXTERIOR SPEAKERS

- 1. 12" two way coaxial loudspeaker
- 2. 64W 70V transformer
- 3. 100W power handling
- 4. Quick disconnect phoenix connector
- 5. Provided with back box enclosure
- 6. Basis of Design:
 - a) EV Innovative Design #C12.2 Ceiling or approved substitution

H. TOUCH SCREEN CONTROLLER

- 1. 3.5", 320 x 240 LCD Touchscreen controller
- 2. RJ-45 10/100Mbps jack for connection to audio system network
- 3. Must fit a standard 2-gang outlet box
- 4. POE power

- 5. Capacitive touch screen
- 6. Completely customizable screen layout with ability to incorporate custom bitmap images
- 7. Basis of Design:
 - a) QSC #TSC-3 or approved substitution

PART 3- EXECUTION

3.1 INSTALLATION

A. General

- 1. Install equipment in accordance with manufacturer's instructions.
- 2. Install all equipment in appropriate enclosures.
- Install equipment, cables, and speakers as required to comply with all applicable
 requirements of the references and/or regulatory requirements called for under Part 1 of
 this section of specifications, as a minimum installation requirement. Exceed this
 minimum requirement when called for herein.
- 4. Install all electrical basic materials per applicable sections of these specifications.
- 5. Connect reproducers to amplifier with matching transformers.
- 6. Install system cabinets/racks in locations shown; arrange to provide adequate ventilation and access.
- 7. Properly ground system per applicable sections of these specifications.
- 8. Support raceways and cabinets under the provisions of Section 26 05 29 Hangers and Supports, and/or as required by manufacturer's instructions.
- 9. Install raceways to conform to applicable sections of these specifications.
- 10. Install system wiring and/or raceways away from any surface that may become hot, including and not limited to, hot water piping and heating ducts.
- 11. Install system wiring with at least 12 inches of separation from line voltage power wiring on parallel runs. Wiring crossing power circuits shall be at right angles. For metal enclosed electric light or power or Class 1 circuits, separation may be reduced as described in NEC latest edition. Increase separation if so required to comply with EIA/TIA referenced standards.
- 12. Special Requirements for Cable Routing and Installation:
 - a) The majority of speaker wiring within buildings will be installed above ceilings. All cabling used throughout this project shall comply with the requirements outlined in the National Electrical Code (NEC). All cabling shall bear CMP and/or appropriate markings for the environment in which they are installed.
 - b) Sealing of openings between floors, through rated fire and smoke walls, existing or created by this Contractor for cable pass through shall be the responsibility of the Contractor. Sealing material and application of this material shall be accomplished in such a manner which is acceptable to the fire and building authorities having jurisdiction over this work. Creation of such openings as are necessary for cable passage between locations as shown on the drawings shall be the responsibility of the Contractor's work. Any openings created by or for this Contractor and left unused shall also be sealed as part of this work.
 - The Contractor shall be responsible for any damage to any surfaces or work disrupted as a result of his work. Repair of surfaces, including painting, shall be

included as necessary.

- d) Maintain proper separation between system cables and all power and/or unshielded cables, as required to prevent noise, crosstalk, etc.
- 13. Terminate all cabling directly on equipment or provide rack mounted din rail kit with high density modular terminal strips to extend / terminate any field cabling.
- 14. Install all equipment at locations shown on drawings.
- 15. Connect all devices, outlets, speakers, etc. to equipment cabinet equipment as recommended by manufacturer(s).

16. Labeling

- All terminal blocks shall be labeled to indicate cable origination point and device being served.
- b) Provide phenolic engraved permanent labels on all amplifiers, I/O Frames, Patch Bays, Mobile I/O's, Paging Stations, and Core's indicating Device ID.
- Additional replaceable labels indicating Inputs, outputs, speaker circuits, etc shall be placed on all Amplifiers and Patch Bays
 - 1. Patch bays shall be labeled as indicated in Audio System Matrix for all I/O.
 - Additional information shall be included on patch bay labels when ports are connected to a piece of equipment. Label shall indicate equipment designation and channel number.
- d) All cabling terminate at any equipment shall have a permanent laminated label 6" from cable end indicating cable ID, cable designation, and location of other end termination.

17. Paging / Messaging

- Paging system shall have interface with existing DTMF telephone system and be configured to match existing telephone interface paging codes / zones.
 - Existing system has multi digit paging / zone interface with telephone system. Contractor shall extract and duplicate existing zones and codes from existing paging system.
 - With the combining of NSB and West Building some codes will be duplicated.
 To resolve this issue contractor shall code a (1) before the code for West
 building and (2) before the code for the NSB.
- b) Marketing / Admin Messaging station.
 - 1. This station shall be configured with the capability of locally recording, reviewing and scheduling messaging for the entire system.
 - 2. Operator shall be able to control all aspects of pre-recorded messages from this location.
 - 3. Operation shall be as follows:
 - (a) Operator shall record message.
 - (b) Message shall be played back locally for review.
 - (c) Once message has been accepted, operator shall be able to select from either a onetime event or repeating event on a calendar layout for message playback.

(d) Operator will then be able to simply click to select one, many or all paging zone for associated message to be played from a graphical layout.

c) Audio Control Paging Station

- This station shall be configured with the capability of locally recording, reviewing and scheduling messaging for the entire system.
- Operator shall be able to control all aspects of pre-recorded messages from this location.
- 3. Operator shall be able to recall all pre-recorded security messages from this location and select paging zone/s using programmable buttons.
 - (a) Contractor to coordinate with Security to determine standard Paging zones/groups to be programmed to the paging station buttons, in addition to using the paging codes as mentioned above from the paging station numerical keypad.
- 4. Operation shall be as follows when using schedules:
 - (a) Operator shall record message.
 - (b) Message shall be played back locally for review.
 - (c) Once message has been accepted, operator shall be able to select from either a onetime event or repeating event on a calendar layout for message playback.
 - (d) Operator will then be able to simply click to select one, many or all paging zone for associated message to be played from a graphical layout.
- 5. Operation shall be as follows when direct page:
 - (a) Operator shall record message.
 - (b) Once message has been accepted, operator shall be able to select from either a preset paging zone/group or enter a paging code for a specific area.
 - (c) Page will be played in selected zone/group.

d) Security Paging Station

- 1. This station shall be configured with the capability of locally recording and playing messages in selected zones.
- 2. Operator shall be able to recall all pre-recorded security messages from this location and select paging zone/s using programmable buttons.
 - (a) Contractor to coordinate with Security to determine standard Paging zones/groups to be programmed to the paging station buttons, in addition to using the paging codes as mentioned above from the paging station numerical keypad.
- 3. Operation shall be as follows:
 - (a) Operator shall record message.
 - (b) Once message has been accepted, operator shall be able to select from either a preset paging zone/group or enter a paging code for a specific area.

(c) Page will be played in selected zone/group.

e) Mobile Paging Station

- 1. This station shall be configured with the capability of locally recording and playing messages in selected zones.
- 2. This station shall be configured to reside on county LAN and be able to reside on any active network ports in the building.
- 3. Operator shall be able to control messages originating from this location and select paging zone/s using programmable buttons.
 - (a) Contractor to coordinate with owner to determine standard Paging zones/groups to be programmed to the paging station buttons, in addition to using the paging codes as mentioned above from the paging station numerical keypad.
 - (b) Control software shall be configure as to allow the operator to easily modify programmable paging station buttons for paging zones/groups as required per show. This shall be accomplished by simply clicking the zones to be included in the page and then assigning them to a programmable page station button at the station being used.
- 4. This device shall be auto discoverable when connected to the LAN system and shall indicate its availability with a flashing button on the GUI. When this button is selected the operator shall be able to utilize the I/O on the selected mobile device.
- 5. Operation shall be as follows:
 - (a) Operator shall record message.
 - (b) Once message has been accepted, operator shall be able to select from either a preset paging zone/group or enter a paging code for a specific area.
 - (c) Page will be played in selected zone/group.

18. Control Room Workstations

a) Equipment

- 1. Connect all equipment indicated above in a neat workmanlike manner at existing control room desks.
- 2. Workstation shall hold and run the audio system control software for the user interface and maintenance.
- UPS Management software shall be provided installed and configured on this workstation.
- 4. Monitor and speakers shall be desktop mounted
- b) Control Software Configuration (GUI)
 - General
 - (a) All inputs shall be configured with preset hard limiters and noise gates.
 - (b) All amplifier channels shall have independent EQ's and be preset for the physical environment acoustics assuming a mostly flat input signal, and should not required adjustment for system operation.
 - (c) System should include a 60 hz power line hum filter on all inputs which

- will be easily assignable as needed by the operator.
- (d) There shall be a preset button to return the system to a "resting state" which would be a default. This will remove any processing or routed beyond what will be considered the default set up.
- (e) This configuration shall be reviewed with the owner and engineer prior to completion and may be subject to change during construction. Coordinate with the owner for additional information and requirements.
- (f) GUI shall be generated with input from owner and engineer. This shall be submitted to the owner and engineer for review prior to substantial completion.
- (g) System will not be considered complete until owner has signed a acceptance of programming and configuration letter.
- (h) Contractor shall include in his bid (1) additional site visit for programming, to be completed within one year of project completion to address any changes or modification to the system configuration desired by the owner at that time.
- (i) NSB Main control shall have a default view of just the NSB with the option to also view the entire campus.
- (j) West Main Control shall have a default view of just the West Building with the option to also view the entire campus.
- (k) Coordinate with Engineer and Owner for graphics of the campus to utilize for GUI backgrounds.

2. Zoning

- (a) New audio system shall mimic current system zoning plan. Including but not limited to codes, graphics, and ease of use.
- (b) Inputs relative to a specific "zone" or room shall be defaulted to route audio and auto mix all inputs in the same room to the associated speakers.
- (c) User shall be able to easily combine and separate areas of the system thru the GUI. Typical group creation procedure shall be as follows:
 - (1) User shall select a "Create Group" button on the GUI followed by a selection of one or more areas based on the multilevel graphics of the building.
 - (2) Once all areas needed to be grouped together have been selected the user shall confirm group by selecting a "Confirm Group" button.
 - (3) This will now route and auto mix the defaulted inputs in the "zones" or rooms to the entire group now created.
 - (4) This group shall be able to be labeled, stored, and recalled both manually and automatically via a calendar style scheduler.
 - (5) The system shall have the ability to "un-group" any combined areas at any time via a menu to view all currently combined areas and selectively remove entire groups or edit current groups

Input routing

- (a) User shall be able to select any input and easily assign it to one or more "zones" "groups" or rooms (as indicated above) and have the input added to the auto mix for that area.
 - (1) User shall select an "Input Routing" button on the GUI followed by a selection of one or more areas based on the multilevel graphics of the building, or select from a list of predefined "Groups" and indicated above.
 - (2) Once all areas needed to be grouped together for this input have been selected, the user shall confirm group by selecting a "Confirm Input Routing" button.
 - (3) This will now route and auto mix the selected input audio to the assigned "zones" "groups" or rooms selected above.
 - (4) This configuration shall be able to be labeled, stored, and recalled both manually and automatically via a calendar style scheduler.
 - (5) The system shall have the ability to "un-group" any combined areas at any time via a menu to view all currently combined areas and selectively remove entire groups or edit current groups

4. Mobile I/O

- (a) User shall be able to locate and connect to either mobile I/O provided and connected to the county LAN.
- (b) Routing audio to and from this device shall be as indicated above and shall act as any other input or output to the system.
- (c) This device shall be auto discoverable when connected to the LAN system and shall indicate its availability with a flashing button on the GUI. When this button is selected the operator shall be able to utilize the I/O on the selected mobile device.

B. Pathway

General

- a) Provide and install raceway for all penetrations of fire rating assemblies/walls/etc., where exposed to damage, underground locations, interconnection of cabinets or any combination thereof, for all cables, and all areas required by applicable codes and standards or as otherwise noted/required in these specifications.
- b) Where acceptable to Authority Having Jurisdiction and all applicable codes/standards, cables above accessible ceilings may be run without raceways provided complete installation complies with all applicable codes/standards. Proper cable type, sleeves, firestopping, and support hardware must be utilized.
- c) All raceways shall meet requirement for raceway per Section 27 10 00 Premise Distribution Wiring System, in addition to applicable requirement of sections within Divisions 26 & 27 of these Specifications.
- d) All raceways shall terminate at point within 12 inches of termination point terminal block with appropriate grounding bushing.
- e) Raceway shall not be shared by power or any other electrical wiring that is not part of the low voltage sound systems.

- f) Bend raceway with minimum inside radius of 6 times the internal diameter. Increase bend radius to 10 times for raceway larger than 2 inch size. Provide proper bend for all changes of direction. Pull and splice boxes shall not be used in lieu of a bend.
- g) Install raceways so no more than two 90 degree bends are in any raceway section without pullbox. Install additional pullboxes as required to maintain maximum of two 90° bends between pullboxes and/or termination points.
- Label all raceway at both ends to indicate destination and sound system source room. Also indicate length of raceway and this labeling/identification shall be fully documented in as-built (record) drawings.
- i) Install polyethylene pulling string in each empty conduit over 10 feet in length or containing a bend.
- j) Properly support cables/wire not installed in raceways.
- k) Special Raceway Systems: Special raceway systems may be specified for some portions of the sound system. Refer to the drawings and other sections of these specifications to determine where or if such systems are used.

I) Firestopping

- 1. Where conduit penetrates a fire rated wall, floor, etc., firestopping shall be provided.
- 2. Provide permanent firestopping seals after cable installers have pulled risers and distribution cables.
- 3. Meet all requirements for UL assembly involved. Provide firestopping UL listed for assembly, conduit, and/or cable involved.

2. Horizontal Cable Pathway

a) Sleeves

- 1. Install rigid steel conduit sleeves with bushings on both ends at penetration of all walls above ceilings. Stub-out each side of wall a minimum of 12 inches.
- Install firestopping at sleeves and all rated firewall/smoke wall penetrations.
 Stub-out wall as required for routing. Firestopping assembly must comply with UL for wall routing, material and cable used.
- Size sleeves as required by the NEC for cable installed, but in no case shall sleeve be less than 2 inch diameter, nor smaller than that required by "4)" below.
- 4. Sleeve size shall not be smaller than that required by EIA/TIA-569, Table 4.1-1, "Conduit Sizing."

b) Cable Support

- Install J hooks located 48 inches to 60 inches on center above accessible ceiling areas for cable support.
- Where large quantities of cables are congested in an area such as near CC or CER, provide/install special supports designed to carry weight.
- 3. Size shall be as required to provide for cables installed plus 50% spare and still not exceed rating of support device.
- 4. Tie all cables to J hooks at all bends with ties accepted for use.

- Pullboxes, Splice (Junction) Boxes, Outlet Boxes
 - Install per applicable sections of these specifications and all applicable codes/standards.
 - b) Boxes shall be placed above accessible ceilings and in an exposed manner and location, and readily accessible. Boxes shall not be placed in a fixed false ceiling space unless immediately above a suitably marked and rated hinged access panel.
 - c) A pull or splice box shall be placed in a conduit run where:
 - 1. the length is over 100 feet,
 - 2. there are more than two 90 degree bends, or
 - if there is a reverse bend in the run.
 - d) Boxes shall be placed in a straight section of conduit and not used in lieu of a bend. The corresponding conduit ends should be aligned with each other. Conduit fittings shall not be used in place of pull boxes.
 - e) Outlet boxes shall be installed at speakers requiring outlet box per applicable codes/standards.
 - f) Provide bushed nipple at speakers receiving cable without raceway/conduit.
 - g) Every pullbox and/or splicebox shall have a hinged cover. Install appropriate access panel to allow cover to open.
 - h) Size
 - 1. Where a pullbox is required with raceway(s) smaller than 1-1/4 trade size, an outlet box may be used as a pullbox.
 - Where a pullbox is used with raceway(s) of 1-1/4 trade size or larger, the pull box shall:
 - (a) for straight pull through, have a length of at least 8 times the trade size diameter of the largest raceway;
 - (b) for angle and U pulls:
 - (1) have a distance between each raceway entry inside the box and the opposite wall of the box of at least 6 times the trade size diameter of the largest raceway, this distance being increased by the sum of the trade size diameters of the other raceways on the same wall of the box; and
 - (2) have a distance between the nearest edges of each raceway entry enclosing the same conductor of at least:
 - (i) six times the trade size diameter of the raceway; or
 - (ii) six times the trade size diameter of the larger raceway if they are of different sizes.
 - (c) for a raceway entering the wall of a pullbox opposite to a removable cover, have a distance from the wall to the cover of not less than the trade size diameter of the largest raceway plus 6 times the diameter of the largest conductor.
 - 3. Where a splicebox is used with raceway, it shall be sized per EIA/TIA latest edition, "Splice Box Sizing."
 - 4. No box shall be smaller than that required by NEC 314.71 (A)(B)(C).

C. Grounding

- Provide and install complete grounding system as required to comply with all sections of these specifications and applicable codes.
- 2. Connect Central Equipment to "systems" ground bus with #6 green insulated copper ground wire (in appropriate raceway).
- Connect metal conduit (via grounding bushing) to equipment cabinet or cabinet ground bus.
- 4. Connect cable shields to equipment cabinet ground busbar.
- Connect surge suppression equipment to equipment cabinet ground busbar.

D. Speakers

1. Each speaker circuit shall have a separate, splice-free cable homerun to the termination block in the sound system equipment cabinet.

E. Surge Suppression

1. General

- a) Provide and install surge suppression devices as specified in Section 26 43 00 Surge Protective Devices for 120 volt source to all equipment. Install on line side of equipment.
- b) Extreme care shall be taken by Contractor to assure a properly surge protected system.
- c) Surge protection equipment must be selected by Contractor to match the equipment being protected including wire sizes, operating volts, amps, and circuit impedance.
- d) Installation of surge protection equipment and it's grounding must be per manufacturer's recommendations to assure short and proper ground paths.

2. Equipment Selection

 a) Contractor to coordinate with suppliers and installers of all equipment being protected and provide surge suppression equipment which meets these specifications on respective equipment, wires, etc.

Equipment Installation

- a) Install surge suppression equipment per manufacturer's recommendation at each wire terminal as noted under Part 1.
- b) Install in surge suppression equipment terminal cabinets, etc. as required to facilitate installation of surge protection equipment and terminal points. Increase size of terminal cabinets (from that shown on drawings) to size required to facilitate installation of surge suppression equipment and terminal blocks.
- Locate surge suppression equipment in terminal cabinet nearest main equipment cabinet.

4. Ground Installation

- a) Ground Bus Connections:
 - 1. Provide "local" ground bus in equipment cabinet housing surge protection equipment (with lugs, etc. as required).
 - 2. Bond "local" ground bus to equipment cabinet with minimum #6 copper wire.

- Connect terminal cabinet "local" ground bus to systems ground bus installed per Section 26 05 26 Grounding and Bonding with minimum #6 copper insulated wire (unless otherwise noted) in conduit.
- 4. Note that "systems" ground bar is also to be used for power transformation ground (480V to 208V) where applicable.
- b) Surge Suppression Equipment Grounding:
 - Connect each surge suppressor to local ground bus in terminal cabinet with wire sized as recommended by manufacturer.

c) Conductors:

- Conductors shall meet requirements of Section 26 05 19 Building Wire and Cable.
- 2. Bends in excess of 90 degrees in any grounding conductor shall not be permitted. A radius of 6 inches or greater shall be maintained on all bends.
- 3. Do not bundle unprotected conductors with protected conductors.
- 4. Conductors shall be kept as short as possible.
- 5. Conductors shall be secured at 12 inch intervals with an accepted copper clamp.
- 6. Grounding conductors shall be properly connected to the building service ground by accepted clamps.

d) Grounding Connectors:

- Connectors, splicers, and other fittings used to interconnect grounding conductors, bond to equipment or grounding bars, shall be accepted by NEC or UL for the purpose.
- 2. All connectors and fittings shall be of the Nicopress crimp or compression set screw type.
- Special treatment to fittings, lugs, or other connectors of dissimilar material shall be applied to prevent electro-galvanic action.

F. Cable/Wire:

- 1. Splice cable only at terminal block units.
- 2. Make cable shields continuous at splices and connect speaker circuit shield to equipment ground only at building surge protection devices and at amplifier and/or as otherwise required by applicable codes.
- 3. Install input circuits in separate cables and raceways/pathways from output circuits.
- Install all cables no closer than 12 inches from any wire/cable installed for Premise
 Distribution System, power system cable/raceway, or fluorescent/ballasted light fixtures.
- 5. Leave 12 inches excess cable at each termination at speaker and termination blocks.
- 6. Leave 2 feet excess cable at each termination at system equipment/rack.
- 7. Provide protection for exposed cables where subject to damage.
- 8. Support cables above accessible ceilings to keep them from resting on ceiling tiles. Use J hooks to support cables. Do not share J hooks of Premise Distribution System. Provide quantity of J hooks as required to provide 50% spare capacity at all J hooks.
- 9. Use suitable cable fittings and connectors.

- 10. Install appropriate cable to match application, i.e., plenum, riser, etc. All cables shall bear CMP and/or appropriate marking for the application in which they are installed.
- 11. Cables routed through rated walls, floors and assemblies shall be routed via appropriate fireproofing system as accepted by UL.
- 12. Label cable at both ends indicating the originating and terminating location of each end. This labeling/identification shall be fully documented in as-built (record) drawings.

3.2 MANUFACTURER'S FIELD SERVICES

- A. Provide manufacturer's field services.
- B. Include making or supervising final wiring connections, inspection and adjusting of completed installation and systems demonstration.
- C. Certify that installation is complete and performs according to specified requirements.

3.3 ADJUSTING

A. Adjust transformer taps for appropriate sound level.

3.4 TEST AND PERFORMANCE VERIFACATION

- Test per applicable sections of these specifications.
- B. Measure and record sound power level.
- C. Refer to section 27 08 13 for additional requirements.

3.5 DEMONSTRATION

- A. Demonstrate system to designated Owner personnel as required by applicable sections of these specifications.
- B. Conduct walking tour of project. Briefly describe function, operation, and maintenance of each component.
- C. Provide detailed operation and maintenance instruction and training.
- D. Use submitted operation and maintenance manual as reference during demonstration and training.

END OFSECTION

SA1	2 5	200	2	SA	SA1	SAI	SA1	SA	SA1	SA1	SA1	SA1	SAI	SA1	SA.	SAT	SA.	SA	SA1	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE LINES	TIE-LINES	TELLINES	TELLINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	TIELLINES	TIELLINES	TIELINES	TIELINES	TIE-LINES	(IE-LINES	TIE-LINES	TELLINES	TELINES	TIELLINES	TIELLINES	TIEL INES	TIEL INES	TICLINES	TIEL INTO	TITL NIE	TEL NES	THE LINES	TIEL INEC		AM BEING SERVERO	DA DEING SED									
MIC 3 RKS02	ı	LINE RKS02			П	- 1		- 1	- 1			ш	_]	- 1	٠.	ı	- 1		- 1	- 1	- 1	- 1	- [- 1										TIE-LINE RKS	TIE-LINE RKS09	TIE-LINE RKS	THE-LINE PASS	TIE-LINE RXS	TIELINE RKS	TIE-LINE RKS	TIE-LINE RKS												1		1000	TIEL INE DIX	יובי ואה פעי	TIEL INE DIS	דור ואר סוגי	יוב ואב פעל	TIEL INE INC.	TIELLINE RESOL	TIC I NIC DV	2407	1170		I OTAL AMP CH	TOTAL AMB CU	TOTAL INPUTS
B 3	o a	A 24	A 23	> 23	A 21	A 20	A 19	A 18	A 17	A 16	A 15	A 14	A 13	A 12	A 11	> 0	Α Θ	> @	A 7	Α	A :	Α:	A 3	A 2	A -									G 24	G 23	6 22	G 21	G 20	G 19	G 18	G 17														,	2 6	3 6	3 5		3 6			-	JACA	CALION	П	ğ	2 2	546
PANEL 040	ANEL 040	ANEL 039	ANEL 039	ANEL 039	ANEL 039	ANEL 038	ANEL 038	ANEL 038	ANEL 038	ANEL 037	ANEL 037	ANEL 037	ANEL 037	ANEL 036	ANEL 036	ANEL 036	ANEL 036	ANEL 035	ANEL 035	ANEL 035	DANEI 035	PANEL 034	ANEL 034	ANEL 034	PANEL 034									FROM TECH SERVICES (F.O.)			The state of the s											NOW INCOME NOOM (T.O.)	FROM NORTH AMP ROOM (F.O.)	TROM NORTH AMP ROOM (F.O.)	FROM NORTH AMP ROOM (F.C.)	TROW NOT IT AMP NOOM (F.O.)	EBOW NORTH AMP SOOM (F.O.)	FROM NORTH AMP ROOM (F.C.)	FROM NORTH AMP ROOM (F.C.)	SPON NORTH AND DOOR OF OR		DESC / SOURCE	INPUTS										
																										RKS09	RKS09	TIE-LINE RKS09 H	RKS09	TIE-LINE RKS09 H	RKS09	TIE-LINE RKS09 H	RKS09									TIE-UNE RKS02 R		TIE-LINE RKS02 R						TIE-LINE RKS02 M					TIC INIC DISCO									KACK	-10				
																									ET TO TECH DESCRIPTION (C.O.)	24 TO TECH SERVICES (F.O.)	23 TO TECH SERVICES (F.O.)	22 TO TECH SERVICES (F.O.)	21 TO TECH SERVICES (F.O.)	20 TO TECH SERVICES (F.O.)	19 TO TECH SERVICES (F.O.)	18 TO TECH SERVICES (F.O.)	17 TO TECH SERVICES (F.O.)									24 TO TECH SERVICES	23 TO TECH SERVICES	22 TO TECH SERVICES	21 TO TECH SERVICES	20 TO TECH SERVICES	19 TO TECH SERVICES	24 TO NORTH AMP ROOM (F.O.)	23 TO NORTH AMP ROOM (F.O.)	22 TO NORTH AMP ROOM (F.O.)	21 TO NORTH AMP ROOM (F.O.)	TO NORTH AND DOOR OF O									PP JACK	N DESC/SOURCE	OUTPUTS						
																											-	and the state of t																																					LOCATION DESIGNATION C	AMP OUTPUT CHANNEL		NOB	100
20 20	20	20.2	20 2	0 2	0 2	2 2	1 2	12	2 2	12	0 2	0 2	2.2	2 2	2 2	2 2	1 2	1 2	12	12			2 2			1	0 2	0 2	0	0	201	20 ;	0 :	20 :	20 2	20	ZD.	Z	20	20 :	20	70	R	70	70	20	20 :	70 :	70	Zi :	2017	0 2	7	1 70	7	20	20	20	20		20	20			A DESC			NOB OCCUP AME ROC	`````
σ σ.	œ	RKS02 A 24	> >	> >	> >	>	A	A	A	>	• ;	> >	. A	. A	. ,	· >	 	>	. >	. >	<u> </u>	A	. A	. 3	> a	0	0 0	0 0	D C	D (20 (c	0 :	A :	Α;	Α.	>	>	Α.	> :	A	8	w	ω.	œ	w .	σ,	В (æ	1	D 0	ο α	000	000	>	Þ	Ĺ	Þ	>	>	Ĺ	A	Ļ			NEW PP LOCATION		OOM 305-431	**********
																																																					-											L	RACK I/O# INPUT	QSC			
																																																																CH	OUTPUT AMP OUT RAI	DI/O CONNECTION NEW AMP DE			
																																																																	CK AMP# CH	EW AMP DESIGNATION			

æ	8	SB	8	8	38	8 8	8	SB	8	88	8	æ	88	S S	8 8	8	B	S8	2	3	2	SAS	SAS	SA2	SA2	97.	200	SAZ	SA2	SAZ	S. C.	2 6	SAS	SA2	200	2	SAS	SAZ	242	2 6	3	SAS	SA2	¥.	2	2	SAZ	SA2	N.	2	8	SA2	S.	200	3	SA2	SE.	2	2	<u>S</u>	8	2 2	2	SA	SA		200	S	SA	3	2 3	2	SAI	SA	SA	3	2	SA	SA	SA1		AM BEING SERVERU	-	Ī	Ī			Ī	_
MIC	LINE	MIC	MIC	MIC	LINE	Sic.	NII.O	MIC C	N. C.	I N	MIC	MIC	MIC	LINE	1800	NIC.	MIC	MIC							-					_				LINE	MIC		MIC	MIC	CNE	1	1100	NIC.	MIC		310	E .	MIC	MIC	LINE	1	1	MIC	Mic	LINE	1111	MIC	MIC	MIC						_						2	MICS		MIC	Mic	Ę	MIC		N.	M.C	Ę		SEKVEKU I YEE		-		TOTALA	TOTAL OUTPUTS		TOTAL
-	RKS02		ı	ı	ı	1	П	1	П	- 1	- 1	- [ı	П	1			ı			1						1	-		ŀ	1	ĺ		1	1	١		l	1	ı	1			L	ı	Ī		ı	i	1				1		ı	NA.SUZ	1				1	-	_	-	1				1	- 1	- 1				П	- 1	- 1		1	1	1	-		PCH	PUTS		PUTS
02 E	02 E	02 E	02 E	Ω E	02	200	3 6	3 6	3 2	3	Ö D	02 D	0	Ö	200	3 6	Ö	02 D												Į			-		+	+	-	-	_	+	-	-+	_	_	+	+	-	_	-	+	+	_	-	+	+	_	-	202	+				1		_		+			a	DIVENSO DIVENS	3	S02 B	S02 B	S02 B	S02 B	9 6	3	802 B	S02 B	S P	LOCATIO		L	į	2	82	1	546
5		3 P/									- 1	- 1		4	1	- 1	- 1			L	-	1						-						20 P	3	3	18 P	17 P	16 P.	1		Į,	13 P	12 P.	3	1	0	9	8 P		7	6	5 P	4		ω V	2 P	-				I					ļ			I۳	7 -	٠١'	미	-1	-	1	1-		- 1	-	7.	1	L		1		_	Ī	
PANEL 024	PANEL 023	NEL 023	NEL 023	NEL 023	NEL 022	WEL 022	WEL OZZ	WEL OZZ	WILL OF	NET 031	NEI 021	NEI 021	NEL 021	NEL 020	WEL 020	NET OF O	NEI 020	NEL 020												!				ANEL 055	WEL 055	111111111111111111111111111111111111111	ANEL 055	ANEL 055	ANEL 044	WEL 044	200	ANE OAA	ANEL 044	ANEL 043	ANEL 043	ANIEL CAS	ANEI 043	ANEL 043	ANEL 033	PAGE 099	ANEL COO	ANEL 033	ANEL 033	ANEL 032	200	ANEL 032	ANEL 032	PANEL 032	*****											ANEL 042	PANEL 042	AND DAY	ANEL 042	ANEL 042	ANEL 041	ANEL 041	MINEL OF	ANE CA1	ANEI 041	ANEL 040		ESC / SOURCE	NPUTS						
																																																					_																													TYPE							_
Н	1		1			-	-			İ	Ì	1			-	-	1											1					l						-																				l		-	L	t				l				H		1		-	_		1	Ī		RA Ç	_		L	+				
H	1	+	-						-	1	+	+	+		F	+	+		_			+	1	1		_			1		_	l	+	1			+			-		+	1		-	+	+		_	-	+				-	+	_			1	_		+	1		ŀ	+	-			+	+	1	-	-		ŀ	+	+		PP L	LOCATION		-	+	-			
	1	1	+	1				-			+	1			_	ŀ	1	1		ŀ	L					_	-	l	1					+					_	-			1		 -				_	_						1	-		_		_														-	_		+			ACK.	DE	OTPU	-	+	$\frac{1}{2}$			
																																																																																		SC / SOURCE	OUTPUTS						
H	1			1	1								1	-					R.	곶	ᄌ	XX-201	2	2	Į.	굣	굣	3	2	굇	곳	굦	!		_	_							1				1	-	-		-	+				1		L	Z.		콧	7.	1	Q	낒	곶	3	2	낒		L		1	-	-			1	1	+	-	5	ļ	L	-				
																		1	-				l	ı	1				ı		i		ı																							i			7X-S01	ı			100	1	1			ı	-													CATION							
																			AMP-1B	AMP-1B	AMP-1A	AMT-7A	-10	AMD-19	AMP 18	AMP-17	AMP-17	AMP-10	AND 46	AMP-16	AMP-15	AMP-15																											AMP-14		AMP-14	AMP-13	VINIT-10	1010	AMP-12	AMP-12	AMP-11		AMP-11											-		DESIGNATION	AMP OUTPUT CHANNEL				Z.		
+	1	t		1	1	1				_		l	1	+				t	3	7	-	9	t	t	+	_	H	l	+	2	-	1											I				Ī					Ŧ				1	-		2	t	1	Н	-	t	1		7	†	•	_	-		1	1				ŀ	-	+		CH AR	CHANNE	F			SOC)	
	t	ł	1		1	+	-				-		ł	1					CX12	CX12	CX120	CX1Z	21.70	200	CHYO	CX12	CX12	CX12		CX1	CX12	CX12		1	-		ļ			_		-	1		_		ŀ	1	_			1	-			1				1	- 1			1	- 1			•	CY		F	ŀ		1				L	+	1		EA DESC		F			HA	!	
RKS02	200	7 7 7	2 2	2 2	070	낒	콨	굕	PKS	RKS	250	7.7	2	D.C.	꽀	RKS	132		NA PK	22V R.K.	DZV IRKS	2V RKS	NA.	200	No.	DV RKS	DZV RKS	ZV ZX		DV.	22V RX	02V RKS	77.77	0	RKS	RX.	232	D.	P.S	RK	R	3		DK.	RK	77.0		DV.	P.	RK	7.7.7		P.	몫	EX.		RX	P.	OZV RK		RV RX	OZV RK	77.		NOV BK	22V RX	02V XX	4.70	70 V	ZZ.	RKS02	7.7.7	1 2	0 2	묏	묏	R.C	3	2 3	5	1	RACK		H			NSB SOUTH AMP ROOM 305-431	;	
88	3 8	2	8 8	3 8	3 6	3	8	8	8	Š	02	202	1	31	ຮ	Ŝ	Š	3 F	Š	Š	ä	Š	200	3 8	3 1	ë	ž	Š		3	Š	ž	Š	3 8	Š	102	200	3	ŝ	ន័	902	Š	3 3	ŝ	ž	502	1	3	ő	őž	902	3 6	Š	ន័	02	Š	ŝ	ž	ž		ŝ	502	Ě	Š	3	82	502		3	8	92	202		3 6	3	รั	S02	502	3 8	3		웃	NEWP				<u>პ</u>	,	
m n	1	-	1	10	1	7	ᅦ	0	0	0	٥	c	,	2	0	0	c	, 5	2	3	2	3	2	2 2	2	2	2	2	2	3 9	3	2	c	1	ဂ	n	c	,	2	n	ი	c	1	7	ი	ი	,		2	ი	0	•	2	ი	n	,	0	ဂ	3	2	2	2	2		3	2	9	9	2	00	æ	α	,	0	20		σ.	Œ	, 0	-	1	용	NEW PP LOCATION	L			25.43	,	
υ 4	·	2	-	K	3	;	6	6	8	7	ი	u		•	ш	N	_	. 2	1					l	1				1	ĺ				3 2	19	18	1	1	ń	15	14	13	1	3	11	ة	4		2	7	6	,	ת	4	u	,	٥		~	1			,	ı	ı			l	1	12	=	ē	9	•	8	7	o	6				ğ	Š			ľ	_		
																		1000	DKSSS	RKS02	RKS02	RKS02	ZNOUZ	2002	000	PKSNS	RKS02	RKS02	7007	DK SOS	RKSO	RKS02																											RKS02	MAGOZ	RKSOO	RKS02	XXXVZ	77.002	DKSOS	RXS02	RKS02	77002	0000						1				Ī			RACK CK	1						
+	l	ŀ	ŀ	İ		+	1	1	-			-	l		-			2	2	2	2	91	S	2	2 5	3	2	2	-	2 9	2	9		+			-			_			-		_		-			-		l				+	1		01	5	2	2	9	2	2	2	2	2	2					+					ŀ	1	-	ğ	200						
T						T					-						ľ	T	Ì					T					ľ	İ											-	_	ŀ				ĺ	Ť				T				l			-		1	_		Ī	1	_		İ	Ì			l	l		1		_		l	9	5	NP C	00 CON		ŀ				ĺ
\dagger	İ				t	+	1	+				-	ŀ	1	1			-	†						+	1			t	+							l	1	+		_	-	ŀ	1			l	1				l	1	1			1			-	+			l	1	_	_	ŀ		1	-				\dagger	1			+	4	2	or P	QSC I/O CONNECTION						
\dagger						-	+	+					-	t	1		-	20	3 3	10	18	17	16	10	+	:	13	12	=	1	5	9					L	-	+				l	+				-							_		1		8		7	— Ф.	U			3	2	-		-			l	+	-				-	2		JT AMP	1	+					
+		H		\vdash	l		-	-	-			_		+		_		ĺ	1	1			Ĺ	ľ	1			Ĺ		ľ	+	-	L	1				1	1					-		_	-	1					1		_	1	1	-			1		L		1			F	1	-					1	1			-	ľ	- 9	OLI RAC	NG)						
-				_	L	+	-	-											-										L		+								1					1	_								1	4			\downarrow				1				1										1							^	NEW AMP DE						
+	L	Ц	_			-	1	-						+	+		_		+	+				-	ļ	-				+	+			-				+	1				L	-				-		-	_		-	-	_						+	_			-	-			1	$\frac{1}{2}$	-		-	+	1	\downarrow		_		+	7	AMP# CH	ESIGNAT	4					
_		Ш			L												_		L															L						ĺ	_		L			_																																_			-	2	2				_		

S-CATWALK	SCATWALK	SCATWALK	S-CATWALK	S-CATWALK	S-CATWALK	S CALWALK	2007	SCATINALK	SCATWALK	S-CATWALK	S-CATWALK	SCATWALK		SCATWALK	S-CATWALK	S-CATWALK	O CAT WATER	CATAVALA	SCATWALK	SCATWALK	S-CATWALK	88	8	ď	3 6	8	SB	SB	S. C.	86	O I	SB	SB	88	86	B	8	SB	SB BS	æ	88	8 6	8	SB	88	SB	6	3 6	S	88	88	SB	SB	S S	8	8 6	8 8	88	8	88	e e	8	8 6	6 6	SP	SB	SB	SB	8	3	8 8	8	8	8	88	SB		RM BEING SERVERD					7	
MIC 1	N C	MIC 2	MIC 1	LINE	MIC 2	MIC 1	E N	No.	100	2	C NE	MIC 2	SIC -	5	LNE	MIC 2	and C		N C	all o	MIC 1	_											_		l	-	LINE	MIC 3	MIC 2	MIC 1	CNE	300	100	Win o	MIC 1	LINE	MIC	MICZ	MIC 3	MIC 1	LINE	MIC 3	MIC 2	MIC 1	CINC	MICS		MICO	MIC 1	LNE	MIC 3	MIC 2	300	-	ž	MIC 3	MIC 2	MIC 1		100	100	100	MIC 1	LINE	MIC 3	MIC 2		ERD TYPE			0.00	OTAL AMP	TAL OUTPL	TOTAL INPUTS
RKS02	DKS03	RKSD	RKSO	RKS02	RKS02	RKS02	7000	BV 603	DV COS	DK SO	RKS02	RKS02	77002	Disco	RKS02	RKS02	ZNOO2	777002	מאלים בי	District	RKS02	1				1					Ī	1	_			11100	RKSOS	RKSOS	RKS02	RKS02	XX.VO.	1		- 1			1	TOO N	DKS	RKSO	RKS02	RKSO	RKS0	RKSO	RKSO	RNSOZ	0000	RKSO	RKS02	RKS02	RKS02	KKSUZ	NOO.	200	DVSN.	RKS02	RKSO	RKS0:	RKS02	NA.	2000	Diversi	RKSO	RKS0	RKS0:	RKS02	RACK			F	l	1		
z:	2 2	z :	z	z	z	z	2	2 2	2 :	z	z	Z	2		z	z	2	2	2 2	2 2		-	_		+	+	1			ŀ		+	_		ļ	+	+	7	_	Н	۰	-	+	-+	_	-	┰	+	+	-+	_	-	-	 	+-	1	+	-	-	\vdash	⊢	-	+	+	+	-	-	-	⊢	+	+	+	~ m	_	-	٠.	P	CATIO		L	15	2	82	546
19 PAN	0 7	17 0	G DAN	15 PA	14 PAN	13 PAN	TAN	3 2		5	9 PAN	8 PAN	· FAS	4					2 2		2	-		L	-	+					-	-			-	2	0	15 PA	14 PAI	13 PAI	12 PA	174		5	9 P	8 PA	12	1 2		S PA	4 PA	3 PA	2 PA	PA	24 PA	23	3 1	30	21 PA	20 PA	19 PA	PA	1	1 2		5	Ā P	13 PA	12 PA	3	3	\$ 1	9	8 PA	7 PA	6 PA	١X	١	_	L	ŀ	1		
PANEL 336	ACT 333	IE) 335	JEI 336	VEL 334	VEL 334	VEL 334	NEL 333	ACT 999	111,000	101 222	VEL 332	VEL 332	NET 332	11.00	VEL 331	VEL 331	VEL 331	VEL 330	AET 930	1000	VEI 330															1004	NEI 054	NEI OSA	NEL 054	NEL 054	NEL 031	NEL U31	100	NE) 031	NEL 031	NEL 030	NEL 030	NET 030	NEI 030	NEI 030	NET 029	NEL 029	NEL 029	NEL 029	NEL 028	NEL 028	ACC 020	NEI 008	NEL 028	NEL 027	NEL 027	NEL 027	NEL UZ/	MEL 020	NEI ODE	NET 026	NEL 026	NEL 026	NEL 025	NET 023	MELOZO	NEL OZG	NEI 025	NEL 024	NEL 024	6 PANEL 024		DESC / SOURCE	ЛS					
H			-										_	1	1				ļ						-	+	1					1		_	-	-	Ì							+							_									-									_									TYPE					_	-
П	l	Ī						Ī	ľ	Ì				l	1				Ì	T	Ì			_		İ		1				1		i		İ	1	1		_	-								İ								t	1						T	1	1						t	1				RACK	יכ				1		
H	F	1	Ŧ	1	1		_		ŀ	İ		-	_		1				-	İ	1	1		_	F	-	1	1				1		_			1	1	-			F	ļ	1	1	-			†			-				ŀ	ļ	+		7	_		ŀ		1	1	1	-	_	-	İ	t	+	1			PP J/	LOCATION		_				
H		ł	ļ					ļ	L		1	-		-	-		_	-		l	+	1	1	_	_					_	-	1		_	L	<u> </u>	+	1		-				1		_			ł	1		1				-		+		-	_			L	<u> </u>	1	+		_		-						Š	DESC	OUTPUT	_	L			
																***************************************																																																														C/SOURCE			- Property Control of the Control of			
-				İ		1										1					200-20	200	DK-SOS	RK-S02	RK-S02	XX-802	700-AX	DIV 200	RK-SO2	RK-S02	RX-SO1	100	BK-SO1	RK-S01	RK-S01		ŀ																					-	1				-											1				LOCATION						
																		_			AMP-24	2000	ACGMA	AMP-23	AMP-23	AMP-22	AMP-22	100	AMP	AMP-21	AMP-1D	AIMIT-10	AMD 10	AMP-1C	AMP-1C			}																																								N DESIGNATION CHIAREA	AMP OUTPUT				Z	
H	_		F	<u> </u>	+	1					t	1	_	F	1	†				ļ	_	, -	. ,	2	_	2	F	t	+	_	H	t		2	=	L	ļ	t	1				ŀ	t	+		_			†	1	1				F		ļ.	1	#					l	1	1			-	_	F	ļ	1	1	1		CHIA	CHANN	_		000	S C C	
\parallel	_		_	-					_	L		1		L	-	1					CAL		2			e CX1		1	CYT	5 CX1	4 CX12	(2)	2		1 CX1:	L	-		1			_			1					+										+		_					1			_	_			1				REA DESC					NOR SOLITH AMD	
RKS02	굊	곳	곶	Ę.	2 3	2 3	Ş	곶	굦	곳	3	2	짖	묫	3	2	쾾	곶	굦	곶	7027	7		NOV IRK	202V RK	202V RK	702V KK	2024	NGN/	202V RK	202V RK	77		PR PR	202V RK	굣	1 4	13	2 2	Į.	곶	곶	곳	13	2 2	P	곶	P	Ę	! 3	2 2	D :	æ	곶	깆	꾸	곶	13	9 2	2	깆	꾸	꾸	20	주	2 3	2 2	ē	2	꾸	Į.	Z	2 2	2 2	2	2	_	1						
S02	802	S02	S02	SOZ	200	3	3	S02	S02	S02	200	3 6	3	S02	202	200	SOS	S02	S02	S02	202	200	Š	SS	S02	S02	SUZ	002	300	SOZ	(S02	202	3	SBS	(S02	(S02	SOZ	200	ò	Ses	S02	(S02	(S02	2	3	cos	(S02	(S02	SOZ	2002	96	SOS	SO2	ŝ	(S02	(S02	SO2	200	9 6	ŝ	ŝ	(S02	\$02	S02	(202)	3 6	9	ŝ	ŝ	\$02	\$02	200	Š	600	ŝ	ŝ		RACK	NEW					
9	G	G	6	၈	G	0	9	6	၀	<u>ه</u>	G	,	p	၈	G	,	9	၈	G	၈	92	5	3 5	3	ន	22	92	2	3	ន	92	5	3 1	8	2	F	7	,		-	7	71	T	-		,	F	-	7		, -	η.	71	7	m	Е	m	7	,	,	m	m	m	m	п	1	7	n	m	т	m	п	,	-		m		PP JACK	징			5	OM 305-431	
3 6	7	6	15	14	ē	;	3	≐	10	9	۵		7	0	U	, 1	Δ	ω	2	_	12	=	:	ŝ	9	8	7			(J)	٠	ci		٠	-	16	5	4	:	3	ಭ	1	10		,		7	6	J	١,		, اد	0	-	24	23	22	2	2 5	3	اء	8	17	6	15	1	:	۵	3	1	10	9			,	6		JACK K	NOIT				~	
						İ															RKS02	KKSUZ	2000	BK SNS	RKS02	RKS02	RKS02	ZNOUZ	DV CON	RKS02	RKS02	XXXXXX	1000	RKSOO	RKS02				Ī						t	1	-						1													ļ							l					RACK						
											-	İ			Ĺ	İ			_		22	2	3 8	3 1	8	8	02	2	3 8	8	ន	02	3	3	ន						-	-	-		t			_	-	t	t	+	1				-		1	\dagger			_			l	t	1					1	+	1	†		ō	၁၉၀		-			
		Ţ						Ī						_		Ī									1				Ţ										Ī																					T	1					Ī	Ī			_				T	1		오	Z P	800					
	1	1				İ	1		j	_	ľ	T					1	1					t	1					1	-		Ī		1	1		T	ľ	t	1	1				1	1	1	-			1		1		1					T	1				l		t	+			-			Ì		-	오	2	MECTION	1				
+	+	1			-	t	l	1			-	l					1	1			12	1	ā	\$ 0	٩	8	7	σ	,	Э.	4	ا س		ار	_				1		-		_	-	+	1		_			-			1		+	-	-	+	+							+	1	-			-		\dagger	+	-	<u>۔</u>	AMPC		+	-			
\parallel	+				_	-	-	1	1			l	1				1	1		-				+		-			1	-		-		+	-	_	_		1	+			_	_	+	+			L	-		+	+	+	+				Ŧ	+	1			-			1	1	$\frac{1}{1}$	_		H	-	+	+			UT RAC	NE NE	1	_			
	+												1	1										-	1										-					1						1							+		1	-				+							1	1							-	+		I/O # INPUT OUTPUT AMP OUT RACK AMP # CH	WAMP DES					
\mathbb{H}	+	1			-	H	l	1	1		L	-				-	1	+	+			ŀ	L	+	1		_	-	+	+	-	L	1	+				-	1	+	+	+	_	H	+	+	1		H	-	+	-	1	+	-	-	-	-	H	-	1	-	-		L	L	+	1	-			_	1	+	+	1	-	#	ĞŅ.	+				İ

S-CATWALK	SCATWALK	S-CATWALK	S-CATWALK	SCATWALK	S-CATWALK	S-CATWALK	SCATWALK	S-CALVVALK	S CATWALK	CONTAIN N	SCATWALK	S-CATWALK	S-CATWALK	SCALWALK	COLANDE	S CATIVAL K	S-CATWALK	S-CATWALK	S-CATWALK	S-CATWALK	SCALWALK	OCA WALL	O CALANTA	S CATAIA K	SCATWALK	SCATWALK	S-CATWALK	S-CATWALK	SCALVVALK	CATAMIN	S-CATWALK	S-CATWALK	S-CALWALK	מ מארואייניי	SCATWALK	SCATWALK	S-CATWALK	SCATWALK	S-CATWALK	SCAL WALK	O COLONIA	S A TANAL K	SCATWALK	S-CATWALK	SCATWALK	SCALWALK	S-CALWALK	O CATANATA	S CATWALK	SCATWALK	S-CATWALK	S-CATWALK	SCATWALK	O CATANATA	A CATANALA	S-CATWALK	S-CATWALK	S-CATWALK	S-CATWALK	SCA! WALK	SCALWALK	200	CATAMIN	SCATWALK	S-CATWALK	S-CATWALK	S-CATWALK	SCATWALK	SCA! WALK	0.00	A INVITACE	SCATWALK	S-CATWALK	SCATWALK		The Country of the	RM BEING SERVERD TYPE				-		_
MIC 1	MICZ	MIC 1	CINE	MIC 2	MIC 1	LINE	MIC 2	MIC 1	CINE	MICA	NIC 3	MIC	LNE	MIC 2	MIC -	0111	Z	MIC 2	MIC 1	LNE	MICZ	MIC	LINE	100	NIC 3	MIC 1	CNE	MIC 2	MICT		LNE	MIC 2	MICT	- LINE	N	MIC 2	MIC 1	LINE	MIC 2	MICT	LINE	T NO.	MiCo	MIC 1	LNE	MIC 2	MIC 1	LINE	Nin .	MIC 2	MIC 1	UNE	MIC 2	MIC	E L	Z	MIC 2	MIC 1	LINE	MIC 2	MIC 1	Livin	THE PERSON NAMED IN	MICO	MIC 1	ENE.	MIC 2	MIC 1	LINE	100	2	MIC 1	E K	MIC 2			TYPE TYPE			TOTAL AMP CH	O AL COIPO	דווםדווי יידי	2
_	RKS02	-	_	_	_	I	_	_	+	+	+	_		_	+-	+	-+	-1		-	+	+	+	+	+	_	-4	-	٠-	+	-+	_	Η-	+	-	-		-	-	-	+	+	-+	7	-	┢	۰	+	DVS03	RKSOS	RKS02	RKS02	⊢	XXXXX	┿	-+	RKS02	_	Н	⊢	+	٠	+	+	-	-	-	RKS02	KKS02	NACON	2007	-	_	RKS02		2000	50				ı	3 3	
-+	3 =	-	-	_		Н	_	٠	+	+	+	+	-	┝	+-	┿	+	-	_	⊢	╌	⊢	╀	+	+	+	3	=	10	;	٥	00	-	,	8	5	4	S	2	ļ.,		2 2	3	23	2	20	19	١	:	17	6	15	12	1	;	3	=	10	8		1		,	л.	4	3	N	-	N 24	5	3	_L	2	20	JACK	2	LOCATION	7	-			+	
PANEL 358	17 PANEL 357	PANEL 357	PANEL 356	PANEL 356	PANEL 356	PANEL 355	PANEL 355	PANEL 355	PANEL 354	FANEL 334	DANIEL OCA	PANEL 354	PANEL 353	PANEL 353	PANEL 353	TOWER GOZ	DANEI 350	PANEL 350	PANEL 352	PANEL 351	PANEL 351	PANEL 351	MANEL 350	TANEL JOO	DANIEL 360	PANEI 350	PANEL 349	PANEL 349	PANEL 349	LVIACE 340	PANE 348	PANEL 348	PANEL 348	CANEL 34/	DANEI 347	PANEL 347	PANEL 347	PANEL 346	PANEL 346	PANEL 346	PANEL 343	DANIEL CAS	PANE 345	PANEL 345	PANEL 344	PANEL 344	PANEL 344	PANEL 343	DANEI 242	PANEI 343	PANEL 343	PANEL 342	PANEL 342	PANEL 342	PANEL 341	DANEI 344	PANEL 341	PANEL 341	PANEL 340	PANEL 340	PANEL 340	PANEL 338	CANEL SOO	DANEI 330	PANEL 339	PANEL 338	PANEL 338	PANEL 338	PANEL 337	LWINET 99/	DANE 997	DANEI 337	PANEL 336	PANEL 336		DEGC GOOKGE	DESC / SOURCE	PUTS					
																															-																			-	4																																
													_									L												L																				L																						117	387						
-				1													-			_			L	L												_						ļ				_			-												_					!					-				RACK PP JACK		1002						
			1								-														l						1		_										İ	1		_									İ	1	1									_			_	_	ŀ				JACK	CALICIA	2	2					
							and an																								The street of th																																													DESC / SOURCE	DESC / SOLIBOR	STUG					
									-	_							ŀ						_																												1												-	1												LOCATION	CONTION						
																																								_																																				DESIGNATION	CONTINUE CONTO COMME	AMP CHIED IT			NO	20.5	
_		+	+	_		1							I				l		Ī	_							Ī							_				1					I	1			_			Ī	1						1			-	_				1	1					L	1	1			S AK	COMME	CHANNEI			000	, , ,	
Z	72	0 2	2 2	2 2	2 2	2 2	0 2	20	R	R	R	12	0)2	20	R	R	7	12	0 2	20	R	R	70	70	20	2	2 2	0 2	20	70	12	0 :	æ	70	1		0 :	20	70	R	70	7	12	012	0 ;	ž	įR	70	7		0 2	70	70	20	20	7	0 2	0	ZO:	ĮR.	Ž)	70	20	12	0 2	0 2		20	R	- 20	7			20		DESC	7				NOT OCCUPANT AC	1	
(S02	\$02	S S	96	2002	2002	200	603	ŝ	SO2	€S02	(S02	200	2002	Sms	\$02	(S02	ŝ	2007	900	ŝ	ŝ	S02	(S02	\$02	6802	7007	1002	600	SO2	\$02	7007	3	(S02	KS02	208	200	COS	SOS	KS02	KS02	KS02	KS02	7007	1005	COS	KS02	KS02	KS02	KS02	2002	SSS	KS02	KS02	KS02	KS02	KSUZ	2002	S	KS02	KS02	KS02	KS02	KS02	7007	2002	Kens I	X SOS	KS02	KS02	KS02	KSOZ	2007	COS	RKS02		RACK		NEW!	-				
د	اے	- -	- ا	٠		،		- •	-	۷	ت	-	-	-	-	_	-	-	-	-	-	-	-	-	-	-	-	- -	-	-	-	+		-	-	-	-	- -	-	-	_	I	1	:	:	=	Ξ	Ξ	π	: 2	Ε :	Ι.	Ξ	1	Ξ	: 1	: :	c :	Ξ:	Ξ	I	I	I	1		:	-	Ξ.	9	ດ	G	G	5	၈		9	NEWFILOCATION	3	+	-	JIVI 505-451	5	
12	= 1	Š ¢	0		10	, 0	1	•	اد	2		24	2 2	3	S	21	20	ď	3	à	17	16	15	14	13	12	=	1	5	9	۵		1	0	o	, ,	,	ו	2	_	24	23	1	3 !	2 5	28	1 9	18	17	ā	5 6	13	4	13	25	=	: =	3	۰	œ	7	თ	5	4	،ا،	3 1	3	4	24	23	22	-	2 1	8			1	2			_	•	
					8				ļ																																																										-					ľ				RACK							
	1	T	İ	ļ		ļ		1	1		_	-	1			_		ľ	İ											_		1				ļ			1					ļ	1					ļ		1		_		L		İ	1			_		ľ									1			5 #	200	2					
		L			L							Ĺ																		_		1																														-													오	NPCT	CONNE	200					
			L																						_	_															_																						_	_										!!	오	OUTPUT	CITON	CTION					
			L																																																																								오	AMP OUT							
																																																																												RACK	USC I/O CONNECTION NEW AMP DESIGNATION						
	†		L						ļ	1										1	1								1		-	+	1	_			1		1					1	+	-			l	l		1					†	1	1						l		1	+								AMP#	PDESIGN			1			
																									-					1									Ī																										Ī	Ī	Ī	T						T	1	유	ATION		T	1			-

S310-F S310-F	\$310-G	\$310-G	S310-H	S310-H	S310+H	S310-H	S310-3-4	S310-3-4	S310-3-4	S310-3-4	S310-1-2	S310-1-2	S310-1-2	S310-1-2	S310-1-2	S310-A	S310-A	S310-A	S310-A	S310-A	S310-B	2310-6	S310-B	S310-B	S310-C	S310-C	S310-C	8106	S310-C	S310-D	S310-D	S310-D	S310-D	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECTIVO	S-CATWALK	S-CATWALK	S-CATWALK	SCATWALK	S-CATWALK	RM BEING SERVERD			
MIC 1 RKS03 E MIC 2 RKS03 E MIC 3 RKS03 E	RKS03	MIC 2 RKS03 C		RKS03	MIC 2 RKS03 C	RKS03		RKS03	MIC3 RKS03 C	RKS03			RKS03	MIC3 RKS03 C	RKS03			RKS03	MIC 2 RKS03 A	RKS03		RKS03	MIC 3 RKS03 A	RKS03	BKens		RKSQ3	MIC 2 RKS03 A	RKS03		RKS03	MIC 3 RKS03 A	RKS03							RKS02	RKS02	RKS02	LINE RKS02 R	RACK CK	TYPE LOC		ı	TOTAL INPUTS 546 TOTAL OUTPUTS 82
1 PANEL 407 2 PANEL 407 3 PANEL 407		20 FANEL 404 21 FANEL 404			14 PANEL 400	- 1		10 PANEL 394	9 PANEL 394				4	3 PANEL 398	<u>, -</u>		ı	2 2	20 PANEL 391	19		6	15 PANEL 389	<u> </u>	3		3 4	8 PANEL 034	4		4	3 PANEL 382	N -	Ţ						ã	17	16	15 PANEL 358	Ä	ION DESC / SOURCE	INPUTS		
	LINE RKS03		LINE KKOO				Civic Constitution of the					LINE RKS03					LINE RKS03				LINE RKS03					LINE RKS03				LINE IRKS03														R	3971			
	3 D 24 TOROOM		3 U 18 TO ROOM				i c	,				D 6 TO ROOM					3 B 24 TO ROOM				B 18 TO ROOM					B 12 TO ROOM				B 6 TO ROOM														PP JACK	LOCATION DESC / SOURCE	OUTPUTS		
RKS03			RKS03			RKS03	RKS03				RKS03	DKCO				RKS03				100000	DKGna				RKS03				NA COO	Dicens															IRCE LOCATION			
AMP-33		Ш	AMP-33			AMP-32 4					AMP-32 2	L				AMP-31 1	1			National Policy					AMP-31 3				7	ALD ST															DESIGNATION	AMP OUTPUT CHAI		NSB S
G CX204V RKS03 RKS03 RKS03 RKS03	RKS03		H CX204V RKS03	RKS03	RKS03	4 CX204V RKS03	CX204V	RKS03	RKS03		2 CX204V RKS03		RKS03	RKS03		A CX204V RKS03	RKS03	RKS03	RKS03	RKS03	11	RKS03	RKS03		C CX204V RKS03	RKS03	RKS03	RKS03	RKS03	2000	RKS03	RKS03	RKS03	RKS02	RKS02	RKS02	RKS02	RKS02	RKS02	RKS02	RKS02	RKSOZ	RKS02		CH AREA DESC RACK			SOUTH AMP ROO
01 10 RKS03 E 1 RKS03 E 2 RKS03 RKS03 RKS03	2 22 23	20 19	18	16 15	1 13	8	7 12	ō °	0 80	7	» v	o	4	دم د	-	44	2 13	21	20	<u> </u>	18	16	5 4	13	2	3 6	9	8	7-	6	4	20 00	-	24	2 22	21	22	3 23	21	18	17	- C	14	П	PP JACK RACK	EW PP OCATION		ROOM 305-431
03 02 1	888	Ш	38	នន		8	88	22.2	\perp	88	1	22	88	1	8	1	2 2	2	4	2 5	2	9	١.	01	9	2 9	01	Ц	2 9	01	9		01	01	1	91			L							OSC IO COMME		
ø	A	Q	3			4	2				3 -	-				4				G	3				2	3			-								٥ ۵	2	_					유	I/O# INPUT OUTPUT AMP OUT RACK	TION		
		4																																											AMP# CH	TO TON	-	

S310-H	S310-H	S310-H	S310-H	S310-H	S310-3-4	8310-34	31034	S310-3-4	S310-3-4	S310-3-4	S310-1-2	S310-1-2	S310-1-2	S310-1-2	S310-1-2	S310-1-2	S310-1-2	S320-A	S320-A	S320-A	\$320-A	S320-A	S320-A	9-070-0	2000	e oces	S320-A	S320-B	S320-B	S320-B	S320-C	S320-C	S320-C	S320-C	S320-C	S320-C	S320-D	S320-D	S320-U	S320-D	0-020-0	S30.D	COCES	DIRECTIVO	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT NO	S-REST RM	O-NEOT DA	C DECT DI	C DECT DA	230	3310-E	33.00	2000	S310±	40168	2304	10104	2300	יאה מבוועס טבונאבונט	RM REING SERVE			-	TO	_
MIC 1		LINE	MIC 2	MIC 1			UNE	MIC 3	MIC 2	MIC 1				LINE	MIC 3	MIC 2	MIC 1			LINE	MIC 3	MIC2	MIC 1			CIAL	Z	MIC 3	MIC 2	MIC 1			ENE	MIC 3	MIC 2	MIC 1			CNE	MIC 3	MICZ	100	NIC 1				-									-	CINE	MICS	MICZ	MIC 1		-	CNE	-	-		+		TOTAL AMP CH	AI OUTPU	OTAL INPU
RKS04		RKS04	DKSQ4	RKS04		+	RKS04	RKS04	RKSQ4	RKS04				RKS04	RKS04	RKS04	RKS04			RKS04	RKS04	RKS04	RKS04			2000	DE SAG	RKSOA	RKSQ4	RKSD4	-	-	RKS04	RKS04	RKS04	RKS04		_	RKS04	RKS04	KKUC4	TANOOTH THE	DKSON				1				1						RKS03	KKUU3	KKS03	RKS03			RKS03	RACK		5	-	I	154	-	
C 19	Н	ი ი გ	$^{+}$	H	1	T	t	ი ფ	Н	C 7			_		П	ი 2	Н		Н	П	П	-	A 19	H	l	t	†	Α .	+	1		┢	1	A 9	Н			_	Α 4	A 3	t	,	†	1	1		1		1	+	1	ł			l	ł	t	+	0	E 7		l	m	٤		OCATION		ľ		1	_
PANEL 439		PANEL 435	PANEL 435	PANEL 435			PANEL 433	PANEL 433	PANEL 433	PANEL 433				PANEL 429	PANEL 429	PANEL 429	PANEL 429			PANEL 426	PANEL 426	PANEL 426	PANEL 426			PANEL 423	DANEI ADD	PANEL 423	PANEL 423	PANEL 423			PANEL 420	PANEL 420	FANEL 420	PANEL 420			PANEL 417	PANEL 417	PANEL 41/	PANEL 417	BONE 447														PANEL	PANE	PANE	PANEL 410			PANEL 407		DESC / SOURCE	DESC (SOLDOE	NOTIFE				_
	- NE					LINE							LINE						LINE						ENE							CNE						LINE																		LINE						LINE			TYPE						_
	RKS04				-	KKS04							RKS04						RKS04						RKS04	1						RKS04						RKS04		_	-								1	1						RKS03		-				RKS03		RACK	5		ľ				
+	D 28					12	H					+	6			-		1	B 24	-	+				18	۲					1	B 12		-			+	ω σ	_	_			-	+		-		+	1		ŀ	ľ				F 12						F 6	H	PP JACK	CALION	2					
	TOROOM					TOROOM							TO ROOM						TO ROOM						TOROOM							TO ROOM						TOROOM																		TOROOM						TOROOM			DESC/SOURCE	OUTPUTS					
RKS04					RKS04						BKS04				-			RKSOA		1				RKS04						10004	BKSOM						RKS04														RKS03	RKS03	RKS03	RKS03	RKS03						RKS03				LOCATION						
AMP-43				Zin Jimo	AMP-42					77	AND AS	CAGMA						AMP-41						AMP-41						7	AMD						AMP-41							-							AMP-34	AMP-34	AMP-34	AMP-34	AMP-33						AMP-33				DESIGNATION	AMP OUTPUT				20	
4 I	T			†			1	1	Ī	*	ა - ა -	•	1	1	1	-			1	1			+	2 B		~		Ī	1	+	3				1	+	4							ļ.	ļ	Ī		ŀ		ŀ	4	ယ	2	Н	11 E						2 F				오	CHANNEL	Г		0	3	
CX204V	İ			CAZOAV	CX204V				Ì	A407VA	24040	VVOCAS	1	l		İ	07.2044	VANCAS	1		Ì			CX204V						CVC044	200	1					CX204V	1				ŀ			t	-	T				CX204V	CX204V	CX204V	CX204V	CX204V		1				CX204V		-		A DESC				7.091	NSB SOLITH AMP BO	
RKS04	RKS04	RKS04	RKS04				RKS04	RXS04	BKSON				1003/d	DV SOL	BKSOA	BKS04	NS S	D CO	BKSOA	BKS04	BKS04	DK SOA			RKS04	RKS04	RKS04	KK CO4	77.004			RKSOL	RKS04	RKS04	BXSO.	BKS04	RKS04	DK SQL	RKS04	RKS04	RKS04	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03			RKS03	RKS03		RACK			-	10	$\overline{}$	
9 5	, 0	C	0	2 5	2	D	ი (,	, (2 5	2 5	2 0	,	, (, (2	2 5	2 0	, o	>)	> >	P	> :	2	8	>	A	Þ	. >	. 5	2 0	: מ)	 	• ,	P (3 0	0	>	>	Þ	A	Ŧ	-	- -	71	m	m	ım	m	요	9	2	9	9	-71	m	m	m	m	2	-	т	-	P	NEW PP LOCATION			714 000-401	305	
9 5	6	15	4	π α	7	12	6			10	, 0						٠	. 5	2 12	3 5	2 2	3	į,	3	6	16	15	14	ï		,	3	5	٥		1	4		4	ω	2	-	24	23	23	22	24	23	22	22	6	15	4	13	12	12	5	9	~	1	=	6	4		JACK	ATION			2	2	
RKS04	RKS04	RKS04	RKS04	RKS04	RKS04	RKS04	RKS04	PKS04	TOOUT	TANOUA	ZK.SQ4	77.004	Thought	NAOU4	DV SOL	10070	DKSN4	10004	10004	2007	22004	DVSOA	RKS04	BXS04	RKS04	RKS04	RKS04	RKS04	XX304	RN-SO4	10004	DKSNA	SKS04	RKSOA	000	DK GOA	RKSOA	DYCON	RXS04	RKS04	RKS04	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03	RKS03		RACK						
88	ន	8	ខន	3 8	22	22	88	3 8	3 8	3 8	3 8	3 8	3 8	2	3 8	3 8	3 =	2 2	2 5	2 2	2 9	2 9	3 9	3	2	01	01	01	9	2 5	2 5	2 2	2 9	2 9	2 5	2 5	2 9	2 9	9	0	2	01	8	8	8	ន	ឧ	ຂ	8	03	ឧ	03	8	ន	ន	ឧ	8	03	ස	8	8	ន	ස		₩ O/I	QSCI					
	12	1	50					١,	٥		L		4	، ا	۸				ā	6	i	:	3			12	1	10	۵			,		1	,	n		,	4	اد	,	-	12	=	ö	9	L			L							ω.	7	6	ćn.			•	요	INPUT	CI/O CONNECTION					
G						2		_			-	-	1											,	ω						^	ا اد	-				-	•								L	4	ω	2	_						6					,	J.	!	오	UTPUT /	CTION					
5				4	3		1		-	2	-		L	L		-	4		ļ		-		,						-	_				1		-	•						_					_	L		4	3	2	-	۵					ŀ	7			오	MP OUT R						
																																																																	ACX	NEW AMP DESIGNATION					
-		4	1			-	-	1											[-				-	1	1	1						F	I	Ī	F	F	Ī	[1												1			7	1	1	1	1	-		1			AMP#	DESIGNAT					
Ш					Ц						Ĺ	L				L						L									L																			Ц					_				1	\perp				_!	요	ᅙ					l

	\$330.3.4					\$330-1-2						3330-A										S330-B								9990-0	330-0	8390				CIRECT I/O	CIRECT SO	DIRECT NO	District SC	DIRECTIO	DIRECTIVO	DIRECTIVO	DIRECT I/O	5300	8300	231015	S310-E				S310-F	S310-F	S310-F	S310-F	3310-7	S310-G	8370-6	3106	S310-G	S310-G		RM BEING SERVERD			ТОТА	TOTAL	101
MIC 1			MIC3 F	П			1	Ι.	MIC Z		ļ		ı		MIC2		l					MIC 1			CNE		ı	MIC 1	ı		CNE	1	MICZ	1	1													MIC 3					1	MICZ				ı	MIC 3	П	١.	34/1			LAMPCH	OUTPUTS	TOTAL INPUTS
RKS05 E	\perp		RKS05 C			-	-		RKSUS C	-	-		RKS05	-	KS05 A	-	-		KS05 A			RKS05 /						RKS05 A		L	_	RKS05	+	+	-			L			1		1		1	1	+	RKS04 E	Н	\rightarrow		+	+~	TRACE OF	+-	+		KKS04	RKS04 C	RKS04	RACK	LOCATION		ı			546
		10	ဖ	7			١,		3 N	,			z	21	23	19			16	15	14	13			ő	9		7			1		N		Ī			İ			İ	1	Ì	Ì	l	İ	ő	9	8	7		,			, -			23	21	20	JACK			1			l
PANEL 471		PANEL 468	PANEL 468	PANEL 468			PANEL 404	PANEL 464	PANEL 464	PANEL 464			PANEL 461	PANEL 461	PANEL 461	PANEL 461			PANEL 458	PANEL 458	PANEL 458	PANEL 458			PANEL 455	PANEL 455	PANEL 455	PANEL 455			PANEL 452	PANEL 452	PANEL 452	PANEL 452													PANEL 445	PANEL 445	PANEL 445	PANEL 445		LANCE WAY	PANEL 442	PANEL 442	PANEL 442			PANEL 439	PANEL 439	PANEL 439		DESC / SOURCE	PUTS				
	LINE					LINE						LINE						LNE						LINE						CNE																LINE					CINE						LINE					34/L					
\parallel	RKS05				1	KKSUS						RKS05				-	1	RKS05						RKS05	-					RKS05					-							l	+	+	L	RKS04					77004	0000	+				RKS04				RACK						
H	12		+	H	1	0	,	-	F	_		B 24						B 18		1			1	D					_	8	F	F		-				L						-	F	٦	Ė		1	+	7		F	ļ		-	0			Н	ğ	OCATION	-	1	-		
\parallel	TO ROOM	Ш				CROOM	L				╙	1 TO ROOM				+	4	TO ROOM						12 TO ROOM						TO ROOM	-			-						-	l	ŀ	-	ŀ		12 TO ROOM	Li		-		CACCA	1	l				24 TO ROOM	L				DESC	STUTION		1		
	M					M						MO						OM.						₩.						OM																OM.					S						MO			****		/ SOURCE					
RKS05	RKS05			1111000	RKS05						RKS05						RKS05						RKS05						RKS05														KKS04	RKS04	RKS04					TOO OT	000					RKS04						LOCATION					
AMP-52	AMP-52			in or	AMP-52						AMP-51						AMP-51						AMP-51						AMP-51														AMP-44	AMP-44	AMP-43					AMIT-43						AMP-43						DESIGNATION	AMP OUTPUT			NS.	
	3			+	ر د د						-1 A				1	+	N .	-		1	1	+	3	1				+	4	_										_		l	_	1 SP10	_			-		^	t	F	F		Н	3 G				1		CH AREA	CHANNEL	#		BSOU	
CX204V	CX204V		H	0,200	CX204V	-					CX204V			1		-	CXXOAV	1				0,000	CYONA					_	CX204V											-			21 CX204	0 CX204V	CX204)					CAZUAV	┸					CX204V		-	1			A DESC	-	İ		NSB SOUTH AMP	
RKS05	1 1	RKS05	RKS05	- 1	- 1		RKS05	RKS05	RKS05		- 1	RKS05	RKS05	RKS05	RKS05	-1	П	DKSOS	DKS05	DVS05	RKS05	- 1	-1	PKS05	RKS05	RKS05	RKS05		- 1	RKS05	RKS05	RKS05	RKS05	RKS05	RKS04	RKS04	RKS04	RKS04	RKS04	RKS04	RKS04		1			1 1	RKS04	RKSD4	RKS04	-	1	RKS04	RKS04	RKS04		/ RKS04	RKS04	RKS04	RKS04	RKS04		RACK.	+	+	3	2	
09	90	00	0	0 5	2 9	o	ဂ	0	ဂ	ဂ	2	ω:	Α.	> :	A	A 5	3 0	0,)	>)	D :	D	2 0	D :	Δ.	A	>	>	9	В	•	A	Þ	A	Е.	т	П	E	Э	ш	m	m	2	2	01	F	m	m	7 (n S	2 -	m	Е	E	m	2	0	0	0	0		PP JACK	NEW PP L			M 305-431	
13 8	7 12	5 °		70	0	6	4	3	2	_	4	24	3	2	22	6	ة	\$ 6	\$ 2	ñ 1	1	١,	3 1	3 6	5	9		7		6	4	3	2	_	24	23	22	21	24	23	23	21	74	13	12	12	10	9	»	13	6	_	3	2		5	22	23	22 5	20	1	JAC	CATION	T		431	
RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	EKSOS	DKSOS	DV SOL	DKOOS	72000	DK 205	DK SOS	90570	DKS05	RKSOS	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS04	RKS04	RKS04	RKS04	RKS04	RKS04	RKS04	RKS04	RKSQ	RKS04	RKS04	RKS04	RKS04	RKSOA	RKSO	DK SOA	RKS04	RKSOA	RKS04	RKS04	RKS04	RKSO	RKSO	RKS04	RKSO	RKSOL	1	Z ACK					
22	\perp	1	Н	1			Ц	-	4	4	4	_	4	1	4	1	1	1	1	1	1	1	1	1	1	1	1	4	4		4	4			4		4	4	_	L	L	L	L				03	1	1	1	Ļ	L	Ц	Ц		4	4		4		į	lo g	2	+			
ω		8 7	6	,			4	ω	2	-	1		5 6	3 3	2 3	2	1	-	3 =	1	5 4	•			20	7	0	Ľ1			7	ω	1	1	1	1	+	8						-				7 0	t	t		l	ဖ				+	+	15	-	2	I/O# INPUT IOUTPUT	200	l			
	2			Ī						1	1	4			İ			,		İ	l	T	,	3		1	1			_						1			4	3	2					6				-	5						4			9	2	OUTPU					
4	۵			2	-					1	4		1	T			٠	T	T	İ	Ì	_	,	T		ı			-								-						2	1	8					7				_		6			1	9	2	I AMP OU	ŀ				
												1	1	+	1	T	İ	İ	1		ı		Ì	1		1		1						1		1							-																1		1000	TRACK	NEW A				
	\parallel		\parallel			-	+	+	1					1			+	1			-	+		l	1	+		1				+				+		1							-		1		+					4		+	+	1		+	241	AMP #	NEW AND DESIGNATION				
П	П										ľ		Ī				T		Ī	Ī	Ī	T	T		Ī	1	1	1	1			1	1			1											T	1		Ī					1	İ	1	1	1	T	9	2 2	ATION	l	1		

SPARE	S210-E	S210-E	370	\$210-E	8100	82700	S210-D	S210-D	S210-D	S210-C	S210-C	S210-C	S210-C	S210-C	S210-C	S210-B	S210-B	S210-B	S210-B	80108	S210-B	\$210-A	\$210A	S210-A	S210-A	2012	360	310.4	DIRECTIO	DIRECTIO	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	S-300	9-300	S-300	S-300	S330-E	S330-E	S330-E	S330-E	\$330-E	S330-E	S330-F	S330-F	S330-F	S330-F	S330-F	230-6	2000	S330-G	S330-G	S330-G	S330-G	S330-H	S330-H	S330-H	S330-H	S330-H		RM BEING SERVERD						_	
		LINE	MIC 2	MIC 1	+	LINE	MIC 3	MIC 2	MIC 1			LINE	MIC 3	MIC 2	MIC 1			EN C	MICS	MICO	MIC 1			LINE	MIC 3	MICZ	3 0	25	1	1				İ					-				UNE	MIC3	MIC 2	MIC 1			LNE	MIC 3	MIC			LINE	MIC 3	MIC 2	MIC 1			LINE	MIC 3	MIC 2		ERD TYPE			O AL AMP	OTAL AND	TOTAL OUTDITE	TOTAL INPU	
		RKS06	RKS06	RKS06		RKS06	RKS06	RKS06	RKS06			RKS06	RKS06	RKS06	RXSO6			RKS06	PKSOS	RKSOS	RKSOS					KKS06														-			RKS05	RKS05	RKS05	RKS05			RKS05	RKS05	RKSOS	1	ŀ	RKS05	RKS05	RKS05	RKS05			RKS05	RKS05	RKS05 E	RACK	ΓQ		-	ı	İ	3 8		
-	H	00	Н	$^{+}$	l	8	A 21	20	<u>1</u>			16	- 1	4	13		1	3	0 0	, ,	7		1	4	u	A 2	, -	Ţ					1	-	1	1						Н	Н	H	E 20	Н		7	+	+	1 13	t		H	Н	€ 8	E 7			E 4	E 3	E 2	닺	1				I	T	_	
		PANEL 155	PANEL 155	PANEL 155		PANEL 152	PANEL 152	PANEL 152	PANEL 152			PANEL 149	PANEL 149	PANEL 149	PANEL 149		100	DANEI 146	PANEL 146	DANE 146	PANEL 146			PANEL 143	PANEL 143	PANEL 143	PANEL 143	200															PANEL 480	PANEL 480	PANEL 480	PANEL 480			PANEL 477	PANEL 477	PANEL 477			PANEL 474	PANEL 474	PANEL 474	PANEL 474			PANEL 471	PANEL 471	PANEL 471		DESC / SOURCE	INPUTS						
	LINE				LINE						LINE								-				Į.																			LINE						CNE					LINE						LINE					TYPE						_	
	RKS06			l	RKS06		1	1			RKS06					NAMO		ł	1		ĺ	1000	90570			-				l	l	l	+				1					RKS05						RKS05	1	İ			RKS05						RKS05	-			RACK	5							
111	6				B 24			1		†	120				Ī	o in	╁	I	I	T	I	c	0					 -	I	Ī	1	1	1		-	I		1	1		+	F 24				1	+	F 18	+				F 12			1		7	F G				PP JAC	LOCATION	2						
	TO ROOM				TO ROOM					10110011	TOROOM					- CACCE						0.000	TOSON																			TO ROOM					0.000	TOROOM					TO ROOM						TO ROOM					DESC / SOURCE	TPUTS						
RKS06			1	RKS06					KNOUG	DVOOD					NAOGO						KKOO															NAOOO	DI COCO	Discos Constitution	NA COS	Diceous	BKSOS					111000	DK SOS					RKS05					111000	RKS05						LOCATION							
AMP-62				AMP-61					AMP-61	2					AMP-01						AME-63		+													AMP-04	AND -04	AMP-OF	PC-JMA	VIII -00	AMD 53					100	AMD.53					AMP-53					200	AMP-53				***************************************		DESIGNATION	AMP OUTPUT			NOD	2		
2 <u>1</u>	-		1	4	•	1	t	T	c	$^{+}$		l		ŀ	2	t					 	╁	İ	1						_	ļ	<u> </u>	İ		ļ	4 073	0		2 4		•	+	1	7	1	+	3	ļ	t			3 C			1	1	- 4	+	1			+		CH AREA	CHANNE	1		000	2		
CX204V CX204V	ĺ		1	CX204V		İ			CXZ04V		ļ				CXZ04V						CX204V		İ	İ			-							_		2 CX204V	CAZ04V	2 CX204V	SP12 CX204V	00000	VACCAS			1	1	0404V	CYSON			1		CX204V		+			074044	VANCAS			1	t		A DESC	-			OCCIT AIME	!		
RKS06	RKS06	RKS06	RKSOS	RKS06	RKS06	RKSOS	RKS06	RKS06	RKS06	KKS06	KK SOB	KK SO6	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	77,000	2000	BK SOS	RKS06	RKS06	RKS05	RKS05	RKS05	RKS05	KKUUU	RKS05	RKS05	RKS05							DKS05	RKS05	RKS05	RKS05	- 1	•	DK SUS	KKSOS	RKS05	RKS05	- 1	RKS05	RKS05	RKS05	RKS05	- 1		SUS YES	DK SOS	DESCRI	DK SOS		RACK	2			200	1		
990	0	00	00	2	w :	> >	>	>	2		Α.	>	>	Þ	2	8	A	A	A	Þ	91	8	A	.,	> :	A	A	m	E	m	m	1	-	Е	т	9	2	9	9	2 2	2 -	n (1	n	m r	חת	n S	2 7	n m	1	m	E	2	0	0	0	0 0	2 5	2 0	,	, (0 0	,		PP JACK	W PP LOC			KOOM 300-437	,		
6 U G	L	ω Α		H					ļ	l		ı			l			١.			İ			ļ	1	-						ı	23				ı		ı	L	1	ı	1	Ţ		7 =		Ì		N		- 1	1	-	1	1	4	П	ı	Т	П		971011	JACK	NOIT			37	,	l	
RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	KKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	KKS06	77,000	DVene	RKSOS	RKS06	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	KKKUS	RKS05	RKS05	KNOOS	77000	DK SOS	DK SOL	RKSOS	RKS05	KKOUS	KKSUS	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	RKS05	BK SOS	DK SOS	ZNOOS	BK SOL	DV SOL	DK SOL	N N O O	DKONE	10.00	RACK							
888	8	92	38	9	2 5	2 2	2	2	3	2	2	2	91	01	ŏ.	2	2	01	9	2	9	2	9	2	2 5	2	2	03	03	03	ន	03	3	23	8	8	93	ន	8	5	38	3 8	3 8	3 8	3 8	3 8	8	8 8	8	జ	ន	8	ខ	3 8	3 8	3 8	3 8	3 8	3 5	3 8	3 8	3		# 5	080	1					
		3 1	•		t	5	4	3				1	10	9			8	7	6	σ	_		4	6	0 1	.	1	12	=	10	9		L									0		10	» u	n	Ĺ	4	ω	2	_		-	5 2	ņ Į	\$ 2	à		Ĭ.	3 =	č	\$ 5	2	NE TO	CONVE	+					
N -				4	4	-			3	ω		L	_			2			-			-	-							-		4	ω	2	-	_			L	-	a	9		1		-	u	+	 -			+	4	1		-	+	6	•	-	1	12	2	TO IT AME	Ž		-				
					1	-			-				_			-				_						+	1			_			L					Ľ	_	<u> </u>			-	1		Ĺ	_				_	0	+	1		+	0			1	l	ř	É C	O T BACK	NEW		-				
				+	1	L							i										L		+	1						L	L											+		-						+					+					-	7	A AMIL DES	AMD DEC	-	-				
															_										1	+			1							-		_	-			-		1	+	+		-	_		+			1	-	1			1	+		-	5	AMD# CH	CNATION	+					

S220-B S220-C	S220-B	S220-B	S220-B	S220-B	\$220-B	SPARE	V-0520	SZ20-A	H-0226	W-0776	A 0000	5000	C221 A	5331-4	\$331-A	S331-A	S331-A	S331-A	S331-B	S331-B	S331-B	S331-B	00010	000	5331 B	S331-C	S331-C	S331-C	9001-0	500	23315	S331-C	S331-D	S331-D	8331-0	9012	2331	53315	S331-D	DIRECT I/O	DIRECT I/O	DIRECT I/O	CIRECTIO	DIRECT SO	DIRECTIO	DIRECT I/O	DIRECT I/O	DIRECT I/O	\$300	\$300	\$-300	3300	98	9300	9728	3329	220	820	9000	BCES	S329	S319	S319	S319	0019	6340	S319	S319	\$300	\$-300		RM BEING SERVERD					5	_
MIC 1		EN	MIC 3	MIC2	200	+		LINE	MIC 3	MICZ	3			CINC	I I	MC a	MIC 2	MIC 1	-	_	LINE	MIC3	Mic	300	1	1		LINE	MIC	100	200	MIC 1			LINE	MIC O	100	100	MICT					l								-	l		1	1	Civic	Nn C	100	200	MIC			CNE	MICS	100	MIC 2	MIC 1				짱	Γ	_	OLAL AMP	STAL AND	TOTAL CITEDITS	OTAL INPL
RKS07		RKS07	RKS07	RKS07	DK S/07	+	ŀ	RKS07	RKS07	KKSO/	ZKOO!	1		NOO/	DV SO	DK SO7	RKS07	RKS07			RKS07	RKS07	KKS0/	KNOU/	DVS07	1		RKS07	KKSU/	7007	DV SAZ	RKS07			RKS07	NAOU/	7000	2000	PKS07				-		1						-	-					7770	00000	DVS OF	DICCOR	RKSOS			RKS06	XXXXX	777000	BKSOS	RKSOS			RACK	2		F	L	ı	200	
C 19		o 0	0	0	1	Ť	t	n	n	+	c	+	†	>	,		>	>			П	A 1	┢	+	+	+	1	>	>			⊣			A	>		,	-				-	†	+	1					-	F	+	ļ	t	ļ	ď	3 0	0 0	,	9			ი	c	,	7	2	+	1	핑	LOCATION		-	Ĭ	Ĭ	+	2
9 PANEL 164		6 PANEL 161	DANC	PANE	0	T	l	PANEL 158		1	1					1	DANE: 491	- 1	-			15 PANEL 489							9 PANEL 486			PANE	-		4 PANE	ı	ANEL 401	П	П						1	-			_	-	-		1	1					ZU PANEL			-				TAIN.			1	-	JACK	DESC	INPUT	L		1	+	_
. 164		5	151	161	101			158	158	158	158			1.481	140		401	401			L 489	L 489	489	489	8			L 486	486	1400	400	486			481	8	100	1	484								The state of the s										450	450	1450	1	450			L 415	1.415	PANEL 410	45	415				DESC / SOURCE	3		-			
	HINE						LINE						CINE							INF						FINE	I PAIS							LINE																						LINE					-		LINE									34/1						-
	RKS07		1	+			RKS07				L		RKS07	ĺ				1		RKS07		_		L		NAOU!					ļ			RKS07				ļ				_				1			_							RKS06	l		<u> </u>		1	ı	RKSOR			-					1	m		_	ŀ			
	+			-		L	07						07 B	₽				+	+	07 B						0	-↓.	_						07 В			ŀ																L			0	+					+	206						-	:	RACK PP	LOCATION						
	1			ŀ			6 TO						24 TO				+	-		18	-					2	4				-	1	4	6 10							_			L		+		-								24 TC	L	_	-		+	_L	18 77						1		JACK	Ž	OUTP					
Cook	BOOM						TO ROOM						TO ROOM						10110011	MOOR					i	CACCE	BOOL							TO ROOM																						TOROOM						.0.100	MOOM								-000000	DESC/SOURCE	TS.					
RKS07					RKS07	RKS07						RKS07					-	RASU/							RKS07							141007	PKS07									j							RKS06	RKS06	RKS06	RKS06	RKS06	RKS06	RKS06						KNOUD	2000						ZN.OUD	ZNOOD T	DVcoe	1000	LOCATION						
AMP-73					AMP-73	AMP-73						AMP-72						AMP-/2							AMP-72							- 1 T	AMP_73															1	AMP-64	AMP-64	AMP-64	AMP-64	AMP-63	AMP-63	AMP-63						AMP-63		-					AMP-62	AMP-62	ALI 63	OCO GIANTION	DESIGNATION	AMP OUTPUT			NO	× 0	
ω σ					2	 >	-	1	1		-	1					ľ	2 8	t		1			_	3 C	t		1	_			,	•	1				_		1				F			Ť	_	_	_	2 SP10	_	_	3 SP10	_						-	†	†				F	4	3 3211	L	3	CHAREA	CHANNE	1		000	3	
CX204V	H				CX204V	CX204		1				CX204V					-	CXZ04V	L		1			1	CX204V	ı	ľ					CVC044	1		1			-		1	1			H		l	+	07/10/	30 CX202	30 CX20	10 CX20	CX20	10 CX20	10 CX204V	CX20			H			CX204V						L	CX20	11 CX204V		S DESC	EA DESC		1		7	<u> </u>	
V RKS07	RKSO	RKSO	RKSO	RKSO	V RKSD	V RKSO	RKSO	PK SO	DK SO	RKSO			RKSO	RKSO	RKSO	RKSO	RKSO			77.00	0000	DK SO	RKSO				מפיטיי	DVCO	RKSO	RKSO	RKSO	NANO.	V DVSO	DK SO	DKSO	RKSO	RKSO	RKSO	KKOO	0,000	DESC	RKSO	RKSO	RKSO	RKSO	77.00	NO.	DVS0	V RKS0	RKSC	RKSC	RKSO	RKS	RKSC	IV RKSC	RKSC	RKSC	RKSC	RKSC	RKS	ZKSC	ZNOC	200	DK SC	RKS	RKS	RKSC	RKS	RKS		75.05		1	+	_	NOD OCCUPANT ACCIN 505-45	֓֞֝֞֜֜֜֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֓֓֓֓֓֡֓֓֡	-
090	L	Ц		Ц	_	4	4	1	1	4	4	-	4	_			L	Ļ		ļ	1	1	_	4		L	ļ.	1			L	L	1	1	1			L	L	1	1	1	_		L	L		1	1				_	Ц						L	L	L								L			NEW DD			UNI SO	2	
13 72	T	П	1	Ħ	6	Ī	1	Ť	3		7		1	S			T		t	t	†	†				l	t	1	1	1	-	1	t	t	t			Г	t	t	†	†	1		H	t	t	†	+	7	1	+		11	H	7	-	-	Н	H	t	t	t	t	1	-	H	t	1		JA	NEW PP LOCATION	CATION	+		0-437	•	
RKS07			-	ı	RKS	RKS	PKS	270	0.00	P.C.	-		۱	ı				Į		ı	l		ļ	١		l	l	ı				ı		ı	Ì				l	1	Į	Į	- [1	П	П	1	- 1	- 1	-		Ш	- 1	- 1						l	П	1	- [l	ı		KACK	П	1	1	_			
$\bot \bot$	L	Ц	4	4	4	1	1	1	1	1	ļ	1	1	4			L	L	L	L	ļ	1	1		_	L	L	1	_			L	1	1	1			L	L		1				L	L			1			1				_					L	L			_				ĺ	l								
ននន	Г	02 7	T	1	8	3 1	Ť	Ť	t	Ť	T	2	1	1			_	01	9	T	T	1	t	1	으	3	r	t	1	1	Г	t	2 5	t	t	1			T	t		†	1	8	ន	2	2	3 5	3 :	2	2	3	2	8	ន			_		Т	r	S	t	1	7	1	ន	ន	8		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	1000	200	-				
+	_						1	١	Ī	1			+	6	5	4	3]-		7	1			L	1	7			-	+	,	֓֞֟֟֓֓֟֟֝֟֓֟֟֓֟֓֓֓֟֟֓֟֟֓֟֟֓֟֓֟֟	3	2	_	6	5 6	h	A (+	-				1	1	1	+	+		-	-		12	=	5	9			٥	1	7	6	5	-		¥	2	ONNEC		1	_			
3			-		.				1	1		+	4			_		ω	ω						2	2			-					1								+	1	4	3	_		ł	+							7			-			σ		1	+					H	AME	CSC CONNECTION NEW AMP	-	+				
		+	+	-		+	-		-	-				+				_				<u> </u>							1				1	-	1								1		_			0	7	710	5	1	30	7	6	1				-	5			1	+			^	ω	Ĭ	OUTRAC	2 NE		+	-			
		+	+	+	+				-		1	1		1							-	-	+								_		1	 -					L		-	+							+	-	-							-	-	_							_				×	W AMP DE	2	-				
			1								1											1					L						1									1			_			-				1										L								-	MP# CH	PDESIGNATION	TOTAL STREET	1				

\$230-D	S230-D	S230-D	S230-D	S230-D	S230-D	S230-C	S230-C	S230-C	S230-C	S230-C	2-0626	0.00-0	A-UECS	S230-B	S230-B	S230-B	0-000	02300	C390 B	S230-A	\$230-A	S230-A	\$230-A	S230-A	S230-A	URECT TO	07.00	DIBECT NO	DIRECTIVO	DIRECT I/O	DIRECT I/O	CARC	DIRECT NO	DIBECTIO	DIRECT I/O	\$-300	S-300	S-300	\$300	5220-G	0	SDADE	S220-G	S220-G	S220-G	0.220	SOUCES	S220-G	S220-F	S220-F	7-0220	6220 E	3-0CS	\$220-F	\$220-F	\$220-E	\$220-E	8220-	3220-5	2 0000	∃_UCCS	\$220-€	S220-D	SZZ0-0	07000	200	Coccs	S220-D	S220-D	S220-C	2-0226	5000	S220-C	S220-C	S220-C		KM BEING SEXVERU				10.	TOTA	ō
	1	N C	1		-[LNE				Ł	1	- 1	i	ı	MIC Z	1	П		ı	-	- 1		MIC 1	ı	1			Ì									-			Ì		C NE	MIC 3	MICZ	1	MIC 1		-	CINE	200	MIC 3	MIC 2	MIC 1			CINE	MICS		1	MIC 1			L	100	1	- [١			F	Z	MIC 3	MIC 2		3441		İ	-	AL AMPCI	TOTAL OUTPUTS	TAL INPUT
	+	RKSOR	+	-	-		_	RKS08	_	-	┡	+	1	-	-	-	XXXXX	+	+						RKS08																	Ī		RKS07	RKS07	NOO!	DK SO7	RKS07			XXVV/	2007	PKS07	RKS07	RKS07			RKS07	KKUO/		DK-07	RKS07	_		NAOO!	2000	DVS07	RKS07	RKS07			10001	PKS07	RKS07	RKS07	RACK	Ş			Ł	-1	82	
H	,	3 2	2 5	3		-		A 16	15	1	13		1	1	10	9	2	ļ	†	1	Т	Δ	╗	╗	A 1				1	-	-	L								-	l	1	+	E 22	-	t	+	+			t	+	+	m	+			t	n e	t	†	E 7	_	L	п	n n	t	T .	1			1	3	C 21	S07 C 20	PP JACI	A ON		ŀ	l		-	_
	1 CINET 100	DANIEL 188	DANEI 188	PANEL 188	PANEI 188			PANEL 185	PANEL 185	PANEL 185	PANEL 185				PANEL 182	PANEL 182	PANEL 182	PANEL 182				PANE 179	PANEL 179	PANEL 179	PANEL 179																			PANEL 176	PANEL 176	FANEL 1/6	DANE: 476	PANEL 176			-							PANEL 170	PANEL 1/0	- CANCE - 170	DANIEL 170	PANEI 170			PANEL 16/	האותר וסי	DANIEL 467	PANEL 167	PANEL 167			LAMEL 10#	DANIE! 164	PANEL 164	PANEL 164		DESC / SOURCE	STURING					_
						4	- N			-			Care	Z						C. C.	i i																					FINE	N N							- LNE							CINE.					-		LINE							LINE						TYPE						_
77,000	DVSOO	İ	İ		1	1000	RKSOR						77000	BKSNB					İ	10000	DIVENS	ł	Ì					ľ	ŀ	1	-			t	1							NOO!	PKS17	1	_					RKS07		ŀ			1		RKS07				Ì	1		RKS07		l	l	-	1		RKS07		1	1	1	RACK	5						
α 2	$^{+}$	Ī	Ţ	Ī	-	ī	n 1						0	t			_			0	t	I	1													1	1	_				1	+				1	1	+	F 18			Ī			+	F 12					1	1	F 6		Ī	1	†	1	┪	D 18	t	1			무	ATION	0	F		1		
I O ROOM						I C ACOM	TO BOOM						CROOM	TOBOOM						CACCE	10000																					2003							_1	TO ROOM						4	TO ROOM					-		TO ROOM						+	TO ROOM	ŀ				×	DESC / SOURCE	OUTPUTS					
RKS08					KKSUS	2000						RKS08		-					RKS08							,	•••								10000	DKS07	BKS07	RKS07	RKS07	RKS07								10000	DKS07							BKS07				_		To the second	RKS07							RKS07	_						LOCAT				,		
AMP-81					AMP-81		l					AMP-81					_	_	AMP-81		ļ			1				L							Ciri	AMD	AMP	AMP	AMP	AMP-74	L	_	1					- 1- Mary - 1-4	AMA		_	L			200	AMD-74				_			AMP-74							AMP-73							TON DES	АМ					
81					93							-81				,			81						İ											71	71	-71	-71	-74									74				-		1	74						1	-74							-73				İ			OCATION DESIGNATION	AMP OUTPUT CHANNEL				SZ	
₽					3	t					1	2 B			Ī				1 A				-	_	Ī					I	1				4	0000	200		1 SP2	۵ د								-	2					I	t	o n					l		-			_		1		2			1	1	1		CH ARE	CHANNEL			100	202	
CX204V		-			CX204V			l	İ			CX204V							CX204V																000000	CYDOAV	NVCX.	0 CX204V	0 CX204V	CX204V						_		A STONE	CYN					l	00000	NOCY O						07.204	CXXX				l		0,000	CXOOA			İ		1		A DESC		_			TI AM	
RKS08	RKS08	RKS08	RKS08	RKS08	RKS08	RKS08	RKS08	XXXXXX	NA SUG	2000			RKS08	KKKOO	NAGOO	80070	RKS08			ı	KKS08	KKSUS	KASOB	NA COUC	DV SOO	PKS07	RKS07	RKS07	RKS07	1200	DKS07	RKS07	RKS07	KKVO/	1						RKS07	RKS07	77,007	20270	RKS07	RKS07	KKSU/			RKS07	RKS07	RKS07	ZNOO!	KK GO			RXS07	RKS07	RKS07	RKS07	XXXXV	-	- 1	RKS07	RKS07	IRKS07	KKS0/	1000			RKS07	RKS07	NAOO!	0000	BK:S07		RACK					NSB SOUTH AMP ROOM 305-431	
2 8		4	_	_	L	L	L	L	ļ	ļ	1	4		L	1	1	4			L	L	L	ļ	ļ	1	4	_		L	ļ	1	п	ш	п	9	2 5	2 !	2	2	2	_	_	,,,		_	m	ļ	_	1					1	-	1	_	_	_	L	L	1	1				-	1	1			L	L		-		PF	NEW PP LOCATION	L		000	305	
4 24	22	2	22	19	3	18	5	15	14	1	4,	•	だ	10	ď		,	7	_	6	4	3		, -		24	23	22	21	1	2 !	23	8	21	ā			14	13	72		18	a	100	15	14	13	=	1			-	l	,	t	t		1		H	-	t	+	+		H	t	t	t	†		H	t	t	†		JAC	CATION			3	421	1
RKS08	RKS08	RKS08	RKS08	RKS08	RKS08	RKS08	RKS08	RKS08	KKSUS	סטפראו	BK500	BKSNB	RKS08	RKS08	KNOUG	111000	RKSON	RKS08	RKS08	RKS08	RKS08	RKS08	KKS08	KNOOO	DIV SOO	DKS07	RKS07	RKS07	RKS07	ימפיאי	DV COT	RKS07	RKS07	RKS07	VASA/	77.007	0000	RKS07	RKS07	RKS07		l	П	1	-		ı	ļ	1	Į			ı	1	1	П	ı	- 1			ı	П	1	1	٠	ı	ı	ı	1	١			ı	П	П	1	RACK						
오오	2	9	2	3	2	01	2	2	97	2	2 5	2	2	2	9	2 5	2	2	9	2	9	9	9	9	2 8	23	03	03	03	ε	3 8	8	03	03	S	3 8	3 8	3	03	ස	ឧ	8	8	3 8	23	03	03	દ	3 8	23	8	03	03	3	8	3 8	3	ឧ	03	03	03	8	3	8	ន	22	02	5	3 8	3 1	_	_	1	1	4			QSC I/O					
	6	5 1	1	3			123	=	10		,	1		00	-	1	2	J.		_	4	3	2	-		à	3	14	13		1						-				_		k	3 :	4	6	9				۵	7	o.	0				4	3	2	-		-		16	15	14		à			12	=	ē	\$!	2	NPCT	OCUNE					
4						3						1	2			-				_										۰	•	7	6	5							4	3	,]				,	J,						-	-							4							ယ					2	TURTUO	O CONNECTION					
			ļ		ω						,	,							_																۵	-	1	,	'n	4					ļ			ú	,						_	,						-							,						-	2	AMP OUT						
																																																																			•										RACK	NEW AM					
	1	1							_	-							1			_	_				t	1			_		+			_			1						l		1				1			_	ŀ		l	\dagger				-		-		1				l				-	-	}	1		AMP#	NEW AMP DESIGNATION					
										L										_														_																		-											1					Ī		I							유	ATION					

PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	BACINO	PAGING	PAGING	S-200	S-200	S-200	S-200	S-200	\$200	32W	925	200	5321	5351	200	2002	1766	2002	288	8322	S322	2700	2200	3 -	231	S311	S311	S311	8311	8311	2313	8313	2313	S313	2372	2313	02001	110070	SZ30-H	SZ30+H	S230-H	S230-G	S230-G	\$230-G	S230-G	S230-G	S230-G	3030	2007	3304	SZ30-F	5230+	3230-E	S230-t	S230-E	\$230-E	S230-E	\$230-E		RM BEING SERVERD				7.	
MIC2	MIC 2	MIC 1	MIC2	MiC	MICA	MIC.	110	100	200										1	CINE	MIC	MICA	MIC 1			LINE	MIC 3	MICZ	MIC			-	Z C	NIC 3	MICO	N C	1	LINE	NIC C	MIC S	100			LINE	MIC 3	MIC 2	MIC 1		_	CINE	MIC 3	MIC 2	MIC 1	1	UNC	MIC 3	MIC 2	MIC			LINE	MIC3	MIC 2	MIC 1		ERD TYPE			TOTAL AME	TOTAL QUIPUTS	
RKS09										1	-								-		ı		RKS08	ı	-			ŀ	RNSUS		1	ŀ	1	1	RKSOR		1		1	1	NASON AND AND AND AND AND AND AND AND AND AN	ı	ł		1		RKS08	П		П		RKS08	1	+		RKS08					1	1	ı	RKS08					ı		İ
	0										1					L	ŀ	t	+	+	+	+	m	+		-	+-	+-	ī	+	+	+	+	+	ΠI		1	+	+	+	n n	+	ļ	+-	+-	+-	0	Н	-	-	\rightarrow	0		-	+	0 0	+	+	+		08	ဂ	c	0	끃	LOCATION		Н	<u>2</u> 2	83	
5 C	P.	4 P	1	ı			1	2 3		+	+	-	_				-	-	+			4	19	L					1 3		+	1	-1	-[0	7		- 1	2 2	- 1		1	ļ				19 P					# 2 E				9				L			2 P	1 1	JACK	1	Н		L	L	
PANEL 116	NEL 008	NEL 008	WEL 007	NEL 007	NEL 006	NEL 006	WEL OUT	SALL ON	NICT ONE											WEL 448	WEL 448	NEL 448	PANEL 448			NEL 446	NEL 446	ANEL 446	PANEL 446			110	WEL 413	VIEL 413	PANEL 413	MEI MA		VINET 411	VINEC 411	ANEL 411	PANEL 471	1		ANEL 200	ANEL 200	ANEL 200	PANEL 200			ANEL 197	ANEL 197	PANEL 197	ANEL 197	-	ANEL 194	PANEL 194	ANEL 194	ANEL 194			ANEL 191	ANEL 191	ANEL 191	PANEL 191		DESC / SOURCE	UTS				
							-												CINE						LINE						CINE						LINE	, in					CNE						LNE					LINE						LINE						34A1					
						L	-					1	-			L.	_		RKSOB		H				RKS08	_	_				KKSOS	l			+	+	KKSOS	L	+			-	KKS08					Ш	RKS08	1	+	-		TAX SO					L	RKS08					RACK			-		!	
						L				ļ	+	1	+						-F	⊢		_			В F			L	L	L	7	+		1	1		7	+	-	1		L	0	+	L			-	8		1	1	1	0	٠.	L				0					P	LOCATION				l	
		-					L			ŀ	+	1	-						24 10	┖	L			_	18 10	-				_	12	1	-	+	-	L	0	┸	-		L	L	24 TC	丄				Ш	# 7	4				12	1_	L		_		6 77					JACK	N	OUTPL			1	
																			TOROOM						TO ROOM						CROOM						CROOM	2021					TOROOM						TOROOM	4000				OROGN						OROOM						DESC / SOURCE	ПS				
	-		+						ļ	l					ı	RKS08								RKS08						RKS08			_			RKS08						RKS08						RKS08					KKS08				_		RKS08							LOCATION					
									AMP-85	AMT-85	AMP-do	AMIT-00	AMD 95	AMD-84	AMP-84	AMP-84	AMP-84	AMP-83						AMP-83						AMP-83						AMP-83						AMP-82						AMP-82					AMP-82						AMP-82							DESIGNATION	AMP OUTPUT			NS.	
	1	1	#	1	-	1										2 S		4		_		_		3			1			2	-	ļ	F	ļ	ŀ	-		F	F			4					Н	3	1	1	+	#	2	✝╌	_				_			7	1	1		오	Ĭ			BSO	
		1	Ť	+		1			230 CX20	20 CX20	30 CX20	20 CX20		CV	CXX	SP10 CX204V	70 CX20	CX2	_		_		1	CX204V		+	_			CX204V	L	ŀ				CX204V			ŀ			H CX204V	L		-	-	Ц	G CX204V	1	1	+	+	F CX204V	L					E CX204V	Н			-	1		AREA DESC	"	+	_	UTHA	
RKS09	RKS09	DESCO	PKS00	BKS00	RKS09	RKS09	RKS09					TKS08	77000	DICOG	NAV PKSOR	AV RKS08	V RKS08	14V RKS08	RKS08	RKS08	RKS08	RKS08	- 1	- 1	RKS08	RKS08	RKS08	RKS08				RKS08	RKS08	RKS08	RKS08			RKS08	RKS08	RKS08	RKS08			RKS08	RKS08	RKS08		04V RKS08	RKSOS	RKSOB	RKSOS	RKS08			RKS08	RKS08	RKS08			RKS08	RKSD8	RKS08	RKS08	RKS08		RACK			- 1	NSB SOUTH AMP ROC	ı
0		200	,	,	,	ا د	D	ဂ	91	- 01	9	L	1	1	1	1	4	_				_	4	1	4	1	4				L	L	L	L		L	L	L	L	L		L	L		Ц			2 0								Ц										PP JACK	EW PP	+	$\frac{1}{2}$	DM 305-431	
7		T	1	T	1	1	1				İ	T	Ī	1	†	†	1			1	1	1	1	1	1	†	1	1				l	t	r	T	H	l	t	t	t		-	H	H	1	1	†	7 6	Ť	+	t	t	t			H				6	1	1	1		+	Ş.	CATION	+	-	431	
		ļ		+	+	1	1	- 1	ì			l	ı	П	1	1	-	4			- [ı	-	1	1	-										١						Ш	1	- [RKS08	1							ш	- 1	Į	Į		-	-		곳	-	CK RACK	7	+	4		
		L	1		1			4			L	L	1	1	1	1	4	_	4	4		4	1	4	4	1	1	4				L	L	L	L		L	L	L						_	1	1	1	1	1	1			L	Ц	Ц	\perp							╛							
+	+	-	1	+	+	1		1	ន	ಜ	ឩ	8	5	3 8	3 8	3 8	3	ឧ	8	8	ස	ន	ឧ	3	<u>ء</u>	3 8	3 8	8	ឧ	ឩ	3	జ	ຂ	ឧ	ឧ	03	03	3	ន	ឩ	ន	22	02	8	ន	ន	ន	8	3 8	3 8	3 8	8	ន	ន	92	02	ន	ន	ន	_	_	_		_		7	0801/0	+			
				-	-	-	1	-	-		_	L			1					6	5	4	ಪ	1	j	3	=	ò	9				7	o	G			4	ω	2	_			16	5	14	3		ķ	3 =	į	9			8	7	6	5			4	ω,	2	_ !	오	NPUT	CONNE				
								_											4						ı						2						1						4					,	اه					2						-				!	2	OUTPUT	CTION				
	l								3	11	ä	9	œ	-	10	,	٦.	4												2						_						4					,	۵					2						-					9	2	NO AWV					
																							T	1				1	1	1																	İ	T	T	1							1	1	1	1	1	1				RACK	NEW A				
+	+		ľ	F	ł	+	1	1	1						ł	1	+	+		1		+	+	+	+	+	1	1		1			-	L	L	H		L	H	H		-	-	-	+	+		+	1	+	Ŧ	H	H				+		-	+	1		+	+		RACK AMP# CH	MP DES	+	-		
+	+	H	H	t	+	t	+	+	+			-	H	t	ł	+	+	+	-	+	+	+	+	+	+	+	+	+	+	+	+	H	H	H	L	Н	_	Н	H	H			-	+	+	+	+	+	+	+	+	ŀ	H		+	+	+	+	+	4	+	+	+	+	4	*	Ž.	+	4		

PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	FAGING	PAGING	DACING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PACING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	and and	DACING	DAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	DACING	DAGING	PACING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGINO	PAGING	PAGING	DAGNA	ייייי טבויייס טבויייס טבויי	DM DENO SEE					
MIC 2	MIC 2	MIC 1	MIC 2	MIC -	NO.	MIC 3	M C	MICS	MIC 1	MIC2	MIC 1	MICZ	MIC -	10.0	Mico	MIC 1	MIC 2	MIC 1	MIC 2	MICT	MIC 2	MIC	300	MIC -	MICI	MIC2	MIC 1	MIC 2	MIC 1	MIC	100	ulCo.	MIC 1	MIC 2	MIC 1	MIC 2	MIC 1	MIC 2	MIC 2	MIC 1	MICZ	310	10.0	MC -	MIC 1	MIC 2	MIC 1	MIC 2	MIC 1	MIC 2	MIC 1	MIC 2	MIC 1	MICZ	MICT	MIC	MIC 1	MIC 2	MIC 1	MIC 2	MICT	MIC 2	3 C -	MICZ	310	MICA	100	NIC A	MC -	100	1	Z P			TOTAL AMP CH	TOTAL OUTPUT	I O I AL INTO
RKS09	RKS09	RKS09	RKS09	8000	2000	2000	0003	RKSOS	RKS09	RKS09	RKS09	KKKOS	S S S S S S S S S S S S S S S S S S S		RKSOO	RKS09	RKS09	RKS09	RKS09	XX.CG	KK SOS	ZK SOS	77008	2000	RKS09	RKS09	RKS09	RKS09	RKS09	7000	2000	DESCO	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	XXXXX	NOO'S	10000	DVS00	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	KKSOS	KK SOS	KKUUS	RKS09	RKS09	RKS09	RKS09	RKS09	RKS09	RKS08	KKUUS	KNOOS	TRUCKS	DVS00	DKSOO	RKSOS	0000	BACK I DD I JACK	3	ŀ	ı	154		ı
15 15	-	m 14 F	13	3 2		3 2	3 :	3	=	3	7	ے		,			7	7	6	o.	o	, ,	4	,	4	ω,	ű	_	_		2 1	2 2	23 !	23	23	B	2	C 21	20	C 20	120	1	:	: 1	; ;	17	17	16	C 16	15	15	14	14	13	13	12	C 12	1	C 11	10	C 10	9	9	a	0 0	,	7	10	0 0	2700	B C	TON TO				_	
PANEL 328	ANEL 327	ANEL 327	ANEL 326	ANEL 326	ANEL 320	ANEL 323	AND SEE	VCE INV	ANE 374	ANEL 323	ANEL 323	ANEL 322	ANEL 322	WINCE OZI	ANIEL 304	ANE 321	ANEL 320	ANEL 320	ANEL 319	ANEL 319	ANEL 318	ANEL 318	ANEL 31/	ANEL 31/	ANEL 347	ANEL 316	ANEL 316	ANEL 136	ANEL 136	ANEL 130	WINET 199	ANEL 195	ANEL 134	ANEI 134	ANEL 133	ANEL 133	ANEL 132	ANEL 132	ANEL 131	ANEL 131	ANEL 130	ANEL 130	WILL 179	WALL 179	DANEI 120	SCE 13NAC	ANEL 128	ANEL 127	PANEL 127	ANEL 126	PANEL 126	PANEL 125	PANEL 125	ANEL 124	PANEL 124	PANEL 123	PANEL 123	PANEL 122	PANEL 122	PANEL 121	PANEL 121	PANEL 120	PANEL 120	ANEL 119	ANEL 119	PANEL 178	ANEL 110	TANEL 11	PANEL 11/	DANIEL ALZ	DESC / SCORCE						
																																	1					i																																	TPE	1					L
															ľ	Ī														ļ			I		1					_			-	Ī												_											ľ			Z CX	LOCATION						
								l	1															İ					-	-		ļ										İ												_		L				_		_						-		JACK			-		-		
																																																																						i de de la constantina della constantina della c	DESC / SOURCE	PUTS					
		1																																																																					LOCATION						
				į																																		-																																	DESIGNATION	AMP OUTPUT CHANNEL				SN	
										-																ļ	ļ	I		_																I								_																	CH AREA	CHANNEL			000	NSB SOUTH AMP ROC	
20	20 2	2 2	2 2	20	2	Į.	2	ŽŽ.	3	2	2 2	0	20	20	20	2	2 2	2 2	0	70	R	20	R	R	20	1 2	2 2	0 2	20	70	70	R	7	12	12	2 2	0 2	0 :	0 :	70	Z)	ZD	70	20	Z	7	3 2	70 :	70	20	70	20	מ	20	70	R	Z	70	20	20	R	20	20	70	TO AT	R	20	20	20			H			7 (10)	AMP R	
RKS09	ŝ	600	Soo	808	ŝ	(S09)	(S09)	\$09	(509	808	300	Sna	\$09	\$09	\$09	900	1009	è	Sna	608	éso9	SO9	(S09)	KS09	KS09	KSOS	1505	COO CO	60S	KS09	KS09	KS09	KSUS	KSOS	200	200	1000	Cena	SOO	KS09	KS09	KS09	KS09	KS09	KS09	Kooy	1000	KSOG	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	KS09	RKS09		RACK	NEW F			COL	Š Š Š	
m	n n	n - -	-		7	т	'n	m	-	"	·	7	m	F	m	т	П	1	1	m	7	m	7	щ	7	m	1	n	m	0	ი	0	1	c	, ,	•	,	,	- «	n	ь	C	0	ဂ	0	c	, c	-	0	0	0	0	ი	0	ဂ	o	ဂ	0	0	0	n	0	0	0	ဂ	0	0	0	ဂ		공	NEW PP LOCATION			1	M 305-431	
15	1 5	13	3 2	3	12	12	11	=	10	6		0	20	8	8		_		20 (5	5	5	4	4	ω	3	-			24	24	23	23	22	3 8	2	2 5	2 5	3 6	8	19	19	8	18	17			5	5 6	35	15	14	4	3	13	12	12	=	=	6	6	9	9	8	œ	7	7	G	6		RACK					-	
																																																1								-														유	I/O# INPUT	QSC I/O CON					
					1																1							-																																	1					1				유	OUTPUT AME	I/O CONNECTION					
																																							-																															오	OUTRACK	NEW AN					
 			<u></u>	+	+								†	1						1	†						-							-	-		-	-	+	1	+								1	+	1			1						+	1				-				-		AMP#	NEW AMP DESIGNATION					

											2		DIRECTIO	DIRECTIO	DIRECT I/O	DIKEC: I/O	0110	DIRECTIO	DIRECT I/O	DIRECT I/O	S-206-425	S-205-421	9-20-200	0.000000	2005006	SPARE	S-206-437	919	3	918	S-100	8	3 5	3	\$100	S-200	S-200	9200	920	2000	I NNE	S-205-416	9106-410	0-100-14/	2 2 2	CANODY SE	CANOPY-SW	\$-200	S-200	PAGING	PAGING	PAGING	200	PAGING	PAGING	PAGING	PAGING	PAGING		PAGING	PAGING	PAGING	PAGING	O GIVE	DACING	PAGING	PAGING	PAGING		VIN DEING GENALING	DE DEINO						
		1																																1						-										×	3	3	3		2	Z	M	M			N.	×	3	31		2	4	×		CVACVO				TOTAL	IOIALOU	TOTAL CLITTELITE	TOTAL
H	1	+	-	-		+								-	_								ļ	+	1													Ĺ					ļ.	L	-						MIC 2		ı	Т	-			1	۱	ı				ı	ı	1	-			L		-		MPCH	7010	1 2 0	NIGHT C
H			l												_																			1		-					1				ļ					RKS09 F	E 60S																			٦۶	200			154	8	3 5	373
	-	-					ļ						1					1											1					1				L		Ī	1						1			23 P	23	12	1	3 2	3	21 P	20	20 P	9	5	19	18 P	18 P	1	;	17	16	16 P	JACK							1	_
																									Carr																									PANEL 336	ANEL 336	ANEL 335	ANEL 335	ANEL 334	ACC INA	ANEL 334	ANEL 333	ANEL 333	HAREL 30Z	AND PRO	ANE: 332	ANEL 331	ANEL 331	ANEL 330	ANCI 220	ANEI 330	ANEI 320	ANEL 329		ESC / SOCKCE	NTCI O	170					
$\ $																		1				-															_										-					_											_							1756							, ,
H	ļ	ŀ							l			_	-	l	1		ŀ	ļ	1		-	-							l	1	,				1					-										-					1			_	-		1				ł	1	1		RACK	_		ŀ					
H	ļ					F	L	ŀ		1							-		+	+	1			-	<u> </u>		-			+					1	1	,	_		-	+		_			-		+	-					-	+			_			1	-	_	-		+	-		PP JACK	OCATION			+				
H	ŀ			H	ŀ	L		L	l		_		ŀ			_				+	1		L						L	1	_									ļ	l	1								-				F	1	+								L			1	+	ACK	DES	OUTPUT		1				
	The state of the s																	A Proposition of							- Performan																																													C / SOURCE	OUTPUTS						
								-	ŀ	1					1					1000	BKS00	RKS09	RKS09	RKS09	ZNOO2	DIVERDO	RKS09	RKS09	KNOON	1000	PKSNA	RKS09	RKS09	KKSUS	1000	DK SOO	RKS09	RKS09	RKS09	RKS09	KNOUS	Dreno	RKS09	RKS09	RKS09	RKS09	KKSO9	10000	BKSNa							+	1				Ì	-						1		LOCATION							
																				Civil 190	ANDOR	AMP-96	AMP-96	AMP-96	CR-JMA	2000	AMP-95	AMP-95	AMT-95	Civil Michigan	AMP-94	AMP-94	AMP-94	AMP-94	AME -90	AMDOS	AMP-93	AMP-93	AMP-93	AMP-92	AMP-92	3	AMP-97	AMP-92	AMP-91	AMP-91	AMP-91	AMP	AMBO	1																			-	_	AMP OUTPUT CHANNEL				Ž,	2	
				4		_			Ĺ	ļ	1			-	+	1	_		-	,			2				3		ı	,	- 1		N							4						3			-					_	ŀ	+	1			ŀ	ļ	-		_	_	-	-			모 오	T CHANN	L			c C	3	
																	_			02.20	0000	CXO	CX20	CX20	CX20		CXO	SB CX20	SB CX20	00	CYO	SB CX20	SB CX20	SB CX20	CV7		CYO	P20 CX20	P20 CX20	CX20	CX20	200	CXO	CX20	SE CX20	SW CX20	SP30 CX20	3F30 CAZ04V	200		-					1			_	_	l	1		_				1		REA DESC				1	NOT TOO IT AME	1	
+				+	-					77,00	DVC	RKSO	RKSO	RNOL	200	Dist	RKSO	RKSO	TANGO.	NA.	200	AV BKS	4V RKSD	₽KS0	RKSO	200	AV BKS	4V RKSC	RKSC	AV AVOC	DVC	₽KSC	4V RKSC	4V IRKS	KNOC	200	AV DKS	4V RKSC	4V RKS	4V RKSC	77.00		AV DKS	4V RKS	4V RKS	4V RKS	4V RKS	TANK.	מאסו	DKSNO	RKS	RKS	RXS	RKS	KKG	200	DKS	RKS	RKS	ZK.C	2 2	1000	PKS	RKS	RKS	KKO	ZN.O	DVO	Ì	RAC				1	č	3	
+				-			-			2	1	4		L	1	1	_	L	L	L	1	1	_		L	L	1		L	L	ļ	_		L	L	ļ	1	4			L	1	1		_	L	L	L	1	0 0				L		1	1	4		L	1	1	-	_	L	Ļ	L	1		Î	NEW PP LOCATION				OM 305-431	?	
+		1								t	1	1		l	t	†			r	t	t	1			H	t	†	1	_	l	†	1	Ī	H	İ	t	†		7		H	t	†	1	_	H	l	t	t	†	†	+		H	H	+	1	+		H	t	1			H	t	t	t	-	ېر م	LOCATIO	_			543	;	
		-								L	ı	-		ı	ı	ı			ļ	L	ı	1	١			ı	1			l	1	ı				1	1	-			ı	1	1	١				KKSUS	П	3 8	3	3	13	3	3		5 6	Š	9	9	0		*	7	7	σ.	a	5	- 1	CK RACK	_						
-		1	+					_	_	L	1	1	_	L	L	1		_	L	L	L	1			L	L					ļ				L		1				L	L		1		L	L	9		1		1										-					L	-			ည	L					
		1		+		1				a	t	3 7		H	t	t	1		r	t	ſ	T		1		F	1	-		ľ	ľ		1	_	ľ	ſ	1	1	1	_	Ľ	ſ		1	1	_	F	ľ	1	-	+	1			-	+	+			L		1				-	-	2	2	# INPL	30 1/0 001						
	1	1	+			+					+	1			-	1				-	L	1			L	-				_		1			-	-	1	-		-	_	1	1			_			-	+	+				_		+			L		-					-	2	2	T OUT	NNECTION	_					
+		+		+	$\frac{1}{1}$	-	-				1			_	ŀ	1				24	23	3 2	23	21	20	16	,		17	ī	;	1	1	13	12			3	9	8	7	0		۸.	4	ω	2	_	_		1				L	l				L	-						_	2	2	AMP TO	QSC I/O CONNECTION NEW AMP DESIGNATION	H	L				l
+	1	+	-	1	1	1										+					ľ	ľ			_	Ľ	ľ		_	<u> </u>	ľ			_	Ĺ		ľ	1	1	_		_	ľ					_		-	1						-	1	1		L	ļ	1						-	OUTRACI	NEV						l
	-								_																						-									Ì																			ĺ					Ì				l	ľ	1	ş						
	+	+	†	Ť	1	T	T	7	_	٢	t	+	+		t	t	+		Г	Γ	Γ	Т	T	J		ı	T	7		ĺ	Т	Т	1		Г	1	t	+	+	-	-	╁	+	+	+	-	-	H	t	╁	+	+	+	-	H	t	t	+	+	•••	H	ł	+	4	_	H	H	ł	1		힑		-	1			

NA1	NA1	NA1	NAT	TAN I	NA.	NA.	NA.		NA.	NAT	¥.	¥1	¥	NA1	NA.	NA.	NAT	NAT	A	NA1	NA.	Š	100	3	NA.	NA	TIELLINES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	- IT-LINES	I E-CINES	I C-LINES	THE LINES	TIEL LINES	TITL LINES	TIEL LINE	TIELLINES	TIELINES	TIELNES	TIE-LINES	TIE-LINES	TIE-LINES	TIE-LINES	E-LINES	- IT-LINES	The LINES	TITLINES	TIE LINES	TIEL NEG	TIEL NEW	TIEL NEG	TIC LINES	TIE LINES	TIE-LINES	TELLINES	110000	TO CINES		TIE I MICC	TIEL NES	TH-LINES	TIE-LINES	TIE-LINES	TIE-LINES			AN OFFICE OFFICE	DIA BEING CED					
MIC 2 RKN02	- 1	- 1	MIC 2 IRKNOZ	1	ı	•	ı	1	1	П	- 1	J				ı	1	1	1	ı	ſ		ı	1	1	1									TO COME NAMED	THE LINE RANGO	THE DESIGN	TIE I INC BYNOT	TIEL INE RKNOT	TIEL INE PKNOZ	TIE-LINE RKN07	TIE-LINE RKNO7	TIE-LINE RKN07															TIETLINE KNOC	THE LINE AND	TICHLING RONGE	THE LINE DIVING	TIEL INE DENIC	TIE-LINE RKNO2	TIE-LINE RKN02	TIE-LINE RKN02	TIE-LINE RKN02		KACK	777	TVD.	1		OTAL OUTPUTS 66	TOTAL INPUTS 45	
B 2 PANEL 048		2 2	3 23	21	20	19	1	17	ō	;	;	14	13	12	11	10	9	æ	7	8	A 5 PANEL			_	PANEL	A DANIE!							İ		C 24 CKOM	C 23 FROM	T T T T T T T T T T T T T T T T T T T	22	MOM:	2003	19 6	18 FROM	_ 17 FROM .										† 					2	2	٠,٠		- 6	2	J 15	J 18	J 17	_	15	LOCATION DESC	1		-	9	5	
48 8	100	47	47	347	005	105	105	005	JU4		504	004	004	003	003	003	003	002	002	002	002	001	001	001											ECH SERVICES (F.O.)	TROM TECH MERVICES (F.C.)	ECH SERVICES (F.C.)	non services (r.c.)	ECH SERVICES (F.O.)	FOL SEBVICES (F.O.)	ECH SERVICES (F.O.)	ECH SERVICES (FO)	ECH SERVICES (FO)								400							SOUTH AMP ROOM (F.O.)	SOUTH AMP ROOM (F.O.)	SOUTH AMP ROOM (F.O.)	COLUMN TOOM (T.C.)	SOLITH AMP ROOM (F.O.)	SOUTH AMP BOOM (FO)	SOUTH AMP ROOM (F.O.)	SOUTH AMP ROOM (F.O.)	FROM SOUTH AMP ROOM (F.O.)			SOURCE	NPUTS					
																_										TO-LINE XONOY	70,00	TIE-LINE BENOZ M	DKN07	RKN07	RKN07	RKN07	TIE-LINE RKN07 M	RKN07										RKN07	RKN07	RKN07	RKN07	RKN07	RKN07	RKN02	KKNOZ	RKN02	RKN02	RKN02	TIE-LINE RKN02 M	RKN02	TIE-LINE RKN02									•		RACK	łΟ				_1		
																										24 TO LECH SERVICES (F.	24 TO TECH SERVICES (F.	TO TECH SERVICES (F.	TO TECH SERVICES (E.	21 TO TECH SERVICES (E)	20 TO TECH SERVICES (F.	19 TO TECH SERVICES (F.	18 TO TECH SERVICES (F.O.)	17 TO TECH SERVICES (F.									10 1001 0010	24 TO TECH SERVICES	23 TO TECH SERVICES	22 TO TECH SERVICES	21 TO TECH SERVICES	20 TO TECH SERVICES	19 TO TECH SERVICES	24 TO SOUTH AMP ROOM	23 TO SOUTH AMP ROOM	22 TO SOUTH AMP ROOM	21 TO SOUTH AMP ROOM	20 TO SOUTH AMP ROOM	19 TO SOUTH AMP ROOM (F.O.)	18 TO SOUTH AMP ROOM	17 TO SOUTH AMP ROOM											PP JACK		OUTPUTS					
																										5.5			7			9.0	5.)	5.5																F.O.)	F.O.)	F.O.)	F.O.)	F.O.)	F.O.)	(F.O.)	(F.O.)			,									LOCATION DESIG	AMP					
										_																-									_																																		CH AREA	AMP OUTPUT CHANNEL			NSB NORTH AN		
RKN02 B	-	RKN02	+	+	+	Ŧ	+	+	-	4	L	RKN02 A	L	L	1	+	1	+	+	+	+	+	+	\downarrow		_	L	L	L	ļ	1	1	1	4				L	L		ļ.	L	ļ	1	1	1	1	4		-	_				RKN08 B	4						L		ł	DENING	4			DESC RACK PP	NEW PP LOCATION		, COOM 001 +C	NSB NORTH AMP ROOM 301-433		
ω 2) -	24	23	2 2	2 2	200	10		17	5	15	14	13	12		ī			•	400	0	n 4	A (اد	2	-	16	15	14	13		3	1	10	9	16	15	14	13	12	11	10	9	22	3	2 6	3	19	18	17	80	7	o	5	4	3	2	1	8	7	6	(Ja	•	C.		. د	•		- 1	JACK RACK	- 1			ند		
																																																																			ġ.	CH CH	NPUT OUTPUT	QSC I/O CONNECTION				1,00	
																																																																			9	CH	I/O# INPUT OUTPUT AMP OUT RACK AMP# CH	NEW AMP					
	Ī																							1																						1													1				_						AMP# CH	DESIGNATION			Τ		

N	8	NB	S	ă	ő	B	8	NB	E.	6	5 6	S	No.	N	ă	20 1	5	B	NA2	NAC	Ę	NA I	NA)	₹	æ	æ	NA2	Š	Ž	200	NA.	NAS	NA2	NAZ.		CAN	NA2	NA2	NAZ.		NA S	CAN	NAS	æ	NAZ	5	3	Z.	8	5	3	SAN	NA.	NA1	5	NA.	Š	NA.	NA1	3	101	NA	š	Ā	4	1	NA.	×.	NA.	5		Ä	NA1	NA1	NA.	- A	NA	NA.	7		RM BEING SERVERD			I			
L	×		Z			2	2	~	_				2	-	2		2	7					İ						L				_	-				_	-					_																									_															Į.	7074	TOTAL C	CIA
	MIC3 F			ı	1	- 1	- 1			ı	1		- 1		1	-	- 1																LINE		ſ	I	- 1		ı	F	ı		1			ı	1			ı	ı	-										1			ı	П	1				ı	1	١			ı		П		1	34/1			AMPCH	2000	TOTAL OUTPUTS	NEG
	RKN02 D																				L									ļ	-	-	_	_	1	+	-	_	-	+-	+	DKN02	-		_	-	+	_	-	+	+	-				-						-	-+	-	+-	+	-	_	_	-	+	-	-	-	-	-	NAMOZ	4		RACK	ē		L	ı	١	ß	
16	15	4	13	12	=	: ;	3		8	7	σ	,	,	4	u	,	١.	_				l	†	1						t		1	20	19	ā	:	1		15	1	:	1	3	=	10	G	,		7	a		,	1		-	+	+				ł	ļ	5	<u>.</u>	14	5	à i	13	=	ē		۰	œ	7	6	5	1		97101		LOCATION		L			+	_
PANEL 011	PANEL 011	PANEL 011	PANEL 011	PANEL 010	TANEL 010	DANIEL CIC	PANEL DIO	PANEL 010	PANEL 009	PANEL 009	PANEL 009	THE COS	DANEI OOO	PANEL 008	PANEL 008	דאותר טטס	PANEL COS	PANEL 008															PANEL 053	PANEL 053	PANEL 053	TANEL OFF	PANEL 053	PANEL 046	PANEL 046	PANEL 046	TOTALE ONG	DANIEL ONG	DANIEL DAS	PANEL 045	PANEL 045	PANEL 045	1 71400	PANEL 007	PANEL 007	PANEL 007	TANEL OUT	BANEL ODZ											PANEI 051	PANEL 051	PANEL 051	PANEL UST	DANE OF	PANEL 050	PANEL 050	PANEL 050	PANEL 000	DANIEI OSO	PANEL 049	PANEL 049	PANEL 049	PANEL 049	PANEL 048	DANIEI OZO			DESC / SOURCE	INPUTS					
																												j																															j																												_
		1			_										_						_	_																-	_												L	-																									L			Т	⊒d∧,						
	+	-	1					+		_	_		+	-		_	ļ		-				-			4					L	-					-				-	-	-																			-	1				ļ	1							-				5	יייייייייייייייייייייייייייייייייייייי	I DOMINO		_				
		1			_		l																	İ	1															-								-		_	l	t	+				+						l	_				1		-		l		1				_	JACA			2					
									-								-																																																															DEGC / GOOKCE		STUG					
		-							-									10000	DKNO1	PKNOT	RKN01	RKN01	KKN01	KNNOT	TONO!	DENO	RKNO	RKNO	RKN01	RKN01	RKN01													1								KKNO	TOWN.	DKNO	RKN01	RKN01	KNAS		PKNO	RKN01	RKN01																			LOCATION	1000						
1		-																7.00	AUOTA	ALIO TA	AMP-19	AMP-19	AMP-18	AMT-18	AMP-1/	200	AMD 17	AMP-16	AMP-16	AMP-15	AMP-15							1														AMT-14	7W7-14	AMD	AMP-13	AMP-13	AME-12	100	AMD-13	AMP-11	AMP-11																_				ON DESCRIPTION OF	AMB CITE			NO	ž	
+	ļ	L		ļ			L	-	+	1				-	1			•	اد	•	9	_	2	-		, -	٠,	3	-	2	-	-	1	-		L			1	_	_		L					-				×		• •	2	1	2	,	-	2		L					-	-	1				İ							Š	OI CHANKEL	200		-	NOD NOT IN AME TOO	֭֚֡֝֞֝֟֝֓֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֡֓֓֓֓֓֓֓֡֓֓֡֓֡֓֡֓֡	
1	+			-	+			-			+				1			5	3 2	2 9			œ CX		Ş		2 9			رم و			-	1			ļ	-											1			e S	2	100	6	5 C	0		2	2	<u>۔</u>				4					i		-	1	1	1					AKE A					C I I	ź	
KKNUZ		21	20			30	70	7				70	חל			_	_	V AZ07	72021	2007	7505	1202V	1202V	12027	V2021	V ZUZV	7000	Vene	ACUCI.	(1202V F	(1202V F					-				,		L									_	(1202V	A70713	1	(1202V	(1202V	(1202V	V2024	1	K1202V	K1202V																		١	DESC					AL Z	5	
KNOZ	KN02	KN02	KN02	ZINOZ	KNOS	KN02	KN02	KNOZ	CONING	2000	CONS	KN02	KN02	ALIANY.	CONTRACT	KN02	RN02	CONOZ	CONNOC	1	X NO.	RKN02	KN02	RKN02	KNOZ	CONOZ	200	CONTRACT	SKN75	KN02	RKN02	KNOZ		CONTRA	KN02	KN02	KKINUZ	20102	CONTRACT	KN02	KN02	KN02	KN02	. 708.7	CONT	KN02	XXNO2	ZONIAN	COLVIN	RKN02	RKN02	KN02	KKNOZ	1	RKNOS	RKN02	RKN02	ZONIZI		RKN02	RKN02	RKN02	ZVNOZ		RKN03	RKN02	RKN02	ZOKIZA	CKIO	RKNO2	RKN02	KKN02	ZNIVOZ	DE NOS	PKNOS	RKN02	RKN02			ZACX		Ì					
0	0	0	0	c	,	-	0	0		,	,	0	0		,	0	U	5	2	2	2	01	2	01	9	9	2	2 :	3	2	2	c	,	,	n	0	c	2	2	ი	ი	ဂ	n	,	1	0	ი	c	,	0	ი ი	01	5	2	2	2	2	-	2 !	2	2	00	α	,		œ	00	0	0	D	0	æ	0	0 0	0		8			F	NEW PP LOCATION				M 301-433	;	
5	4	13	12	=	:	6	9	8	ļ	,		5	4	٥	٠,	2	_	20	2	-	1	17	6	15	1	č	;	3	1	6	9	16	5	'n	À	13	12		:	6	9	8	7	٥	,	5	4	c	3	۰	1	8		1 0	5	G	4	ن	3	N	_	ಹ	10	1	14	3	12	-	1	ð	9	œ	-	,	200	5	4			JACK	, io	ATION I			_	•	
					1									l			i	KKNOZ	KKNOZ	ZONIAN	DENIOS E	RKNOS	RKN02	RKN02	RKN02	KKNOZ	20417	2000	SKNO	RKN02	RKN02			İ			-	İ						l	1			l	l		-	RKN02	KKNOZ	2000	RKNOS	RKN02	RKN02	ZOMOZ		RKNOS	RKN02							ŀ				-								RACK	!						l
								_										3	5	9		2	으	9	2	2	2 5	2	2	2	2			1	1			-	1		-	_				+			Ì	1		9	2	2	3	2	2	5	2	2	으	_	-	+	+					-				+		+	-			ò #	C SC	}	1				-
								_																										ŀ																															,														유	NPCT	I/O CONNE						
																																																																															오	OUTPUT	C						
												}						20	8	ā		17	16	5	14	13	ī	=		3	9				ļ																	œ	7	0	2	5	4	ú	,	3	-1																		오	AMP OU							
										L																																																					-																	RACK	NEW AME						
]	Ţ					1	1				Ī		_			1					1													1										I				ļ	1					1					1				ļ										I	1	1				AMP#	DESIGNATION					_	
		1				Ĺ									L																													L																																				유	NON T						

	N-CATWALK					ļ	Ì									l	TWALK	ATWALK	NB	NB	NO	100	NO C	N. D.	SB.	NB	NB.	20		Ž į	ND NO																						-																						NB			KM BEING SERVERU				101	TOTAL	101
	MIC 1		ı		1	Т	1	ı	- 1	- 1				1		ı	-	-															CZ	SIC G	П	П	1			1	ı	1	П	- 1	- 1		l	1	1	ı			ı	1	П	- 1			ı	ı	П	-	- 1			L	П	ı			ŀ	Т	- 1	ļ	MIC 1	l		YPE			-	TOTAL AMP CH	STRATES	L INPUTS
RKN02	RKN02	RKN02	KN02																														RKN02	ZNNOZ	TANK		DKNING	RKN02	RKN02	RKN02	XXNO2	ZNNZ		RKNOS	RKN02	RKN02	KKN02	ZNZZ	2000	RKNOS	RKN02	RKN02	KKNUZ	2000	CONNO	DKN03	RKN02	RKN02	RKN02	KKN02	70102	DKNING	RENES	RKN02	RKN02	ZONIZ	2010	PKNDS	RKN02	RKN02	ZVINOZ		DKN3	RKN02	RKN02		RACK PP JA	ē		ľ	ı	128	ı	
17	N 16	N 15	Z 14	1	t	t	Ť	1	7	7	7		Т	2	t	t	†	2				-	t		-	-			ŀ		-	_	T)	7	1	-	n -	T .	F 7	-	7	1	1	+	F 3	_	-	←	┿	~+	-	_	+	+	+	+	_	_	⊢	⊢	+	-	-1		٠	₩.	4	4	_	_	╄	4	4.	m	_		PP JACK	CATION		F		7	7	_
PANEL 305																- ANG	2	PANE		_		-		1	1			L	L		1	-	PANE	PANE	Z A			PANE	PANE	PANE	PANE	AN		NAC.	PAN	PANE	PAN	FAN		DANI	PAN	PANE	PAN	7		Z	6 PAN	5 PAN	PAN	PAN	1		P	PAN	PAN	FAN	2	DAN	PA	PAN	PAN		2	2 PANEL 012	PAN	L	웃	DES	NPOT	L	ł	+	-	_
L 305	L 305	L 304	L 304	1 304	1 303	1 303	200	202	302	1302	L 302	L 301	1.301	L 301	1 300	2 300	300	300															L 052	1.052	1002	1002	0.00	019	L019	1 019	1.019	LUTO	1000	018	018	L 018	L 017	1.01/		047	1 017	L 016	L 016	1010	1000	1 046	015	L 015	L 015	L 015	- CI+	014	7 014	L 014	EL 014	EL 013	11.010	010	EL 013	EL 013	EL 012	0.016	043	EL 012	EL 012				NPUTS					
																L							L												L					_					-																								- Ann									TYPE						
					L	L																						-																																																	RACK	ارور]		
\mathbb{H}	1	-			L	-		ł	+	İ	1	+			_		ŀ	+	+	1			_				+		-			1		_		ŀ	1		-			_	-	+	1					-	1				1	1	+	-			_	Ŧ	+	1				T	1					1	1			LOCATION			F]		
																																The state of the s																																													JACK	DESC / SOURCE	OUTPUTS					
											Ī							KNO		DKNO	RXNO	RKN01	RKN01	KKNOT	2	0	DKN	RKN01	RKN01	RKNOT	ZZNO	ראואו					ľ													Ī						Ī		1				Ī	1						Ì		_		ı	1				LOCATI			T			
H	+	+				_		 -			1	1	1	-	-			AMP-24		2	awa	AMP	AMP	AMP	AME		210	AMP	AME	AMP	AMT							-	+				L	1	İ	1	-			İ	1				L	<u> </u>	+	1	+			ŀ	+	+					1	1	_	L		1	+			ON DES	ΑM					
																		-24	1	2 1	3	23	ż	22	1	2	2	ñ	-10	-18	ā	5																							!																i							SIGNATION	AMP OUTPUT CHANNEL			100	Z ∩ D	
H	1	‡	‡	1	1				F	ļ		1	+	1	1	-		2	-	,	3	1	N	-		,		,	. 1	2	ŀ		1	Ī		-	F	#	ļ	1				t						ļ	1	1	~		L		+	1	1		_	ļ	1		1				+					l				오 오	TCHAN			0	20	ı
H	ļ	-	-	1	4	-			L		-	+	1	1		_	L	2	=	2 2	3 !	0 0	8 C	7	o C	9 5	2 9	2	э С	2	-		4			L		-	1	-	-					1	1	_	L	L		1		L				1				L	-						1					1		1			É		L	5	Ĕ	
														-				(1202V	A7071	1	300	7000	V202V	(1202V	AZDZLY	A 20.21		2000	1202V	7202V	K1202V							ĺ															ı																									DESC				ACC MONTH VIEW INCOME	à	
RKN02	Z XXX	KIND		DIVINO	RKNO	RKN02	RKN02	RKN02	RKN02	RKN02	KKNOZ	ZONIZZ	2000	DE SOS	BKNO	RKN02	RKN02	CX1202V RKN02	KNINOK	2000	DVACO	RKNOS	RKN02	RKN02	KKN02	ZONIOZ		CONNE	RKN02	RKN02	KNOZ	NO.		RKNOS	RKN02	RKN02	RKN02	ZONIZ	200	RKNOS	RKN02	RKN02	RKN02	KKN02	ZZNZZ	DC NO.	RKN02	RKN02	RKN02	KKNOZ	NAME OF THE PERSON	CONNE	RKN02	RKN02	RKN02	RKN02	1000	DIVINO	RKNOS	RKN02	RKN02	RKN02	ZNACZ	100	SUN	RKN02	RKN02	KKNOZ	ZONIZ	BKN03	RKN02	RKN02	RKN02	ZVIVE				RA Ç						
၈ ေ	0	0	3 6	0	7	၈	၈	၈	၈	6	6	6	9	0	0	o	Ш	L	L	1	4	4	_	L.	L	Ļ	1	4	_		L	Ļ	4	1	_	_	L	L	4	4	-	-	H	-	ŀ	+	+	+	_	H	1	+	-	Н	H	H	+	+	+	+	_	L	╀	+	+	4		ŀ	╀	+	_	_	L	חו	ł	+	1	g	IEW PP LOCATION		H	001-100	2	
17 0	15	14	ī	3 5	3	3	=	9	8	7	6	0			۵,	S	_		_			,	-	ω	N	-		2 !	23	22	2	-	;	1	5	9	8	_	1	,		4	3	2	_		24	23	23	21	2 2	3 8	3	18	17	16		4 4	1	13	12	=	2			8	7	6		,	_	ω	2	, _			1	Š	CATION		_	Č	š	
			l	l							-					-		RKN02	ZXNOZ	ZONOZ		DKNO	RKNO	RKNOS	RKNO	ZNING	NAME	פועומי	RKNO	RKNO	RKN02					_								-		1						1	-	-				l				_			1		_										1	RACK	-					
H		H	H	ł	1	1	$\frac{1}{1}$			_		ŀ		+	-		4	L	L	ļ	1	1	1		L	ļ		1	-	_	L	L			1	_	_		+						L	1					ŀ	1	+	_			ŀ	1	1	-	-		L	-							-	_				+			۵	-				
	-										-	-	ŀ					9	_	-		1	-		-		-		2	3			-			_								-				-					+	-		_	-	t		1		_			1			L		+						,	2	#	SC 1/0 CC		_			
-	-		ŀ					1				L	L	-					-	ŀ		1	1	_	_			1		-		-			_					1	1					l	1	-	_	L			1			-		+						ŀ	-		_				1		_	H			3	2	NNECTIC		_			
					1	+	+	+	-						ł		+	4		4			_	_		N.		,		,		_								1		-		H		-	+					1	+	-	_		-	Ŧ	+					ŀ		-	-		-		-				+			AMI	ž					
+				-	+		1			_			_		-	+	-	ಜ		٦	9	5 6	ŏ	7	6	0	4	1	اقد	3	-		_	+	+				ŀ	+		-					1			L	-	-	1	+	-	_			1	-				L	-	+		_				-	_	L	L	1	É	OI TEL		-	_			
																ŀ											-																																																		CH CH COLLOCK	2	VEW AMP					
-	l				t	t	1								-	1			_		l	1	1							1				†	+				l	l	†	1					\dagger					+	+	1					1	+		-				1	1		-	ł	1			l		-	2001	AMD	DESIGN					
																			_									Ī	1																		I											I	T	1				l			1				1						5	2	NOLLY	Ī		Γ		

N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CA WALK	N-CA WALK	N-CATWALK	N-CATWALK	200	NOATWALK	N-CATWALK	NCATWALK	N-CATWALK	NCATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CA I WALK	INCV. NAV.	N CATAVALA	N CALLANA CA	N A TANA K	N-CATWALK	N-CATWALK	NCATWALK	N-CATWALK	N-CATWALK	N CATANAL K	N CATANA	NI ON TACK	NAME OF STREET	NO TANK	N TANAL K	N-CATWALK	N-CATWALK	N-CATWALK	NCATWALK	NCATWALK	N-CATWALK	N-CATWALK	N-CA TWALK	N-CATWALK	N-CATWALK	N.CATWARK	N CALLANIES	N.CATWARK	N-CATWALK	N-CATWALK	N-CATWALK	N CATWALK	NO TANK	N-CA WALK	N CALWALL	N CATALAN I	N-CATWALK	N I AWE A			RM BEING					_
MIC												l									i		딛	NIW.	MIC	LIN	ME	M		MIC						No.										M.	N C	5	2	N.	5				ĺ				2 [ŀ									RM BEING SERVERD TYPE			TOTAL AMP CH	0.00	
RKN	RKN	2 RKN	MIC 1 RKN02	RKN	2 RKN	1 RKN	RKN	2 RKN	1 RKN	RKN	2 RKN	7.72	DIV	BKN	DIV	RKN	T RYS	RKN	1 RKN	RKN	2 RKN	: 1 RKN		2 RKN	: 1 RKN	E RKN		ı	1	1	1	П	- [1	1			1		1	П	1	1													TOWNS TO THE	1		1	1	1	1	1	CINE KNING		101			_		MPCH		
02 R			23 23																										г	$\overline{}$	$\overline{}$	7	5 F	_	_	┰	_	_	7	_	_	_	_		_	_		_	_	$\overline{}$	_	_	_	-	_	_	+	-	+		-	-	-	+	2 2	-	7	BACK DD JACK	LOCATIO			128	L	8
10 PAN	9 PAN	8 PAN	7 PAN	6 PAN	5 PAN	4 PAN	3 PAN	2 PAN	1 PA	24 PAN	23 PAN	ZZ PAN	3 2	2 2	2	DA	18 PAN	17 PAN	16 PA	15 PA	14 PAN	13 PAN	12 PA	11 PA	10 PAI	9 PAN	8 PAN	7 PA	6 PAN	J'A	A FA	2	2	3 ·	- 2	2 2	2 2	21 PA	2 2	3 6	TA.	- TA	7 0	0 2	5 1 0 2	D ;	3 N	3 -	1 2	5 0	9	8 ·	7 0	0 0	4 0	, c	2 2	۰ د د	• •	2 2	1	21 PA	20	3	0 0	2	5	2 2	2	2		-	ĺ	_
PANEL 327	IEL 326	IEL 326	IEL 326	ÆL 325	IEL 325	IEL 325	IEL 324	IEL 324	IEL 324	IEL 323	IEL 323	VEL 323	VEL 322	VEL 322	1000	JEI 300	VET 321	VEL 321	VEL 321	VEL 320	VEL 320	VEL 320	VET 318	VEL 319	VET 319	VEL 318	VEL 318	VEL 318	VEL 317	VEL 317	NET 31/	AEL 310	VEI 316	1E 346	1000	10 045	400 345	VEL 314	VEL 374	VEL 314	VEL 313	NEL 313	ALL 212	ACT 012	NEI 313	NEI 312	NEI 312	NEI 311	NEI 311	NEI 311	NEI 310	NEI 310	NET 340	NET 308	NET 309	NET 308	MEI 308	MET 300	NET 308	NEL 307	NEL 307	NEL 306	NEL 306	NEL 300	TANEL 305	NEI 205		SC / SOORCE	DESC/SOURCE	TS.				
																																																											-			l						1770	TYPE					
													L																					I																																	Š		3					
H	1	1			-	1			-		-					+		1	1	1	+		+	+				_				l	-			+				-			-	l	+	+	t	+	i	1	-	+	1					╁	ŀ	-				1		<u> </u>	TAC.	LOCALION IN	Ž C	_	1			
																																																																				DESC / SOURCE	DESC /SOLIBOR					
+	+	+			1						1			_								 	+									-	-								_					-	-																			-		CATION	AMP OUTPUT CHANNEL					
																																							L	_																								L				SIGNATION	AP OUTPUT	5				NODE
+	t	\dagger	ļ		ł			1	1	+	+		H			-	+	-	+	+	ł	İ		1	+	1	+	-	_							L	-		-				L	-			-	l	ŀ	ŀ	+	+						H										S ARE	HANNEL	-				CZI
	l		İ				+	1	1	l						-						l	Ì	Ī	+																									F									-	_								A DESC		-	l			NOB NOX IT AME ROOF
RKNOZ	RKNOZ	RKN02	RKN02	XKN02	KKNOZ	ZVIVOZ	2000	DENIS	DKNO3	DKNOZ	BKN03	RKNOS	RKN02	RKN02	RKN02	RKN02	RKN02	KKNOZ	NAMOZ	NAMOZ NAMOZ	NAMOZ NAMOZ	TANOZ	DV NO.	DE NOS	CONTRACT	DKNOS	PKNOS	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RXN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02	RKN02			RACK			ľ			COM S
	į	د.	۔	-					-	-	-	-	-	-	-	-	E	-	-	-	-	-	1	-	1	-	-		-	-	-	-	-	-	Ξ	=	I	Ξ	×	I	I	Ι	I	I,	I	ī	I	I	Ξ	Ξ	I	-	Ξ	π	ı	I	I	I	6	<u>.</u>	၈	ഒ	6	_ດ	စ			g	/PP LOC,					V 301-433
5 4	8	, ,	6	o	4	٥		, -		2 6	2 1	3	21	20	19	8	17	6	ā	ā		3 2	5 =	:	5 4	٥		7	6	თ	4	3	2	_	24	23	22	21	20	19	18	17	16	5	14	13	13	=======================================	10	9		7	6	5	4	з	2	_	24	23	22	21	20	19	18		ı	1	NEW PP LOCATION				•	•
																																																																				RACK]					
ļ	L	L				-		ļ		ļ	l								-		-		l		Ţ			1			4																			L																		ŏ #	QSC I/C					
									-		-	1				L	_		-	_									-																		L	L		L																	오	NPUT	QSC I/O CONNECTION	L				
-					L						-	-								-	-		L			1							Ŀ	L													L	L	L								L		L			_					오	UTPUT A	NOIT					
					L			Ļ			ļ	1					L										1							L	L												L		L																		오	MP OUT F						
																																																																				ACK	NEW AMP DESIGNATION					
l									ļ			1										T		I		ļ		1																		L																						AMP#	DESIGNA					-
L																_			L	L																										Ĺ																						유	NOIL					

N310-G	N310-F	N310-F	N310-F	N310-F	N310-F	N310-E	N310-F	N310-E	N310-E	N310-E	N310-E	N310-3-4	N310-3-4	1000	1000	10-0-4	1000	N340.34	National A	N310-1-2	N310-1-2	N310-1-2	N310-1-2	N310-1-2	N310-1-2	N310-1-2	10000	Nation	N310-D	N310-D	N310-D	NSTO-D	N310-D	Nation	No.	Nation	N310-C	N310-C	N310-C	N310-C	N310-B	N310-B	N310-8	N310-B	1000	N310-B	N310-8	N310-A	N310-A	N310-A	N310-A	N310-A	N310-A	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECTIO	DIRECT I/O	URECT I/O	200	N CATANAL K	N COTAN K	N-CATWALK	N-CATWALK	N-CATWALK	N-CATWALK	N-CAT WALK	N CATANAL Y	N-CATWALK			RM BEING SERVERD					7	-
MIC 1		LINE	MIC 3	MIC 2	MIC 1			Ž	MIC 3	MIC 2	MIC 1			-	CINE	MICO	MICA	100	1				LNE	MIC3	MIC 2	MIC 1				LINE	MICS	MIC 2	MICT		1	-	LNE	MIC 3	MIC 2	MIC 1			LNE	MICS	1000	MIC 3	2			LINE	MIC3	MIC 2	MICT				ŀ			CINE	MICZ		MIC	L	MIC 2	MIC 1	CNE	WIC V	ui Co	1		HALL ONE			TOTAL AMP CH	001	TAI CLITP	
RKN03	\dagger	RKN03	RKN03	RKN03	RKNOS			1	1	ı	RKN03		L		KKNUS	ı	1					- !	RKN03			l	ı		-	-		l	RKN03			100000	RKNO	RKNO	RKNOS	RKNO	1		l	KKNOS	ı	ı	1	-	١				RKN03			_	-			ZONOZ					RKN02		ļ	ı	1		존				l	l	1	
Е	+	c	c	0	0	+	ľ	7	2	ဂ	၀	-		-	c	c	, (, (,		+		n	0	ი	ი	+	+	1	Α	>	Α	Α	1		,	> :	•	>	>			>	Þ		,		+	1	Þ	>	A	>	+	F	_	_	F		2	7 2	,	0	20	70	R	7	, ,	0	1	쁑	LOCATION		H	821	8	3	
1 PANEL 325	- 1	22 PANEL	- 1	- 1	- 1	+		DANIE									1	MA	-		1		PANE			ı		1	- 1	1		1	19 PANEL	1		1	- 1	- 1	14 PANEL	- 1				9 PANI			- 1	1	F	PAN	- 1		PANEL	L	L	L			L	PAN					14 PAN					-	힋	DESC/	INGINI				-	
L 325		L 322	1 322	L 322	33		1000	340	310	L 319	PANEL 319				1 316	1 316	100	TANEL STO	1				PANEL 312	L 312	1 312	L 312				310	L 310	L 310	L 310			- 500	306	306	306	L 306			L 303	PANEL 303	1 303	203	302			L 398	L 398	EL 398	L 300							-L 329	PANEL 329	1000	300	L 328	L 328	EL 328	EL 327	-L 32/	207			C/SOURCE	S					
	LINE				-	EINE								CINE								Ź						CINE	N						CINE							CNE						Circ	LNE																							TYPE						
+	RKN03		1	1		KONOS	2	Ì	†	-				RKN03					-		1000	RKN	1					COANA	DEN			-	-		KNINGS	2	1	1	1	+		RKN03		-	L			1111111	RKN03	1							L						l				_	-	1	10.0	RAC							
+	o	1	+	1	+	c	,	-		1				o	Н	_			ļ		0	-	1		-	-		0	0	-		_			0	+	+	+	+	+	4	3 8	_			-		+	3 B	+	-							_	_		ŀ	ļ				_				:	8	LOCATION		_				
	70 1	-	1			107	1	-		+	1	-	_	12 TOF							2	1			-			4	┸	-		_			0	1	+	1		-		12 10		_		l	Ŧ		6 []	1	-							L							-	_			<u> </u>	100	.IACK	DESC/	OUTPUT					
	TO ROOM		-			CROOM								TO ROOM							OROGE	202						CKOOM	3						CKOOM							TOROOM						101000	MOOM	-																						C / SOURCE	8					
RKN03					RKN03							RKN03	RKN03				-		RKN03	KNNOS	DVAIO						RKN03							RKN03							PKN03						KKNOS	DE NOS																								LOCATION						
AMP-33					AMP-33						- CA	AMP 33	AMP-32						AMP-32	AMP-32	3		1				AMP-31	-						AMP-31						7.101	AMP-31			_			AMP-31																			-	-					DESIGNATION	AMP OUTPU		_	NO.	100	
2	+	+	+	F	-	T			ŀ	t	1	4	ω	-	-				2	-	+	+	+	+	1	+	4						-	3		ļ		ļ	+	,	3	1	_			H	-		+	+	+	-								_	L	-	+	ļ					ļ	+	9	3	CHANN	1	_	Z	Ś	
F CX204V		-			E CX204V	L				ŀ		A CYCCYO	SX2						2 CX204V			+	-		1	4	D CX204V				1			C CX204V	_					0,400	2				_		A CX204V		+	+	1	+			1	-							<u> </u>		1							AREA DESC	2		j		75 ^^	
MKN03	공 공	P R	공	- R			RK	굕	고주	7.5				낁	굕	R	RK					22			2			곷	7.7.7	2 2	270	R				Z.	22	2				R	RK	RK	RKI					2	2	곳	2 2	곳	곳	굊	곳	짖	곳	곳	굕	Ę	172	70	RK	굊	곳	곶			100		+			NOD NOT IN AME ACC	5	
Н	4	1	L	Ļ	Ш	L		L	L	L	1	1	1	4	4	4				L	L	ļ	1	1	1	4			L	1	1	4	4		L	L	L	L	1	1	1	1		_		L	L	L	1	1	1	1	ຣ໌	Š	ลี	ธิ	ลี	Ŕ	Ŕ	N02	200	NOZ	100	103	3	NO2	202 202	200			- 12	×Ι	NEW P			₹	3	
3	1	t	T	T	Н	H		l	H	t	t	t	t	1	1	1		-		H	t	t	t	t	t	†		H	t	t	†	1	+	_	H	t	t	t	t	†	t	†	1			F	H	t	t	+	†	1	>	+	د ا	1	+				_	H	t	+	†	1	-	-		1		PB GG	OCATIO	1		001-400	ò	
10 R		1	ı	ı	H		H			ı	ı	1		1	ļ	1					1	ı		Į	1	1			ı	1	ı	- [-				ı	L	1	Т	į	1	-	4		ı	ı		П	П	1	-			- 1	-	- [-		17	6	ō	À .	-	13	12	⇉			ı	1	ž					
RKN03	200	NO3	ŶO3	NO3	NO3	NO3	Ŷ03	NO3	NO3	ŶQ3	S	1100	3	SON S	ÑO3	KN03	NO3	ŝ	KN03	KN03	NO3	NO3	S	1100	NOS	SON S	KN03	KN03	KN03	KNOS	100	KN03	ŝ	KN03	KN03	KNO3	KNOS	KNOS	CANO	NO.	200	FOL	NO3	XN03	KN03	KN03	KN03	NO.3	2100	200	Z Z	KN03	Š S	KN03	KN03	XN03	KN03	KN03	KN03												300							
ន	88	8	ន	02	2	8	22	ខ	02	ន	2	3 8	3 6	3	8	3	02	ន	02	02	22	5	2	3 6	3 6	3 :	3	91	9	2	2	3	3	2	01	3	9	9	2 5	2 5	2 5	2 5	2	2	2	2	2	2	2 9	2 5	2 9	3	2	2	9 !	2	2	2	2				ļ		1					ļ	1	IO# INBIT CHTRITA	282					
	ā	3	14	13			ស	=	6	90			-	ľ	*	7	6	տ		_		4		3	. د	1			6	5	;	4	ಷ			13	3	ĕ	\$ 4	•		(00	7	6	5			*	٠,	2 1	٠	_	23	2 !	22	19	æ	7											5	2 5	N T IGN	CONVEC					
	•					ω							•	3	1					_	-			-				4							ω							s					L		1	1																				5		A ITEM T	Į.					
6					5					_	4		,						N	_	L		L				4	_						ω			L			,	,					L	_															_								5	200	200						
																																																																							3	TOACK AWIT	NEW AMP					
														1	1	1									<u> </u>	1	1				1	1									1	1	1																				ľ						t	l	AMP #	AMD#	DECICNA			_		
																																																																	ľ						5	2 2	2				ĺ	ļ

N330-E	N330-3-4	N330-3-4	N330-3-4	N330-3-4	N330-3-4	N330-3-4	N330-1-2	N330-1-2	N330-1-2	N330-1-2	N330-1-2	N330-1-2	N330-1-2	NOZON	NOZO D	10000	Nacho	10200	10200	NO DO	N COLOR	N3DPC	N320-C	N320-C	N320-C	N320-C	0-070M	1000	N300-B	N320-B	N320-B	N320-B	N320-B	N320-A	N320-A	NO2CH	A DOEN	ADCEN	N320-A	N320-A	DIRECT I/O	DIRECT I/O	DIXTO: NO	01101	DIRECTIO	DIRECT I/O	DIRECT I/O	DEEC I/O		N-300	1200 14-200	200	NOC'N	OF ANCE	SPANE	2000	Nator	N310-H	N310-H	N310-H	N310-H	N310-H	N310-G	N310-G	N310-G	1000	NO G	NAME			RM BEING SERVERD TYPE					
MIC 2			-	MIC	MIC 2	MIC 1				LINE	MIC 3	MIC2	MIC 1			LINE	310	MIC N	300			-	Z	MIC 3	MIC 2	MIC 1			1		MIC 3	MIC 2	MIC 1			CINC	PIC C	N Cal	MICS	MIC 1																		-	Z N	MIC 3	MIC2	MIC 1			LINE	MIC	MIC Z	NIC 3			VERD TYPE			TOTAL AMP	TOTAL OUT	TOTAL CLITPLITS
RKN04			1000	ZKNO4	RKN04	RKN04				RKN04	RKN04	RKN04	RKNOA		l	KNNOA	DE NOV	NAMO.	NAMO.	200		10101	RKNO	RKN04	RKN04	RKN04	l	İ	1 11 11 11	RKNOA	RKN04	RKN04	RKN04			XXXV4	#OK120	PONAG.	DKN04	RKN04		-		l									+	-					RKNO3	RKN03	RKND3	RKN03		_	RKN03	KANUS	ZNNGS	DKN02	10101	RACK	5		_	L	1	8
0 C	L		(3 6	ဂ	c			4	ဂ	ი ა	c	ი	+	Ŧ	>	• •	2 2	. >	1	l	,	D	>	A 14	A			1	>	A 9	>				4	• •	> >	٥ د	-	,	_							F		ļ.	<u> </u>	+	ļ	t	ļ	+	,	7	-	m	\neg	_		т	ı	1 1	n	1	PP JACK	LOCATION		_	_	1	+
PANEL 354			- 1	PANEL 351					- 1		PANEL 347		ı			PANEL 345	PANEL 343	PANEL 343	PANEL 345						PANEL 341						- 1		PANEL 338			1	1	BANIEL 335	- 1	PANEL 335																		- 1	DANE 307	- 1	- 1	PANEL 327			ı		PANEL 325			×	DESC / SOURCE	INPUTS				
		Cive	i Nic						LINE						LINE						LINE							CINE							ENE																						CINC							LINE							JAKI					
H		NOWO4	01470	l					RKN04						RKN04	-				-	XXNC4	1					-	KKNOA	2	+	1				RKN04			ł	1										L	_	-						KNNGG			1	+			RKN03				ļ	3	RACK	2					
+		0	+	F		-		-	o 6	1	7			L	B 24	F	ļ	F		L	18	,	1		1			8 12	,	Ì	1				8	F	l	1		1		_	_	L	†	1			F		F	ŀ	İ		ŀ	F	7 12	1		1	1	1		F 6		-	F	ļ	17	B	LOCATION					
		OROOM	┸					1	TOROOM						TOROOM	H					TOROOM	+						TOROOM	+						TO ROOM	H							-														2 TO KOOM	1					┚	TO ROOM					5		DESC/SOURCE	UTPUTS				
	RKN04	RKNO				101101	RKNO	RKNOA						RKN04						RKN04							RKN04							RKN04														,		RKN03	RKN03	RKN03	RKN03	RKN03	RKN03	RKN03							PKN03							-00,0	LOCATION					
	AMP-42	CA-GINA				746	AMP-42	AMPAZ	İ					AMP-41						AMP-41					+		AMP-41							AMP-41																AMP-34	AMP-34	AMP-34	AMP-34			AMP-33			†	1			AMP 33							0.000	DESIGNATION	AMP OUTPU			140	201
\parallel	\dagger	۵	H			+	٥-	-	1	1	+	1	7	4						3	-		+	ł	+	1	N		Ė	ļ	+	1		-	-			L			1			_	+	+	1			4 S	⊢	⊢	┾-	-	_	4	-	ļ				+	ω	1		_		F	ŀ	9	CH AREA	CHANN			1	250
	4 CX204V						A POCKO	2				1	- 1	CX204V			_			C CX204V					1	4	B CX204V			l	1	1	_	A CX204V					ľ	+	1				l					P30 CX20	P20 CX20	P20 (CX20	SP20 CX204V			H CX204V	ı					0.000	1		-						REA DESC	2	-		NOD NOT THE TOOM OF HOS	71. 00.00
- 1 - 1	- 1	RKN04	RKNO	RKNO	RKNO		1		NXN	DE LA COMPANIA DE LA	D	DKN	- 1	- 1	RKNC	RKNC	RKNO	RKNO				RKNO	XXXX	Z	DENT	- 1		RKNO	KKNC	72/40	200	DKN	- 1	1	RKN	RKNO	RKN	ZKN	ZNIN	2000	DV.VI	RXN	RKN	RKN	ZZN	TO THE	BKN	RKN										ZXX	77.72	ZXX	7578			RKN	RXN	RKN	RKN			3	١				200	200
0 0	1		Ц		1	ļ	1		L	1	1	1	1	4								_			1	1				ľ	-		1	_			L	Ĺ	-	_	1				L	1					_	_	01		Ĺ	_	_		L	Ĺ		1				_	_	L				NEW PP	-		VI 001-	3
13	+	\dagger	Н	7	\dagger	t	Ť	t	t	t	+	t	t	+	+				_					ł	t	+	-		H	t	\dagger	†	+	1	1		-	H	t			+			l	l		1		1	-		15			H	-	t	, n	t	t		t	5	1	3				5	PD GOOD	OCATION			too	3
RKN04	1			- 1		1		ı	ı	ł	ı	ı	1	-	1	-					1		ı	L	1	1				ı	ı	П	1	1	-[L	П	1	-	- 1		ı	ı	П	1	-	-					Ш			ı		ı	П	1	1	-1						1	X BACK			_		
ខន	3 8	22	22	2	3 8	3 8	3 8	82	22	5 5	3 8	3 8	3 5	01	2	01	9	2	2	2	01	3	93	9	2 5	2	2	9	9	9	2 5	2 :	2 :	2	2	91	01	2	5	2 6	3 8	33	03	<u>.</u>	03	3 8	2 0	03	3	ස	8	ខ	03	03	03	ន	03	03	03	03	ç	2 6	3 8	3	03	03	03		-	2	5 6	285				
3 9			œ	4	ں م	,			4		٠,	٠,	1			6	5	14	ವ			12	=	ā	3	,			00	_	1 0		^			4	3	2	-		;	1	5	9														œ	7	o:	U	,			4	3	2		오	2 2	NO CONTRA	CONN				
	ļ	2						-		İ					•						з							2							_										4		3	9	_								o						,	אנ					오	2						
	×ω					2							4	4						3						,	s						-	•																4	3	N	1	6	5	8						Ī	1						요	AMP COL	200					
																																																																						2405	MOCIFO CONNECTION NEW CHIEF PACK	NEW AMD D				
\prod	-			-	-			L		-	-		-			-			\downarrow				L			-							1					L		-	-	-	1				1		-										Ĺ					\int					_	AMP #	DEGIGNATION	TAICUST		1		r-
	1																	1		1						l				ĺ																	ĺ												Ì											3	2 2	2	1			ı

N210-D N210-E MIC 1 RKN05 C 1 PANEL 113 N210-E MIC 2 RKN05 C 2 PANEL 113 N210-E MIC 3 RKN05 C 3 PANEL 113 N210-E UNE RKN05 C 4 PANEL 113 N210-E	A A A A A A A A A A A A A A A A A A A	M210-A MIC 1 REVIUS A 2 PANEL 101 M210-A MIC 2 REVIUS A 3 PANEL 101 M210-A MIC 3 REVIUS A 4 PANEL 101 M210-A MIC 3 REVIUS A 4 PANEL 101 M210-A MIC 1 REVIUS A 7 PANEL 104 M210-B MIC 2 REVIUS A 7 PANEL 104 M210-B MIC 3 REVIUS A 8 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B MIC 3 REVIUS A 9 PANEL 104 M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B M210-B	T RAN. T	TOTAL OUTPUTS
LINE RIANDS D 8 74	RKN05 B 12	70 (20 (20 (20 (20 (20 (20 (20 (20 (20 (2	UNIE ROOO F 12 17	LINE RIGIDA D 18 TO ROLLINE RIGIDA F 6 TO RO
TO ROOM RKN05 A	RKANDS	RKN05	TO ROOM REVIOUS REVIOUS REVIOUS REVIOUS REVIOUS REVIOUS REVIOUS REVIOUS REVIOUS REVIOUS	SOURCE
AMP-51 4 D CX204V RI	AMP-51 2 B CX204V R R R R R AMP-51 3 C CX204V R R R R R R R R R R R R R R R R R R R	AMP-51 1 A CX204V R R R R R R R R R R R R R R R R R R R	AMP-44 1 CX204V R AMP-44 1 CX204V R AMP-44 2 CX204V R AMP-44 3 CX204V R AMP-44 3 CX204V R R R R R R R R	NSB NORTH AMP ROON AMP OUTPUT CHANNEL COCATION DESIGNATION ON AREA DESC RACH RANGE RANGE
D C C C C G B	B 12 A 1 13 A 1 14 A 1 16 B 16 B 16 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 22 A 23 A 34 A 44 A 54	A A A A A A A A A A A A A A A A A A A	F F F E E E E E E E E E E E E E E E E E	NEW PP LOCATION RACK PP LACK RACK
		03 12 03 12 03 12 03 13		0.00 JO COUNTECTION 10.0 # INPUT OUTPUT AMP OUT CH CH CH 0.2 11 0.2 11 0.2 12 0.2 13 0.2 14 0.2 15 0.2 16 0.3 4 0.3 7 0.3 5 0.3 7
				TAMP OUT PACK CH CH AMP # CH 5

Nasorc	N330-C	N330-B	N000-0	O OSEN	N330-B	N330-B	N330-B	N330-B	N330-A	M-DOCK	NOODA	1230 4	N330-A	N330-A	N330-A	Olivino.	DIRECTIVO	DIRECT I/O	DIRECT I/O		DIRECTIO	DIRECT I/O	DIRECT I/O	07.00	0	DIBECT IO	N220-G	NZZ0-G	14220-G	200	N220-G	N220-G	NZZOG	SOCO	N220-F	N220-F	NAZOFF	1000	N220-F	N220-F	NZ20-F	1000	OCCI.	N220-E	N220-E	NZZO-E	1020E	- OCCN	N220-E	N220-D		N220-D	N220-D	N220-D	0.000	N220-D	N220-D	NZZO-C	N220-C	NO CO	COCCIN	N220-C	NZZOC	10-022	1000	N220-B	N220-B	N220-B	1000	N20CN	N220-B	N220-B	N-UZVA	1000	A-OCCIN	N220-A	N220-A	N220-A	NZZU-A	NZ IOE	230			RM BEING SERVERD					7	
MIC 2	MIC 1			-	N	MIC 3	MIC 2	MIC 1	-	-	LINE		MICS	MIC 2	MIC 1			_											UNIT	1	MIC 3	MIC 2	MIC 1	1			CINE		MICS	MIC 2	MIC 1				LINE	MIC 3	MICZ	1	MIC 1				LNE	MIC 3	1000	NIC S	MIC 1			0,46	INC.	MIC 3	MIC 2	MIC -				LNI		NIC 3	MIC 2	MIC 1				LINE	MIC 3	MIC 2	MIC					ERD TYPE	 -	1	0.000	OTAL AME	TOTAL OUTPUTS	TOTAL INP
- 1	RKN06	1		П	1			RKN06		-	1	1	1		RKN06	1	1	-	L		1		_	-		1	-		ı	1	ŀ	RKN05		ı			ı	ı	1	RKN05		ı	1	-	RKN05		ı	ł				Ì			ı	SOLVE	ı			l	DEVIOR			l	ı		-		ļ			RKN05			1	1	RKNOS		l	1	1		RAC	Ļ.		L	ı	1	-	
_	Α	⊢		+	55 F	-	-	-	_		>	+	+	۶ ک	-		1	-	_	L					ŀ	1			┿	+	-+	m K	⊢	+			⊢	+	+	6 m	-	┿		-	E .	Н	+	+	┪		ļ	-1	-	⊢	+	7	\dashv		L	+	2	-	-	⊢	+		-	⊢	+	+	-	<u>ი</u>	۱-	l	+	+	ი ი	-	Н	٠			PP	LOCATION			į	ş i	3	2 55
- 1	13 PA	ı			5	- 1	- 1				4	1	- 1	2 00		-		-		L		_			-			_	5		- 1	20 F/			-					14 P/			-		10 P						-	- 1			ļ	0 :					3 !			1					1	- 1	- 1	19 P			-	- 1	5			1		-	JACK	D	- N	L	1	1		
NEL 378	PANEL 378			NEL 3/2	NEI 376	NEI 375	NEL 375	PANEL 375			WEL 372	WEL 3/2	NICI 979	NEL 372	PANEL 372														NEL 134	2400	NE: 134	PANEL 134	NEL 134				NEL 131	2400	NEI 131	PANEL 131	NEL 131				PANEL 128	NEL 128	NEL 128	WALL 150	NEI 128				NEL 125	NEL 125	PUEL 123	DANEI 135	NEL 125			PANEL 122	NEI do	ANE: 122	NEL 122	WEL 122				NEL 119	- 1.0	AND 440	ANEL 119	PANEL 119			1100	AND 116	PANEL 116	ANEL 116	ANEL 116					ESC / SOURCE	NPUTS					
			LINE							E						_							-						_							LINE							Civin	200						_	CINE	Z					İ		LINE								Z					,		LINE									_	TYPE						_
Н			RKN06			1	-			RKN06					-			1										RKN05			1					RKN05	_	l					SONOS	0	1			-	1		KNNOS	0						_	RKN05								RKNOS			1	-	-		KKNOS	!				_	ŀ	ļ	+	- 1			L				
	_	-	В	⊢	-		1	1	-	8	۴.		-	l						_	-	+		_			4	6			1		-	L	-	G G							G	-			L	-	1	_	G	_	_		L		1	_	05	_			_	L	L			_		1				C	+		1		_	L			공	LOCATION			-			
\parallel	1	- 1	12 TO		ŀ	-	1	1	4	6 (10				+	-			1	-	_		+		_		-	1	24 TC						-	1	18 10		L	1			L	1	1			L	ļ	-		0	1	-	_	L	+	+	_	24 17	Ļ	-	1			L	1								12 10	Ļ	+	-			-	ļ		위		Ę	L	L			
			TOROOM							TOROOM																	No.	TO ROOM								ROOM							CROOM	BOOK							CROOM	BOOM							TO ROOM								TO BOOM							CROOM										SC / SOURCE	S					
	777400	RKNOS	+	-				Tana Para	BUNDS			_													_	KKNOO								XXXVC								RKN05				_	-			RKN05					_		10000	RKN05						i	CONNO	DIVANCE				+	1		RKN05							RKN05				LOCATION						
	WILL-OH	AMD SA	1					VINIT-04	200																_	AMP-53								AMP-53								AMP-53								AMP-53							2001	AMP-52							AMP-52	25							AMP-52							AMP-52					AMP OUTPUT CHANNEL			1400	ZOD	
H	^	+		1		F	F	-	t	1			L		1			t	+	7	_		+		_	4		1			ŀ	-		3	+	1			ļ	1		N	L	†	+	-		F	1	-		1	1		F			4		F					4	,	1	_			+		N		ŀ	ļ	+	+	_	1		#		오	CHANN	-	-		25	
	2	L	1	1		L	-	2	1	1					+	-		-	1				1			G CX	ı		-			1		CX					Ļ	1	4	m Q		l					ı	S S		-	+			ŀ	1	2							CX	1	+				1	1	A			-	+	+		E CX		+		REA DESC	72	L			7.0	
20 2	CXZU4V K		2 2	20	20:	20	2	VACU4V	П	9 :	20	20	20	2	0 2	20	20	12		ō	70	2	2 2	0		CX204V R		0 :	Z)	20	ä	oi:	- 1	CX204V R	П	0 :	Z)	70	12	0 :	- 1	CX204V R		12	2	2	R	20		CXXXXV					Z		- 1	CXONAV	70	20	Z)	0	ã	CX204V IR			20	70	1	012		CX204V R	20	7			0 :		CX204V F	ı					L		1	NOR CORTH AMP ROO	l
RKN06	SOS	NO.		S	90N	SON S	Ŷ06	COO	8	100	Ŝ	NO6	<u>206</u>	NO	100	NOS	Ŷ05	S		SOS.	Ŷ05	COND	200	NO.	NO5	205	CONT	100	NOS	S 05	VNOS	NO.	NO5	NO5	VIVOS	NO.	NO5	KN05	VIACO	NOE C	SON	X V O S	KN05	S	100	NO5	KN05	KN05	1	SOS	KN05	S		KN05	KN05	SNO	7.00	X NO.	KN05	KN05	KNOS	200	200	KN05	KNOO	2140	2010	KN05	KN05	ZNOO	NO.	NO.	SONY.	KN05	KNOS	VIACO	200	NO.	KN05	KN05				RACK	NEV					
>>	2	2 a	,	Þ :	Α	>	>	2	o	,	>	۸	>	>	> =	r	I	1	-	Ξ	o	G	0	0	G	2	-	,	n	m	ŗ	1	7	21	,	1	_	m	'n	,	n	2	F	,	,,	-	3	m	1 5	3	ח ח	, ,,	,	n	m	r	1	2	0	c	c		2	c	01	2	,	n	ი	r	,	2	9	0	c	,	,	2	0	91		1		ğ	NEW PP LOCATION			2	M 201_/22	
4	4		٦	3	۵	œ	7	3	0	,	٠,	۵	N	-		2	23	2	3 2	3	24	23		3	21	ź	24	2	3	2	è	3	i	1	ē		16	15	4		4	õ	12	5	,	٥		7		٥	o		١,	ا،	N	_		0	2	22	27	2	3	19	7	ō		3	21	2	3	١	n	12	ā	2	1		3	5				ACK	TION					
RKN06	RKN06	KKN06	KKNOO	DENIOR	RKN06	RKN06	RKN06	RKN06	Z NOO	2000	SON	RKNOS	RKN06	KKN06	2000	000	RKN05	XXNOS	NAME OF THE PERSON	DKNOS	RKN05	Z X NOS	1	DVNOS	RKN05	RKN05	KKNOS	1	DKNOS	RKN05	KKNOS	1	BKNDS	RKN05	KANUS	DVAID C	RKNOS	RKN05	ZZZZZ	2	SKNOS	RKN05	RKN05	ZKNOS	170	DKN05	RKN05	RKN05	T T T T T	DKNO5	RKN05	XKNOS	NAME OF THE PERSON	DKNOS	RXN05	RKN05	ZVIVO	DKNOS	RKN05	RKN05	XXN05	1	DK NOS	RKN05	RKN05	ZNINO		RKN05	RKN05	KKNUS		2017	RKN05	RKN05	XXNO5	77.400	77.400	DK NOS	RKN05	RKN05				R C C	1					
2 5	2	9	9	2 9	2	10	01	2	9	2	2 9	2	01	2	2 5	3 :	03	8	8 8	23	ឧ	ç	5	3	3	ឩ	03	2 2	2	ខ	03	3 2	3	03	93	3 8	2	03	0.3	3 8	03	င္သ	03	s	3	23	8	03	5	2	03	93	3 8	2	ဒ	03	8 8	3 8	ន	02	02	200	3	8	 ន	20		3	22	20	32	3 6	3	2	02	20	3 8	3 6	8	ន	L	l		1/O#	<u>8</u>	_				
5 "	Т		a	T	7			ı		T	Ť	1		Г	2	1		T	t	1		ľ		İ				t	1		T		1	_	-	Ť	1		r	,	1			t		1	7		t	1	_	t		†		r		1	7	5	Г	t	1				t	1		H	,	t			8	t	1 0	t	1			5	2 .	NP.	000		l			
T		2			1		_		-	İ						1	_		l		œ	7	0		'n		4	+	1			l			ű	,				t	+		N		l				ļ	1	_		l			-	ŀ	1	4			ł				,	+			ŀ		l		2	_	l		1				2	2	2	NECTION					
+	2			l	1		_	1			+							_								4	L		-			1		3			1	_		Ī		2			l				-			ŀ				_	4			_				-	_ u	-							3		_	-				_	_	5	2	AMP	I/O CONNECTION					
+	-	-	-	-	1	1		L	L		+			_	l	-		-	-	+	-		-				L		1	-		-				1	1		L		+					1				1		L	1				-	1	+	_	_		1	-		ļ		+		L		1	1			ŀ		1						RAC	<u>z</u> .	-	_			
																																																																	_				_															`	NEW AMP DESIGNATION					
					\int						ļ	ſ		_	Ĺ	-	Ţ		Ĺ	ļ		_		-	1	1						ſ	Į	_		ſ	1			ſ	I					T				1			I	1	_			1	1				1				I	1	_	_		1											7000	AMP#	ESIGNAT				_	
Ц,																																L											_						L			L				L	L								_																		2	2	ğ					

N321 N321 N321	N230-B	N230-B	N230-B	N230-B	N230-A	N230-A	N230-A	N230-A	N230-A		DIRECT I/O	DIRECT I/O		DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	N-300	N-300	N-300	N-200	N-200	N-200	N-200	N-200	N3Z9	PICON	N220	Nacen	NOOP	N329	NACEN	N319	N319	N319	N319	N319	N319	N312	N312	NJIZ	NJIZ	21017	ZICH	1010	N244	N344	Nati	N311	Nati	Nove	Nagor	Nagon	N330-D	N330-D	N330-D	N330-D	N330-C	N330-C	N330-C	N330-C	1000		AM DEING SERVERO	DIA DEINIO CEDIA			1	TO	
MIC 1		LINE	MIC 3	2 MC			ENE	MIC3	MIC 2	MIC 1		1	1		1	1													CINE	INFO C	N CA	MIC -	MIC 1				MIC 3	MIC 2	MIC 1			LINE	MICS	MICA	MIC	5		LINE	I INC O	MIC 2	MIC			Cite	I I	MIC 3	MIC 2	MIC 1			E N	MIC 3		1	יייי				OTAL AMP	TOTAL OUTPUTS	
RKN07	T	RKN07	RKN07	RKN07			RKN07	RKN07	RKN07	RKN07	1	1	1			Ì				ĺ			_						ZVIVO	DKNO6	DKN S	BKN08	SUNNE	1		RKN06	RKN06	RKN06	RKN06			RKN06	KKN06	KKNOO	NXNO.	1		ZZZZZZ	25,1400	DKNO8	NAN S	2000	T	100	DKN06	RKNOS	RKN06	RKN06			RKN06	RKN06		Ş	2 2	5	ŀ	ı	-	88	I
A A A	-	††	A 2	+	Ι.	Н	7	7	2	7	1	1	1		1	1	1	1	7									l	Ť	+	+	2 0	+	1	7	ဂ (၈	7	7				T	T	0	2	,	1	+	7	7	3 -	,	Ŧ	,	+	Þ	>	>			Α	A 15		J.A.	LOCATION	24	F	-	٦	-	
PANEL 365 PANEL 365		PANEL 140	- 1				PANEL 137	PANEL 137	PANEL 137	PANEL 137								,														PANEL 360				PANEL 334									PANEL 332	2			1	F	PANEL 330	1			OBE SINGS							5 PANEL 378		×	DESC / SOURCE	NPOTS				_	
																															-																	-					-													•				i	
	LINE																											LINE		I					İ						LINE						CIVIC						LINE							CINE					TYPE						
	RKN07 B		-		-4	RKN07 B					-	1	+	1				-										RKN06	+		1	-		CONNY	+	-				-	RKN06 D			ĺ	L		KNNS	+-		ļ			RKN06	-					-	RKN06 B				RACK	JΧ						
	12				H	6					ľ			1	l	ł												24						-	+					-	12						0	t	l	t	l		8 24	t			+		1	B 18		_	-	PP JACK	NON	9	-		1		
	TO ROOM				***************************************	TOROOM																						TOROOM						CACCE	TO BOOM						TO ROOM						CROOM						TO ROOM							TOROOM					DESC / SOURCE						
XXN00					RKN06													AVIANO	KNINGO	DOMAN	SCHOOL	SCANGO	DKNOS	DKN06	RKN06	RKN06	RKN06						KKNUG							RKNOS						RKN06						RKN05							RKN05						LOCATION						
AMP-64					AMP-64													AMP-63	AMP-03	AMP CO	AMD 63	AND SA	Cadina	AMPLES	AMP-62	AMP-62	AMP-61						AMP-61							AMP-61						AMP-61						AMP-54						7	AMP-SA						DESIGNATION	AMP OUTPUT CHANNEL				NSB	
2	Н	1			- i	Ŧ	Ť		1	+	1	ļ	Ī	H					2			2 4				- - Z	4			F			ú		+	†	†	1	ľ	5						-			F	F		4	H	F	ļ	l	+	+	3	1	-				유 유	CHANNE	L	_		NOR.	֡
CX204V	Ц				CX204V			+	+		-		ŀ					31 CX204	12 CX20	0.00	AMONO CCON	200	200	ייייייייייייייייייייייייייייייייייייייי	0 CX20	10 CX20	CX20					-	CX204V	L		ł			0,000	CX204V			_	Ļ.	_	CX204V				H		CX204V				-	+	1	CXOLAN						EA DESC					ΙAMF	
RKN07	1	RKNO	RKNO	- 6		DKN0	KKNC	KNO	Z K	Z KNO	RKN	RKNO	RKNO	KKNC	RKNO	RKNO	XXXX	RKN	XXX	ZZZ	200	DVN.	0	NYG V	RKN	RKN	RKN	RKNO	RKN	RKNO	RKN	RX	1		NAME OF THE PERSON OF THE PERS	DIAM.	DKN	RKN	- 1	- [RKN	RKN	RKN	RKN	RKN06	1		RKN	RKN	RKN				RKN	RKN	ZXX	277			RKN	RKN	RKN			RACH		_	_		NSB NORTH AMP ROOM	
						1			ļ		ľ	ŀ	L	Ļ	L	L	L	Ļ	L	-	1	1	1	1	1	-	-			L	L	L	_	Ļ	l	ļ	1	1	1	1	_		_	L		L	L	L	L	L	L				L	ļ	1	1				_							13	M 301-433	
A A A	\dagger	t	Н	1	†	t	t	t	t	t	t	t		t	l	l	r	╁	l	t	t	t	Ť	t	†	1			ŀ	ŀ	-	H	t	ŀ	t	t	t	t	t	†	1		1		H	H	H	t	t	t			-	ŀ	t	l	ł	t	†	1				_	Ď,	NEW PP LOCATION			1	333	
14 RKN07 13 RKN07 14 RKN07		1		-	Т	i.		L	П		1		1			l	ı		ı			ı	ı	1			-1					ı		ı	ı	1	1	1	1	1	-	- {			li						Ш			1	ı	ı	П	П	ı		١			li	CK RACK	ı					
	4	\perp	Ц	1	1	ļ	L	L	L	L	L	L	L	L	L	_	L	L		L	ļ.	1	L	1	1	1			L		L	L	L	L	L		1		1	1					Ш	_	L	L	L	L						L				1		╛									
222	Ť	T	П	1	3 5	T	T	T	T	T	T	1	-	T	ន	ន	02	2	3	5	2	2 2	2 2	2 5	3 5	2	ន	٦	П	r	r	r	T	8	T	t	†	Ť	1	3 1	1	1	1	Н	Н	22	ន	2	ន	ន	92	2	01	3	3	9	2 2	2 5	2 !	†	7	†	-	_	I/O# IN	QSC I/O					
6 9	+	8 7	6	5	+	4	3	2	-	8	19	18	17	-	_					-	-	-	-		-	1		-	16	15	4	3			7.1	5 =	1 2	5 0	1	+		8	7	6	5			^	3	2	_			16	5	4	: 6	3	1		2	=	-	오	IPUT OL	C I/O CONNECTION			-		
	2			+	-					-				00	7	6	5				-	1			+			4			L			ω		-	-			•	9			1			_						4		L		-	-	•	2	+	-	-	오	ITPUT AM	NOI					
2	-		$\ $	-	+		L	_										ź	=	10	۳	0	-	1 0	0	ת	4						ω						^	اد	1		-			-					Н	4			L		1	6	٥					오	POUTRA			-			
																																																																ļ	S	NEW AMP					
					1	L								-	-							İ	l		1	1										İ	1		1										L					-		l			1	1		+			AMP#	DESIGNATION					
					1													۱				ĺ		ľ	ſ	ſ	ĺ												Ī	Ī		Ī	Ī														ſ	Ī	Ī	Ī	Ī	Ī	1	1	윤	NOIT		Γ	Γ	T	

PAGING	PAGING	PAGING	PAGING	PAGING	DACINO	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PACINO	PAGING	PAGING	PAGING	DAGING OF	PAGING	PAGING	PAGING	PAGING	FAGING		PACING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGING	PAGINO	N-300	N-300	N-300	N-300	N-300	N-300	N-000	N-300	N-300	N-201	N-201	N-201	N-201	N-200	1000	N-200	N-200	N-200	N-200	N-200	N-200	N-200	N-100	N-100	8 8	4 60	14100	N	N-100	N-100	N-100	N322	N322	N322	NSZZ	ZZCNI	Nego	N333	N321	N321	N321			RM BEING SERVERD				<u></u>	
MIC2	MIC	MIC 2	MIC 1	MIC 2			MICS	MIC 1	MIC 2	MIC 1	MIC		AIC 1	MIC 2	MIC 1	SI C	THE STATE OF	MIC	MIC 2	MIC 1	MIC 4	100	100	MIC O	MIC	MIC2	MIC 1	MIC 2	MIC	NIC.	3	2								+				-								_								1						LINE	MIC3	MIC	100				LNE			YERD TYPE			TOTAL AMI	TOTAL OUTPUTS	TOTAL INF
RKN07	- 1	ı	l	ì	П	П	-1			ı	ı	П	- 1		ı	i	П	ı				1	1	П	- 1	- (ı	П	П	+	1	_	L	L			+	+	1			L		+	+		4	-				L	-	1	+	+	1	+	+	1	+			RKN07		1	L	+		RKN07		- 1	- 1		-	PCH	STO	STO
Ю Н	ମ ଜ	Ю7 Н	107 G	97 H	. 6	7	7	07 ଜ	9 H	107 G	H /0/		0 :	107 H	107 G	2	3 3	9 G	107 H	107 G	2	. 6	3 5	107 E	ñ	Į.	67 G	? ∓	107 G	2	3 5	3	1	-	-			ŀ	ŀ	1	+	+	-				+	+	1	+	+				L	ŀ		-		+	+	1	+	+	-	⊢	9 A	╄	┿	+	+	+	407 A	-	RACK PP JACK	LOCAT	ŀ	-	128	8	455
28	2	5	19	ä	5		1	7	6	16	5		;	1.4	1	č	3 6	13	12	12	=	=	:	3 2	ŝ,	۰	9	œ		-	1	,									İ						I									1	İ	İ		İ	Ī					ĸ	2	20	3 6	à		1	5		JACK	<u>Q</u>	_		_		
PANEL 113	PANEL 113	PANEL 112	PANEL 112	PANEL 111	DANCE ATT	CARCE SIG	DANIEL 110	PANEL 110	PANEL 109	PANEL 109	PANEL 108	200 IOO	DANIEL 409	PANEL 107	PANEL 107	PANEL 106	SHIEL 100	PANEL 106	PANEL 105	PANEL 105	PANEL 104	PANEL 104	LAMEL 103	DANEL 103	PANEL 103	PANEL 102	PANEL 102	PANEL 101	PANEL 101	PANEL 100	PANEL 100	BANEL 100																																		PANEL 367	PANEL 367	PANEL 36/	PANEL 307	DANIE) 367			PANEL 365			DESC / SOURCE	IPUTS				
								1				l						1			L			ŀ	+								1															1		1							-								LINE	_		L	-		Live	Ž				77				L	_
\parallel	1					-											-	-	_				-		1	1				L	-	-		1					L			-				L	L	-	-	1					_				L							_	L	L		-	١		-			3971		4	_		
\parallel	1	-	-	4		ļ							1	1			L							-						L		-		1				_	L		1	1						1	1	4								Ļ	L	1	1				RKN07				ļ	1	1000		1		RACK PP JACK	200					
\parallel	t	†	+	1	ŀ			1			_		ł		1		l	1	1			-	ŀ	l			†	-	-	l		İ	t			_					t	\dagger	1			_		t	+	+	+	-	-				ŀ	-		ŀ		1	+	+	B 12			L		ł	,	╁	1	9,0	IAC	2	2	1	1		
H	1	T	1		-	T	l		1			-	l	Ì			r	†	1				t	t	t	t	1		_			İ							l	ļ	l	t	1			-	l	t	1	†	1						t	l		t	t	t	t	_	TO ROOM	Ī	l			t.	1000	3	+	1	~	DESC	T I	1	1		
									- Contraction -																																																								ŎM						Ca				000000	SOURCE					
			Ì																													KKNOZ	Z Z Z	00000	RKN07	RKN07	RKN06	RKN06	RKN06	ZXNOS	ZZNO/	NICK NO.	BKN07	RKN07	RKN07	RKN07	RKNO/	SOLAO!	2000	DKN07	RKNOS	RXNO6	RKN06	RKN06	RKN07	RKN07	RKN07	RKN07	RKN07	ZXNO/	ZNNO/	NAMO?	DVN07	BKN						KKINUS	1	İ			1000	CATIO					
																_														_		AMP-/1	AMP-/	200	AMP-71	AMP-71	AMP-66	AMP-66	AMP-66	AMT-66	C/-dwy	AMP 75	AMD 75	AMP-75	AMP-75	AMP-76	AMP-76	AMP-/O	200	Se ciny	AMPLES	AMPLSS	AMP-65	AMP-65	AMP-74	AMP-74	AMP-74	AMP-74	AMP-73	AMP-/3	AMP-/3	AMP-/3	AMD 70	ANDSA						AMP-04					0.000	OCATION IDESIGNATION	AMB CITE			N.C.	
H	t	l	t	+			L	İ	ļ			_	-	ļ	1		L	l	ļ				L	L	-	-	†					4											2) 1	2	-	4	ω	,							4	3	2		4		, ,	, -	. 4							ú	1		1	+	9		CLAN			Š	,
			ļ	1		_	_						L	ļ	1					1					L	L						SP 30 C	OF 30	2 2	200	SPS	NP 20	NP10 C	NP10	NF10						_				Š	3	2	CON	CON		_																			Š	CH ABEA	Ē			A HILL	
				İ																												X204V	X204V	×		X204V	X204	X204V	X204V	X204V	X204V	V#04V	YANCY'	X204V	X204V	:X204V	X204V	X204V	V+0	2044	VACCA	VANCX	X204V	X204V	CX204V	CX204V	CX204V	CX204V	CX204V	X204V	X204V	VA204V		VVOCY						CX204V					000	25				ST T	
RKN07	RKN07	RKN07	KKNO	DKN07	RKN07	RKN07	RKN07	KKNO/	NO.	DVN107	RKN07	RKN07	RKN07	NOWO?	BKN07	RKN07	RKN07	ZNIVO/	DE NOT	DKN07	RKN07	RKN07	RKN07	RKN07	KKN0/	KKNO/	20007	BKN07	RKN07	RKN07	RKN07	RKN07	ZKNO.	NOV.	DKN07	RKN07	RKN06	RKN06	RKN06	RKN06	KKNO/	NAMO!	DKN07	RKN07	RKN07	RKN07	RKN07	KKN0/	ZVINO/	70100	SOLVE	RKNOS	RKN06	RKN06	RKN07	RKN07	RKN07	RKN07	RKN07	RKN07	KKNO/	יסאמא	77.400	DENIOR	RKN07	RKN07	RKN07	RKN07	RKN07	KKN06	XXXVO/	NOV.	DV107		25.00		200			NSB NORTH AMP ROOM 301433	
DΩ	0	0		,	2	0	0	-		,	5	0	0	,	,	0	റ	c	,	,	0	ဂ	0	ဂ	6	c	, 0	,	0	0	င	2	9	2	2 9	2	2	9	9	2	9	2 5	2 2	2	의	2	2	2	2	2 9	2 2	3 !	2	2	2	91	91	2	2	2	2	2	2	2 0	D :	>	A	>	A	91	α	,,,	-	t	1	NEW PT LOCATION	8	+	1	24.	
14 14	13	13	12	3 -	3	=	1	10	ē	,		9	8	0	. 0	7	7	a		,	55	5	4	_	3		3	ر د	s	_	_	20	į			1	2	5	18	17	1				13	7,5	=	١		,			1	13	8	7	6	٠,	4	ω	2				2	3	21	2	-	_	ã	1			2	NO.	3	1		చ	
							_				1		_							1					-								ļ	l	ı	ı		- 1			ı		1	1				ı	۱	l				1	RKN07	-					1			t								ł			NAC.	1		1			
+			ŀ	-	1	1				t	1			-	+	+		L	1			-		H		-	+	+	+			83	92		3 6	3 1	3	8	ន	8	8	5	3 5	3 2	8	ន	8	2		2 5	2 5	3 5	R	8	9	9	_ 9	9	9	9	0	c		,	,	٥		9	o,	0	9		_	+	Į	100	2	1	1		
+				l					l	l	t				1		_	ŀ	t	Ì					-	l	l	1	1	1	_	-	-		T					-		T		1		-	_					1	Ť			_	Ε		F	Γ	Γ		ľ	T	t	+	15		l	H		12		ç	#	100		+			
+	L				+	-	_	_		l	1			L	+	+				+	1	-				L	+	+	+	-	_			-	-	+	1						1	1				L	ŀ	ļ.	+	+	+	+		-	_				-	-	<u> </u>	+	+		_	_					-	-	5	NEC		1	_		
					1				L						-	1		L			1										-	22	12	1		ا.		1	1.	-				1	9	8	7	6	0			3	.		12	اِ	=	9	8	7	6			+	^					ı	3	1		Ė	TO! AMP	NEW AMP DESIGNATION	-				
+		H	L		1	-		_			+	1			-	-		_	1	1		-	_		L		1		1		-	_	"	1	1	1	-[-	_	۳	Ľ	ľ	1	1		-	Ĺ	Ĺ	Ĺ	ľ		ľ	1	-	-	_	_				ľ		ľ	+	+	1			L	Ĺ	L	1	-		20	2	_	+	-		
		١											i																																																														Ş	NEW AMI	2				
\parallel				t		†					t	+		-	1	1				-			1		-	-			+	+					\dagger	+	+			-	-	l	\dagger	+	+	\forall		l	-	+	+	1	+	1					-	-	H		t	+	+	+	+		-	H	l	l	+		AME	DESIG			$\frac{1}{2}$		
\top	1	H			t	1	1				t	1	1	-	1	1			t	t	†	1			ŀ	H	t	t	†	+	1		t		t	t	†	1	1	r	\vdash	t	+	†	+	+		f	f	t	t	+	\dagger	+	+	+		Н	Н	H	t	H	t	t	+	1	+		H	\vdash	t	t	+-	+	#		1	t	$^{+}$	Т	+

101-7 201-7 201-7 201-7 DIRECT I/O DIRECT I/O DIRECT I/O DIRECT I/O DIRECT I/O DIRECT I/O	PAGING PAGING PAGING PAGING PAGING PAGING	PAGING PAGING PAGING PAGING PAGING PAGING PAGING PAGING PAGING PAGING PAGING PAGING PAGING PAGING	PAGING PAGING	
	MIC 1	MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2	MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2	TOTAL OUTPUTS TOTAL AMP CH TOTAL AMP CH RVERD TYPE MIC 2 MIC 1 MIC 1 MIC 2 MIC 3 MIC 2 MIC 2 MIC 3 MIC 2 MIC 3 MIC 2 MIC 3 MIC 2 MIC 3 MIC
	RKNO	REAL REAL REAL REAL REAL REAL REAL REAL	RKN07 RKN07 RKN07	PACH RICKY
	X L X L X L 2	7		
				JACK IN
	AMEL 313 AMEL 313 AMEL 314 AMEL 314 AMEL 314 AMEL 315	AMEL 307 AMEL 308 AMEL 309 AMEL 309 AMEL 310 AMEL 311 AMEL 311 AMEL 311 AMEL 311 AMEL 311 AMEL 311 AMEL 311 AMEL 311	PANEL 301 PANEL 301 PANEL 302 PANEL 302 PANEL 303 PANEL 303 PANEL 303 PANEL 303 PANEL 305 PANEL 305 PANEL 305 PANEL 305 PANEL 305 PANEL 306 PANEL 306 PANEL 307	ROE
				TYPE
				RACK
				LOCATION OUT
20 20 20 20	Q			DESC / SOURCE
RKN07 RKN07 RKN07	X NOT			OCATION
AMP-72 AMP-72 AMP-72 AMP-72	AMD.72			NSB NORTH AMP OUTPUT CHANNEL LOCATION DESIGNATION CH AREA
- 0 2 4				NOR.
CX204V CX204V CX204V	CVA			TH AMP
1 1 1 1 1 3 1 1 1 1 1 1	1 1 1 1		2222222222222222	P RO
(NO7 (NO7 (NO7 (NO7 (NO7 (NO7 (NO7 (NO7	(N07 (N07 (N07 (N07 (N07 (N07	(NO7 (NO7 (NO7 (NO7 (NO7 (NO7 (NO7 (NO7	RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07	NSB NORTH AMP ROOM 301-433 NITPUT CHANNEL NEWPP LOCA NATION CH AREA DESC RACK PP RANDT C
7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7		11 11 11 11 11 11 11 11 11 11 11 11 11		301-433
223 223 223 223 223 223 223 223 223 223	3 5 5 5 5 2 2 3	13 12 11 1 10 10 9 8 8	- 0 0 0 0 4 4 0 0 0 0 7 7 0	15 16 16
RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07 RKN07				RACK
22222222222	8			QSC I/O#
				O CONNE INPUT
. ω ω 4				СТІОИ ОЛГРИТ СН
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				AMP OUT
				OSC I/O CONNECTION NEW AMP DESIGNATION NEW AMP DESIGNATION OF CHI CHI CHI CHI CHI CHI CHI CHI CHI CHI
				ESIGNAT AMP#
				NO S

	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HAI D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL DIADDITIVE 31	HALL DIADDITIVE 2)	HALL D (ADDITIVE 2)	HALL 0 (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (ADDITIVE 2)	HALL D (BASE BID)	HALLU (BASE BID)	TALL D (BASE BID)	D (Droce oil)	יפינר ט (מיפר טוס)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	ואררים (פאסה פוט)	Section (Brose pro)	HAT D (BASE DID)	HALL D (BASE BID)	HALL D (BASE BID)	HAI D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	HALL D (BASE BID)	TRUCK DOCK	TRUCK DOCK	WEST MEZZ	WEST MEZZ	WEST CONCOURSE	WEST CONCOUNSE	AND CONCOURSE	WEST CONCOURSE			RM BEING SERVERD			TOTA	TOTAL	101
	İ																																																																T	Ī		İ	-	347	1		LAMPCH	TOTAL OUTPUTS	INPUT
												I																		ĺ									ľ	Ī				1												Ì									ľ			ZACS	DACK .	_		ı	i	l	
	‡	F					†	+	†	†	†	†	1	1	1	1								-			†	1	+	+	_								-	+			+	+	+	1					_			+		-		1				_			ľ	ļ	+	77		OCATION IT		- 15	9 2	6	75
	+	-	_				1	+	+		İ	+		1	+	1	1	+	1	-		-	L			ŀ			1	1		_					L	L			l	t	ļ	1	+		-	-		-						-	-		-	-			_		l	ŀ	l	Ś	200	DES.	3		1	+	_
				ĺ	į																																										İ			ļ					ı														DESC / SOUNCE	O SOLID				i	
}		L			+					-	-	+	-	+	+		1	1						L	_	L			ļ	ļ	+	-								ļ.			ļ			1	-		1				4	4					-							L			L	1	-	ļ	4		
.	1				-	1	-	-	ļ						-	1		1				4					ļ			1								_	L	Ĺ	L		Ĺ	-							-															L			i i	Š					
																																																		ĺ																	- Indiana	ZACX	5	3					
	+		1	+	+	1		-	L	ŀ				Ì	1	+	+	+	1	+	1	-	-								1							_	_			F		-	Ŧ	1		1	1	1	-	-		7	1	1	1	1	1	-	1							JACK	Ž	OCATION OF		F			
ŀ				Í	İ		+	İ					-	l	l	T	Ì		İ	1	1	1					İ	l			t											r				ļ	1	+	+	1		1	+		1	†	+			1	+							Ľ	`		ŀ	l	1		
				ĺ																										-				i										ļ																									DESC / SOURCE	200					
													T	Ī	Ī	Ī		Ī		1	9	CSEC	CSEC-04	CSEC-04	CSEC-04	CSEC-04	CSEC-0	CSEC-04	CSEC-04	COECA	200	CSEC	CSECT	CSEC-D	P 2 ISO	OSEC-0	SEC	OSEC-0	CSEC-04	CSEC-04	CSEC-04	CSEC-0	CSEC-P	COEC-P	2010	200	CSEC	CSEC-D	CSECTA		CSECA	CSEC-0	CSEC	200		200	200		200			CSECA	CSEC-0	CSEC	CSEC-0	CSEC-04			LOCAT						
-		+	+	+	1	+					ŀ	-				ŀ			1																														AMP-03													- 1	- (- 1		4 AMP-01	i		ON DES		L	-			
																		-			8	3 8	8	8	8	6	8	8	ŝ	S	8 8	3 8		3	3	ଝ	S.	\$	2	2	2	\$	\$	\$	2 2	3 2	3 8	3 8	3 8	3 8	3	8	3 8	3 8	3 8	3 6	3 8	3 8	3 4	2 2	5 5	5	5	럿	9	효			GNATION	AMP					
F		1	1	+	-												-	-		l	1 1 20	7 5		5 15-2	4 LF-2	3 F-1	2 LF-18	1 15-7	8 LF-16			6 1 1 1			3 11	2		8	7 15-7	6 FF	5 LF-5	4 LF-4	3 LF-3	2 15-2	-	13	n 4			٠ - -	- ,	20 -	, 。	n (n +		5	3 -		٠,		η.	4	ω	2	1		F	오	AMP OUTPUT CHANNEL	-		Š	ž	
															!										1									ŀ												07-11/CZ-1L	36 UL 36	2 1 2	HF-18,HF-20	200	7 45 19	515	I I	En 41 En 43	מולים לי	0,77	1	1	1	, -		. اد	3	ω	2	-1			AREA	HANNEL			אלבט האבר ע אואיד אסטואו (ד	CT L	-
									-										İ	İ	10000		ED SOL	ED BOH	ED 80H	IED 80H	IED 80H	IED 80H	IED 80H	HOB CH	Ş			5 6	200	E 6	5 5	ED 80	三 日 8 日	ED 801	IED 801	IED 801	IED 80H	HED 80H	ED 80	Ē		500	٥		5 5	5 6							100		1000	10000	IED 200	ED 200	IED 200	IED 200			DESC				Ę	=	
}	CSEC-02																				MANON W	AAOO7 III	WINDS IN	WOOK IN	M 200W	M 200W	M 200W	M 200W	M 200W	M 200W	MOD W	AAOOY M	AAOOY M	WOOD I	WOOD IN	M 200W	WOOD W	M 200W	M 200W	M 200W	IM 200W	M 200W	M 200W	M 200W	M 200W	MUZUUW	AAOON MI	AAOOZ WI	MOD WITH	AAOOZ MIL	AAOOC PR	MUUC M	WOOC M	AAOOZ WI	AAOOZ WIL	AADD7 WL	AAOOZ WI	AAOOZ WI	V		1		Į.	۶	\$	₹							7 7	200	
CSEC-02	CSEC-02	0.0380	COLCO	CSEC-0	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	SECO	CSEC-02	CSEC-01	CSEC-02	CSEC-02	CSEC-0.	CSEC-03	CSEC-02	CSEC-0	CSEC-02	CSEC-0	500	2000	Cello	CSECTO	CSEC-O	CSEC-0	CSEC-0	CSEC-0:	CSEC-0	CSEC-0	CSECT	200	2000	2000		CSEC		CSEC	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC	2000	200	CSEC-O	200	200		200	2000	0.000	25	201	2010	25	Conco	2000	2000	200	CSEC	CSEC	CSEC-C			RACK	NEV		H	ON	2	
K	Z.	2 3	: 3	3	3	3	Z.	2	Z	3	æ	S.	M	3	×	×	3	3	3	3	~	7	5	× :	~	0	0	0	0	0	0	9 0	0	3 2	2	E 3	5 F	S	2	2	N Z	2 M	Z M	2	3	3	3 3	3 1		3 2	3 8	2 3	2 3	: 3				. 3				3 6	3 1	7 :	ام ح	7 7							PHASE-1	٥٠٠	
22	21	3 2	5 6	17	16	15	14	13	12	-	5	9	8	7	6	cn	4	ω	2	,	24	3	3 2	3 !	2	8	7	o	ر.	4	4	,	, -		3 5	3 2	3 :	2	8	19	18	17	16	15	4	13	3 2	;	100		0	» -	, 0	, ,				, .				3 4	3	:	5	9		i	JACH	VPP LOCATION			1	1	
CSEC-	CSEC-01	CSEC	CSEC-	CSEC-	CSEC-	CSEC-	CSEO-	CSEC	CSEC	CSFC.	CSEC	CSEC.	CSEC	CSEC-	CSEC-	CSEC.	CSEC.	CSEC	CSEC.	CSEC	CSEC	CSEC	200	Cent	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	2000	2010	200	200	Caro	200	200	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	255	200	CSEC	CSEC	2000	200	200	200	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	200	200	200	CSEC	SE			RACK	Ιi	L				
\vdash	01	+	╄	∸	-	_	-	-	-	-	L	4	_			_	_	ـــا	_	_	_	_	_	_	_	_1	_		i		_	_		1		1	1		_1	_1	!	l F	- 1		ı	ı	1	1	1	1	1	1		1	1	1	1	1	ŀ	1	1	1		- 1	- 1	- 1									
		-	-	-	_	-	1			1			-	•	*	•	*		Ľ	Ľ	F						-	•	-	_	_				1	-	1	1	1	Α.	4	^	1	4	^	-	-	*	4	4	-	- 4	1	4	4	4	4	•		3	3	0	3 6	20 6	۵	<u>ت</u>		- 1		QSC I/O CC					
L	+	t					1	1	1	1	1		1	-						F	-	-			1		1		-					-	1	1		+	+			-	-			-		ŀ	-	l				l	-	ŀ					-	-						Ω	미	NNECTIO					
22	22.0	19	18	17	16	15	1	12	3 -	1 2	5,	٥	8	-1	6	CF:	4	3	2		_	u		, .	.	3 !	ω,	30	28	28	27	26	2	1	2 2	1 2 2	1	2 2	212	1	18	3	4	#	<u>,</u>	-			5	9				5	4	3	2	_	24	N	, N			, ,	اد	2		٥	AMP	z				i	
CSEC	CSEC-05	CSEC	CSEC	Ш	ı	- 1		1	П	П	1	- 1	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	COEC	1	-	- 1	- 1	- 1	- !			1	1		1			-		- 1	- 1	- 1	- 1		1	ı	1	1	CSEC-05	1	1		ı	1	ı	CSE	CSE	ı	1	1	1	1	1	1	- 1	- 1		_	OUTRAC	NE)	+	_			
H	+	╁	Н	Н	+	+	+	+	+	$^{+}$	+	+	+	┪	+	┪	Н	7		Н	H	┢	╁	$^{+}$	+	+	+	+	+	-	-	٠	╁	۲	+	╁	╁	╫	+	+	+	+	+	_	Н	H	╀	╁	-	⊢	╁	╀	╀	+	┝	H	╀	⊢	Ͱ	⊢	╀	╁	╀	÷	+	+			Σ Σ	V AMP DE					
22 2	7 4	21 3	21 2	Н	+	+	S 5	3 7	t	t	+	+	+	+	18 2	18	17 4	17 3	17	17 1	25	H	20	t	t	t	24	+	+	-	Н	23 2	t	4	t	t	╁		$^{+}$	+	21	21	+	20 3	H	20 1	19	t	19 2	╁	18	Ė	18	t	17 4	17 3		17 1	14	14 3	16	4	t	, C	+	5	-	와 와	MP#	SIGNATIC		-			
Ц		L	Ш		_	_[1	Ĺ	Ľ	L		_[Ĺ	Ĺ	Ĺ	Ĺ	1	ľ	1	1	_[1		Ľ	Ĺ	Ĺ	ľ		Ĺ	Ľ	ſ	1	1	1		_		L	Ľ	Ľ	Ľ			ľ	Ľ	Ľ	Ľ	۳		Ľ	Ľ	Ľ	Ľ	1	ľ	1	1	1		1	Ĭ	ž			_	اـــا	l

W213	W212	W212	W211	W211	W210	W210	M	HALL D (ADDITIVE	HALL D (ADDITIVE	DALL O (ADD) I I VE	האבר בי (אניטון ויאר	TALL D (ADDITIVE	TALL DO CADOLLAR	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	TALL D (ADD) I I VE 2)	TALL O MODILIVE	TALL DO SOUTH A	EAL D (ADDITIVE	100000000000000000000000000000000000000	TALL DISCOURSE	HAI D ADDITIVE	HALL D (ADDITIVE	HALLO (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL DIACOLINE	2000	HALL D VADOUTIVE	HAL! D ADDITIVE	HALL D (ADDITIVE	ÁDDI	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADD)TIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	ĝ	HALL D (ADDITIVE	AB	HALLO (ADDITIVE	ADD	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	밁	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE	HALL D (ADDITIVE		TALL O (ADDITIVE	יארר ה (אסהו) ולנ	דוכ	TALL D (ACCULA	TALL D (ACC) IV	HALL D (ADDITIVE	HALL D (ADDITIVE		RM BEING SERVERD						
-					_		2	2)	2)	1	2		*	1	2	2)	2)	2	2)		1		1	*	2	2	2	2)	2)	2)	[2]	-	*	*	ا د	١	2	او	21	2	23	2)	2	2)	(2	2)	2)	2)	2)	(2)	2)	2)	2)	2)	2	2)	3 6	-	1	1			-	1		2)	2)	1		- 1	-	TOTAL AMP CH	OTAL OU	CIAL	
F												-		+	-			F	L			+	+	1									-	+	+		1			1				-	-									1		+	1	1	-	-		-				L	L	П	3977			MPCH	TPUTS	SFO C	
Ĺ										-												1			1							L	-		1	1																	ĺ						1				-			L		RACK	LOCA			97	1	ú	
ŀ	1	-							ŀ	_	ĺ				1		-		-	-	l	1	t	ł						-		-	\mid			1	1	+		+	+	+	+	1	-										1	+	T	+						+	+	-		PP JACK	LOCATION	INPUTS	1				
																																																																					DESC / SOURCE						
	1	1	1									l	Ī		İ			١			İ	l	T	T			1	1	1				l	T	†	t		İ	T	İ	1		1	1									1	1	T			l	T	İ									TYPE		1	-	-	_	
		1		1					_					l													t		1	1				l	\mid	\dagger	İ			†	+				1				1	1			1			+				l		-		_				RACK		-	-	_			
H						-				_				ĺ			_									l	ŀ								-				-	$\frac{1}{1}$		1	-	1									+	-	+	-							_					PP	LOCATION	2	+				
	1	-		+	-	-									-	-							L			-	-	1							-	-	-	1			-	-	1			4	+			1			_	1	ļ				L		L	_		L						STU					
																																																																					DESC / SOURCE						
CSEC-03	60000		600	SECTO	SEC-03	SEC-03																																		ļ									ĺ																				LOCATION						
AMP-02	2870	AMPO	A CANA	A COMPA	AMP-01	AMP-01																																						1																								- 1	DESIGNATION CH	AMP					
_	,	ıσ	, ,	n z	,	3	1	1				-			l	+	1	1					_				l	ļ		1		-	L	-	F	t	t	+		ļ	†	ļ	‡	†	1	1		1		1	1	1	+	+	ļ	ļ	L		L								+		요	8	+	-	≤		
>	>	- a	>	> 0	0	Δ					Ì																								i																																		AREA	CHANNE			EST HA		
IED 200W	IED ZOOW	IED 200W	IED ZOOW	IEO ZOUN	100000 COOK	MUDG CH																																																															DESC				WEST HALL D AMP ROOM (P		
CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	2000	CSECUS	200000	00000	Concord	CSECUS	CSEC-03	CSEC-02	CSEC-02	CSEC-02	CSEC-02	0000	CSECTO	CSECTO	CSFC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	COEC-02	000000	Conco	CSECUO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	20-02-02	70-0162	COEC-OZ	0000	Cercos	CSECTOZ	COLO ST	CSECTO	CSECTO	2000	COLORES	CSECUS	Concor	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02		RACK			- 0	S NOOR		
െ	G	၈	G	G	9 6	0	0	0	0	'n	o	S	s	s	S		2 4	3	5	o	۵	O	۵	۵	Ð	۵	۵	c	2 6	,		٥	۵	۵	۵	o	0	c	0	£	۵	c	c	o		,	0) (5 6	0 0	0 0	> 0) c	0	0	0	0	0	0	0	0	0	٥	0	0	Z.	×		PP JACK	9	ľ	100	HASE-1)		
	l			~		٠.		-	4 0	8	ת	-		2	_	ı		1	ı	21	-							ı	3		-		ç	g	7	o	5	4	u		-	24	2	3 2	3 -	2 .	3 4	à	5	7 6	5 , 5	2 1	1 2	1	=	16	90	8	7	Ø)	5	4	ı	2	_	2	23	9	JACK	TON.		:	<u> </u>		
CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	2010-01	COEC-01	000000	00000	0000	0050-01	2352	CSEC-01	CSEC-01	CSEC-01	CSEC-01	C9EC-01	CSECON	2000	CSECO	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	Carcoll	25000	0000	0000	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSECO	0-010-0	2000	COECO	0000	00000	Conco	2000	2000	COLCOL	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSECO	CSEC-0	10.01	RACK	t					
នន	⊢	Н	H	⊬	+	+	+	+	+	+	+	+	\dashv	_	H	╀	+	+	+	+	-1		4	_	Н		⊢	₽	+	+	+	4	_	05	┡	╙	05	<u> </u>	┺	┺	05	Ļ.	╀	╀	╀	+	+	+	+	+	+	+	200	╀	₽	⊢	L	Ь.	Н	Ц	-	4	4	4	4	4	1		100						
						I	l		Ī	Ī	Ī																																			Ì		Ī	Ī	1		1	Ť		l						1						2	2	NO CON	5000	İ				
					Ī		Ī			1	İ	1				<u> </u>	1	1	1										I		1						T							l	T	t			T	İ	ı		†								1	1	1	1			9	2	S I S	ECTION					
7 0	55	4	3	2	-	1	ī	10	1		3 ,	3	1	10	9	a	•	4 0	0 4	,,	4	3	2		32	31	30	29	200	1	3 2	36	25	24	23	22	21	20	16	10	17	ō	25	1.2	1		3 =	÷ =	5 4	0 0	0 ~	40	0	-		22	-1	32	31	30	28	28	27	26	25	2 5	2 5	2	DOUBLE	-					
CSEC-US	CSEC-0:	CSEC-0:	CSEC-0	CSEC-0	CSEC-0,	CSEC-0:	CSEC-0	CSEC-0	Conc.o	2010	2000	00000	CSEC-0	CSEC-0	CSEC-0	CSEC-0.	0.000	0.000	2000	00000	CSFC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0.	CSEC-0.	CSEC-0	Conce	2000	CSFC-0	CSEC-0	CSEC-0.	CSEC-0.	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	00000	CSEC-0	Conce	0.000	Control of	CORCA	Conce	CSEC-0		CSEC-6	0:SEC-6	CSEC-05	CSEC-0	CSEC-0	0-03SO	CSEC-0	CSEC-0	CSEC-0	CSEC-6	CSEC-0	CSECO	CSECO	3	MO# INPIT OF TRAIL OF THE PACK AND # CH	NON	-				
3 8	Н	+	۲	Н	H	╁	╁	╁╌	╁	t	$^{+}$	+	+	+	-	H	╁	╁	+	+	+	+	+	+	\dashv	-	-	┞	╀	$^{+}$	+	+	\dashv	_		H	-	H	H	H	H	┝	H	╀	╀	╀	21/2	+	+	+	3 3	+	8 8	H	\vdash	Н)5 25	24	┪		1	1	1	+	23	$^{+}$	3	Own	AMP	TO DECK		1			
3 2		+	-	2	H	H	4	╁	t	t			,,	2	1	4		t	+	+	١,	ω I	2	_	44	ω	12	-	4		3 ,	١,	_	4	3	2	-	4	H	N	_	4		1:0	-		. (4	,	,	4		t	╁	_	(3)	2		4	Ç3	22	+	4	+	2	<u></u>			1	# GNA	1	H	1			

TIE-LINES	TIELINES	TIELINES	TIE-LINES	TEL NES	TIELLINES	TIELLINES	TIE-LINES	TIELLINES	TELINES	TELINES	TIELLINES	TIE-LINES	TIELLINES	TIE-LINES	TIE-LINES	TIE-LINES	W236	W236	W235	W235	W.C.W	A COM	PECON	VC27	WZ3Z	W231	W231	VVZ3U	WZ30	W229	W229	W228	W228	W227	W227	W226	W226	SCCW	477AA	W224	W223	W223	W222	W222	W221	W221	W 220	W219	W219	W218	W218	W21/	W216	W216	W215	W215	41 ZAA	W213		RM BEI		Ī		T	1
																				i						-																																		RM BEING SERVERD		707	IOIA	777	1
П			1	Ī	TIE-LINE	TIE-LIN							III.	TELIN	III.	TE-LN	İ		1	1	Ì			T	T	ļ	T	İ								Ì	İ	t	T	t				Ì			İ					t		-	-	1	t			골	İ	AL AMP C	001701	TOTAL CHITCHES	
Ħ	Ī		T	t	CSEC-C	CSEC-02	CSEC	CSEC	CSEC	CSFC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC		1	1		İ	İ	T	t	T	l										Ì				t				1	1					1		İ			1		t		RACK		-	Ŧ	0	0	1
		1	1		-	2 A	-+	_	-	-	-	\rightarrow	-	-	\rightarrow	_	1		+	1	‡	+	+	-				L		L		L						\downarrow										L		1	ļ	ļ	L		+		l		PP	LOCATION	₹	97	2 2	6 6	4
\parallel		+	+	-	24 TC		22	2 2	3 3	1 2	3	3	6	5	1	13	+	1		+	1	+		-					L	L	_	L	4			1	1	-	-		L					1	1	L			1	L	L		4	1			Ř	ŝ	0		L	ļ	
					W 4.032 AV	TO W 4.032 AV	W4.032 AV	W4032AV	VA 020 A V	WA DRO AV	MEZZANINE (224)	MEZZANINE (224)	MEZZANINE (224)	MEZZANINE (224)	MEZZANINE (224)	MEZZANINE (224)										-																																-		DESC / SOURCE					
	TIE-CINE			TIE-LIN			Ť	T	Ì										Ī	l							ľ								7	1	T						Ì	İ	1	†	T					İ				1	l	l		꿃	İ	r	T		
TIE-LINE CSEC-02	CSEC		CSEC	CSEC		1				İ	İ				1				1		+	+		l			l				_	-	1									-			1	1					\dagger	t	-		l	İ	t		RACK	_	-		<u>}</u>		
8 8		_		-					1				1		+		1		1	İ	L	_		L			L												ŀ	_	_					+					_					1			g	LOCATION	2	l			
13 0	=	4 4	1 =	٦		_	-	-	+	1	-		1	-	1	1		-					L						L							-		ļ	_	L						1			-	_	+							L	~	_	110				
D PHASE 3	AUDITORIUM	AUDITORIUM	AUDITORIUM	AUDITORIUM																																										-														DESC / SOURCE					
									ļ							00100	SECO	CSECOS	Second	COLC SO	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSECUS	CSECTO	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSECTOR	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSECOS	CSEC-03	CSEC-03		LOCATION					
																Cient do	AMP-07	AMP 07	AMP-07	AMP-0/	AMP-07	AMP-07	AMP-07	AMP-06	AMP-06	AMP-06	AMP-06	AMP-06	AMP-06	AMP-06	AMP-06	AMP-05	AMP-05	AMP-05	AMP-05	AMD-05	AMP-05	AMP-05	AMP-04	AMP-04	AMP-04	AMP-04	AMP-04	AMP-04	AMP-04	AMP-03	AMP-03	AMP-03	AMP-03	AMP-03	AMP-03	AMP-03	AMP-02	AMP-02	AMP-02	AMP-02	AMP-02	AMP-02		DESIGNATION CH AREA					
H	7	F		H	7	-	+	l	Ī		-		-	1	1	G	2	10	0	4	ω	2	-	8	7	6	ch	4	အ	2	_	۵	7	0	y 1	٠, د	s N	,	8	7	6	5	4	3	.	<u>-</u> α	, 7	6	У	، 4	2 12	_	8	7	o (4 4	ω	2	-	CHO		L	S.	ź	
				•												0	2	0	, -	• a	>		>	8	>	œ	Þ	8	Þ	8	Þ	8	>		•	0 3	• •	, >	6	Α	8	Α	œ ?	> 0	20/3	Þα	,	æ	>		- m	Þ	6 0	>	20/3	> 00	×	В		AREA			N IN	of EA	
																IED ZOUVY	IED 200W	ED SOOM	IED ZOOW	IED ZOOW	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	ED 200W	ED 200W	ED 200W	ייייט אא	ED 200W	ED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	ED 2000	MD020M	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W	IED 200W		DESC			WEST HALL DAME ROOM (THASE-1)	:	
CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	SEC. SE	CSECTO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSECOZ	2010	COLUMN TO A	20-02	2000	CSEC-UZ	20-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSECTO	2000	COEC-OZ	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSECUS	CSECTO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSECTO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02		RACK			OOM (F	5	
w w	+	+	H	+		+	+	✝	۲	t	+-	+-	+-	+		t	$^{+}$	t	-	+	1-	t	-	_		-	-	-	-	-	_	-	-	+	-	-	-	-	-	-	-	-	+	╅	+	$^{+}$	t	ဓ	+	+	t	H	\forall	+	+	+	⊢	Н		P CO			HASE	5	
13 12	3 2	9	8	7		100	15	7	ü	12	=	ē				10	0	4		2	-	24	23	B	21	20	19	18	17	6	5	1	<u>ئ</u>	3	:	ŝ «		7	6	5	4	ω	N)-	. 4	3 5	3 13	21	20	i 0	1 7	16	15	1	<u>ئا</u> د	3 =	10	9	8		PP LOCATION			-1	١	
	+				1	+	-							l		CSEC-03	CSEC-O	CSEC-UT	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-01	CSEC-0	CSECO	CSECO	CSECO	2000	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	CSEC-0	Control	Conco	CSEC	CSEC-0	CSEC-01	CSECTO	Conce	CSEC-0	CSEC-0	CSEC-0	CSEC-0	COLCO	CSEC-0	CSEC-0	CSEC-0							
	1		1	1	ł	+	-	H	-		ŀ	-	-			+	+	╀	╀	₽	⊢	⊢	H		Н	\dashv	Н	_	4	4	4	4	4	4	4	1	\perp	L	L	Н	4	_	+	4	4-	4	Н	2	4	1	╄	Ц	4	4	4-	┸	L	Ш		280	L				
	Ī				Ī							T	T	T				T															İ	1	T	T	T				1				l				Ì							Ī	-		£ .	I O CON					l
H				Ì	1	İ							T	T	T														-			1	1		t	l		r	-			1	t						\dagger	+					t				2	INDIT CHIEFIT	-				
	1													+	t	N	21	22	19	- 500	17	16	15	14	13	12	=	5	9	8	7	6	7 4	١,	۵ ۸	, -	32	<u>ي</u>	30	29	28	27	26	24	2 6	2 12	21	20	à	-	16	15	14	13 1	3 =	10	9	8	2	D GWA T					
H		-	+	\dagger	-									+		CSEC-	CSEC-	CSEC-	CSEC-	CSEC-	CSEC-	CSEC-	CSEC-L	CSEC-	CSEC-	CSEC	CSEC-	CSEC-	CSEC	CSEC	CSEC	CSEC	CSEC	COEC	200	CSEC	CSEC	CSEC	CSEC	CSEC-	CSEC	CSEC	CSEC	COLC	2000	CSEC	CSEC-	CSEC	CSEC	CSEC	CSEC-	CSEC.	CSEC	CSEC	CSEC	CSEC-	CSEC-	CSEC	10.01	NEW AMP D		H			
H	+	H	+	+	+	l				L		-	F	-	L							03 12																										8											3	AMP DESIGNATION	H	\parallel			
Ш	+	H	4	+	╀	+	H	Н		L	L	L	F	+	+	Ë	_	3	F	٣	3	2 4	2 3	2 2	+	+	+	2	7	+	3	+	1	1	1"	1	<u> </u> "	Ĺ		8	7	1	1	10	٥١٩	0	6	5	1	70	H	4 3	1	- (4	3	3	2	1		L	Ц		1	l

HALL D FOB	HALL D FOB	HALL D FOB	HALL D FOB	HALL D FOB	HALLDFOR	20100	150	HAIL DEOR	HAI I D EOB	HALL D FOR	HALL D FOB	HALL D FOB	HALL D FOB	TWILL D TOB	TALL OF CO.	HAI I D FOR	HALL D FOR	HALL D FOB	HALL D FOB	HALL D FOR	HALL U FOR	1 NEL 0 100	2000	HAIL DEOR	HALL D FOR	HALL D FOB	HALL D FOB	HALL D FOB	HALL D FOR	15000	HAI I D EOB	HALL D FOB	HALL D FOB	HALL D FOR	5100	EAL DEOR	HALL DEOB	HALLDEON	HAIL D FOR	HALL D FOR	HALL D FOR	HALL D FOR	HALL D FOB	HALL D FOB	HALL D FOB	HALL D FOB	TALLUTOB	2000	DEC 00	HALL DECK	HALLDEOR	HALL D FOB	HALL D FOR	HALL D FOB	HALL D FOB	HALL D FOB	HALL D FOR	HALL D FOB	HALL D FOB	HALL D FOB	TIE-CINES	TIE-LINES	TIE-LINES	TIE-LINES	TIELLINES	TIE-LINES	TIE-LINES	I IT LINES	THE LINES	TOLINES	TIG - ENEX	TIE INIEO	- CE 100	RM BEING SERVERD				70.		
Міс	MIC	MIC	MIC	MIC	MIC	Mic	3	5 0	5	ž.	N.	Mic	MIC	3	3	5	S.	MIC	MIC	MIC	MIC	MIC	3 0	N C	2	MIC	MIC	MIC	MIC	300	N C	MIC	MIC	MIC	300			1	N I	N C	N C	MIC	Mic	MIC	MIC	MIC	N.C	3	1	5 0	2	2 1	NIO O	M.	MIC	M	M.	MIC	MIC	MIC											+		-	왕 집			DTAL AMP	TOTAL OUTPUTS	OTAL INPU	
CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	COEC-U	2010	2000	CSECO	CSECO	CSEC-02	CSEC-02	CSEC-0	COLC	2000	CSECTO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSECO	2000	Conco	CSECO	CSECO	CSEC-0	CSEC-03	CSEC-02	00000	2000	CSEC-0	CSEC-02	CSEC-0	Conco	2000	2000	2000	2000	CSEC	CSECTO	CSEC-0	CSEC-02	CSEC-0	CSEC-02	CSEC-0	CSECO	0000	00000	0000	2000	CSECO	CSECO	CSEC-02	CSEC-0	CSEC-0	CSECO	CSEC-0	CSEC-0	CSEC-0										-	1	MON	0000				İ			ı
ī																																																						0														L	L	ŀ		1	8	OCATION INFO	-	5	97	8	75	
6 至				12 KM	ı	1		1		1	2	8	19 IM:	18 IM	M		Ď	돐	Z Į	13 I	12	1			2 9	2	2	21 FU	20 FM	M		18 FN	17 FM	16 EL	Į.	2 12		3	3	2 5	2 9	2	∞ ₽	2	21	20 CN	19	2 2	2 5	2 2	<u> </u>	5 4		13 BM2	2	1 2	10 ·	e e	2 .	A.						L	L	L	L	ŀ	ŀ	Š	5	2	07	-	+	1	4	I
2	4	3	2														2	4	13	2		2	•		3 6	3	3	_	4		3 1	2		_	1		0 1	3		2 1	4	3	12	==	Z	4	3				2 1 7		a i	2	3	Z	4	3 1	5													1177	DEGC / GOORGE	300100100E						
																-																		_							Ì								Ī			l									TE-L NE	TIE-LINE	TIE-LINE	TIE-LINE	TIE-LINE	TIE-LINE	TE-LINE	TIE-LINE	TIE-LINE	TIE-LINE	TIE-LINE CSEC-02		177	ı						
																																		İ				Ī																						-	CSECUP	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	ZAC.		SIDAIDO						
	1									1	†	1		L	F	1	†	1					ŀ	ļ	†	1	1		_	L	+	+	-	_	F	ļ	ļ	Ť	1	†	1	1		+		-	L	L				#	+	1	+	1	#	1	1	,	20 0	В	m	œ	œ	ω.	00			00	00	Ę	Š	2017		+	_			
H	-	+		-		_	ŀ	H	l			1				<u> </u>	1	1					-	-	+	+					+	+	1					1	1	-	+	+	+	+		H		ŀ	ŀ		ł	1	+	1		-	1			13	70	70 TO F	201	70 TO F	101	10F	10F	17 TO F	16 TOF	15 70	10	ACK			<u>'</u>	+				
						_		L															-																																					1	CHEST	HASE 2	HASE 2	HASE 2	HASE 2	HASE 2	HASE 3	HASE 3	HASE 3	HASE 3	TO PHASE 3		DESC / SOURCE							
																	İ																			•		l															ľ																				LOCALION	COTON						
																																							-																		1																DESIGNATION C	AMP OUTPUT						
	1			-								l																				+				İ											_								1				+														AKEA	IPUT CHANNEL				WEST H		
												1																																																													DESC	200			i con and a second	WEST HALL DAMP ROOM (P		
CSEC-02	2000	200	2000	CSECUS	CSEC-02	CSEC-02	203 203 203 203 203 203 203 203 203 203	CSEC-02	CSEC-02	CSEC-02	CSEC-02	2000	2550	CSEC-02	CSEC-02	CSEC-02	20-0300	2000	CSEC OS	CSFC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	20-03-02	2000	CSECTO	CSEC-02	CSEC-02	CSEC-UZ	200	255	CSEC-02	CSEC-02	CSEC-02	CSEC.	COECHIZ	COECUL	COECOZ	Second	2010	Concession	CSECTO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	COECTO	Con Con	2000	000000	2010	CSEC-07	2000	2000	2000	CSECTO	COLO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02		RACK	, A			0	NSC NSC		
mir	+	+-	+	-1-	-+	+	+		-	Н	٠	+	+	-1	_	⊢	+	+	+	+	-		_	Н	Н	+	+	+	-+		╌	+	+	-	_	ŀ.	╁	┿	╀	┿	₽	+	+	+	4		Н	⊢	⊢	+	╀	+	+		+	+	+	┿	+	+	+	+	-4	4	-	-	_			⊢	Н	ŀ	F			H	3	PHASE-1)		
7		n .		۸	١.	-	2	23	23	21	20	3 4	3		17	5	ō	;	: :	3	12	=	10	9	00		1		5	4	4	٥,	٥.	_	24	23	22	21	2	120	12	;	3 6	100	5	14	13	12	=	5	6		,	10	,		١,	۰,	, -		2 2	3	3 !	2	20	19	18	17	16	15	14		JAC	V PP LOCATION			֡֟֝֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓֓	7		
																															-	-																						l																			RACK	1						
		İ		1									1				-	İ	1							İ						İ	1		_							İ	İ				_							l	T	Ì		T	1	İ										1			ò #	asc					ĺ	
																																						L																																		£	NPUT	O CONNE						
																													•																																					Ī						오	OUTPUT	CTION						
																																																																		Ī						오	AMP OUT							
										_																	Ī	1															T	1								Ī										1	T					1					RACK	QSC I/O CONNECTION NEW AMP DESIGNATION						
Ħ	T	ľ		İ							l		j	1			l							ļ					1		l			1					-	r			+	†	1					-		l		t	t		t	t				-	1	+	1								AMP#	P DESIGN	-	-	1			
T							I																					Ī					I	I								Ī	Ī	Ī	1																Ī	I	Ī	1									유	ATION			1			

															DIRECT I/O	DIRECT I/O	DRECT I/O	CIXECT IO	DRECT NO	DIRECT I/O	DIRECT I/O	DIRECT I/O	1	1	ŀ	HALL D WEST WALL	ı			HALL D WEST WALL		RM BEING SERVERD			TOTAL	TOTAL	TOTA
																							MIC	l		MIC CS	ŀ				22	TYPE			AMP CH	UTPUTS	TOTAL INPUTS
			L		-			1					_										CSEC-02 G			CSEC-02 G	EC-02 G	EC-02 G	EC-02	EC-02		10	_	_	97	18	75
-			_					-	+												L		8 98	7 97	8	5	4 04	3	'n	_	PP JACK	L	STO				
															,																	DESC / SOURCE					
											i														-							TYPE					
															1																RACK	LOCA					
-				L	_					1		-										_									PP JACK	LOCATION	OUTPUTS	-			
																																DESC / SOL					
										1								_										-				JRCE LOC					
			,								-							_			_											ATION DE					
							ŀ																	-								DESC / SOURCE LOCATION DESIGNATION CH	AMP OUT				
ŀ					-						1	-																				AREA	AMP OUTPUT CHANNEL			WEST	
- -			-								-										_			-							-	DESC	ř			WEST HALL DAMP ROOM	
							_	L							Ω	Ω	Ω	Ω	Ω	Ω	Ω	Ω	Ω	Ω	O	0	0	O	0	O		R				MP ROC	
			_												SEC-02	SEC-02	SEC-02	SEC-02	SEC-02	SEC-02	SEC-02	SEC-02	SEC-02	SEC-02	SEC-02	CSEC-02	SEC-02	SEC-02	SEC-02	SEC-02		RACK	NEW P		ŀ	$\overline{}$	
-		-					L	_		1	1	-		†	+		2	Α .	Α 4	A 3	A 2	_		-	E 13	+		+	+	E 8		PP JACK	NEW PP LOCATION		_	PHASE-1)	
ŀ		1	1								1	1						CSEC-01	CSEC-01		CSEC-01		5	4	3	2	1	٩			-1	RACK	_	-			
-					1								+	4	-	4	4		-01 01	-	4	01	_			1							စ္အ		-		
	İ					_					İ		1		4	3	2	1										1			요	NPUT	QSC I/O CONNECTION				
																			4	ω	2	_									요	/ TURTUO	ECTION				
-	 -	1	4									+		-						-							1		-		유	OUTPUT AMP OUT RACK	z				
																		-	4									-				ĆĶ.	NEW AMP DESIGNATION				
1	1																					ĺ										AMP# CH	SISI				-

1	HALLE	HALLE	HALLE	HALL	5	TA P	HAIL	HAILE	HALLE	HALLE	HALLE	HALL E	HALLE	HACLE	HACLE	אויר נו	2500	HAILE	HALLE	HALLE	HALLE	HALLE	HALLE	HALLE	TALLE		יייייייייייייייייייייייייייייייייייייי		HALL	HAILE	HALLE	HALLE	HALLE	HALLE	דארר ב	1 1	2 5	HALL	MAI I	HALLE	HALL	HA T	TRUCK DOCK	RUCK DOCK	TRUCK DOCK	TRUCK DOCK	TRUCK DOCK	TRUCK DOCK	- CNC		TICLUNC	TIEL NO	THE PROPERTY.	TIEL NE			TIEL CIVIC				TIPL INF	DIRECTIO	DIBECT I/O	DIRECTIO	DIRECTIO	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O			RM BEING SERVERD					
																																,													MIC 4	MIC 3	MIC 2	MIC 1	TIE-LINE	TIE-LINE	TIT-UNE	ווני-טאַנ	TIE LINE	TIE UNI		THE LINE	TIE LINE	TIE-UNE	TIC UNC	110 NO	TIFL INF											VERD TYPE		TOTAL AMP CH	IOIAL OUIPUIS	TO TOTAL THE COL	TOTAL INPUTS
	-							ĺ			+	1						1											+	1	-										1				CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	Concoda	Con Con	Conco	CSECOS	Concord	Cent Cold	TIE I NE CSEC-03	200	Cercos	2000	CSEC D3										RACK	LOCAT				100	
-									+	+	+						ŀ	+	+											1	1											+	+	+					7	-	-	1 =	1	1	1		1	1	1	1	+	1	+								P JACK	LOCATION	INPUTS		-	+	_
										1																																	-	and the second					O PHASE 3	OPHASE 3	OPHASE 3	O PHASE 3	O FINAL O	DELACE 3	O PRAGE -	O TRANSE	TOPHAGE	OPHASE 1	O PRIASE I	DIAGE	DELACE											SOURCE/CABLE ID					
									İ				1				İ	İ	İ										ľ	1									İ	ļ	T	İ		1	MICA	MIC 3	MIC 2	MIC 1	TIE-LINE	TIE-CINE	TIE-CINE	III-CINE	TIC CINE	יוניינייניינייניינייניינייניינייניינייני		TIE-LINE	TE-LINE CSEC-03	- In-LINE	1000	10-01/0	TICTING	l			1							TYPE				L	1
																															-										ľ	1		00000	CSECOR	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	COECAGO	200	COLC OF	Concord	CSECOS	CSEC-03	COECOS	COECAGO	20103	l			1						RACK						
F			1								l	I									1								l					_				İ			İ	Ī	1		1	1						<u></u>		+		ļ	ļ		ļ			ľ	1		1		1				PP JAC	LOCATION	OUTPUTS				
																			1												1																														T	1									×	CABLE ID	07				
																					-		İ					Ĺ																	-																											LOCATION					
587	586	585	188	583	582	581	580	579	578	577	576	5/5	27.4	574	573	572	571	570	986	500	568	567	566	565	564	563	562	561	360	909	500	7.50	557	556	555	554	553	614	610	606	602	10	700																													SPEAKER CKT CH AREA	AMP OUTPU		VVE	i i	
		+									-	-			j					l											-																							-	-		L								1							오 AR	CHANNEL		SI AM	; ;	
587	586	585	500	583	582	581	580	579	578	577	576	575	5/4	200	573	572	571	570	569	200	500	667	566	565	564	563	562	561	560	559	200	550	557	556	555	554	553	Z2008D	Z2008C	Z2008B	Z2008A	720020	720070																	_							l		-			CABLE ID			WEST AME ROOM 2.021 AV]	
CSEC-05	CSEC-05	CSECUS	COLCAGO	COECUS	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	COEC-US		CSECUS	CSEC.05	CSEC-05	CSEC-05	CSEC-05	COEC-OB	COLCAGO	2000	CSECUS	CSECUS	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	COLCAD	00000	CSECOS	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	COEC-02	CSEC-US	Concord	COEC-03	200	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-US	Concord	200	CSECUA	CSECUS			RACK	NEW P		.021 AV	,	
ន	8	3 8	3 8	3 8	+	\dashv	-1	\dashv	H	Н	⊢	⊢	۰	╁	+	+	\dashv	⊢	⊢	╀	ł	+	+	+	-+	\dashv	Н	⊢	⊢	⊢	+	+	+	-	\dashv	-	⊢	⊱	-	╁	H	╀	+	╀	╄	+	+	+	4	Н	Н	H	┝	⊢	⊢	⊢	⊢	ļ	⊢	⊢	₽	⊢	-	-	╀	+	4		+			공	V PP LOCA		(PHASE-2)	j	
23	1		ļ	ı	1	1	ı						ı	1		1		o		ĺ		ı		1	-	- 1						П	1	-	-1				ı	o		ı	ĺ		22	2 2	3	21	12	11	10	9	8	7	ฌี	1	10	ဖ	œ	7	4		2	_			,		1			PP JACK	NOI) -2	,	
CSEC-02	CSEC-02	COECUE	CSEC-02	STO STO	CSECTO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	COEC-0Z	2000	CSEC NO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	COEC-02	2000	CSECTO	COECUS	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	2000	CSECTO	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02																		CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	CSEC-02	000000	0000	CSEC-D3			R					
8	3	3 5	07	1 5	3	9	9	9	8	8	8	8	05	S	2 5	3	ន	2	ያ	g	\$	2 5	2 1	2 5	2	2	03	ខ	8	23	8	3 8	2	03	8	22	8	ន	02	ន	ន	22	02		l	İ		1							L						2	2	2	2	9	9	2	2 5	2		-	o d	0801			i	
	1	-		-		-									ļ	1																-								_																					4	3	2	-						1	2	NPUT	CONNEC				
		-			+	1				-											-	+											+		-										ļ															-					4	u	,		•	-	2	DUTPUTIA	Ž				
5 CS	1	1	ı	1	1	ı	CS	١	8 CS	1	6 CS		8 CS	ı	1	ı	5 Cs	- 1		ı	1	1	1	1	-1	5 CS	ı				L	١	1	ı	5 CS	-	11 CS	8 CS				Г	1					-																		-		+	1	9	2	NP OUT RA	2	-			
CSEC-06	S S	8	60 86	60.06	8 8	2 2	n i	3	e e	EC-06	96 EC	96 HC HC HC HC HC HC HC HC HC HC HC HC HC	EC-06	EC-06	S	8 8	5	90-0H	EC-06	ÉC-06	-06	8	88	8 8	3 8	8	90-09	EC-06	EC-06	ЖС-06	1EC-06	Š	8 8	8	86 66	е 6 6	8 6 6	EC-06	т С-06	EC-06	HC-06	EC-06	EC-06	_										L													L				1	ĆX .	EW AMP D				
ā:	t	t	H	t	t	3 1	+	+	+	3	+	5 -	-	3	t	t		13	13	13	13			3 1	3	12	4	3	11 2	-	10	+	t	3	1		9 3	08 4	ж 3	08 2	08	2	3													_																INPUT OUTPUT IAMP OUT RACK AMP# CH	ESIGNATION				

W232-A W232-A	W232-A	W232-A	W231-C	W231-C	WZ31-C	W231-C	W231-C	WZ31-B	W231-B	W231-8	WZ31-B	0-102AA	W 201-0	WORLD CO	W S	W21-A	W231-A	W231-A	W231-A	W231-A	W230-D	W230-D	W230-D	W230-D	W230-D	W230-D	W230-C	W230-C	W230-C	4200	COCCA	A CONTRACTOR	NO CO	W230-B	W230-B	W230-B	W230-B	W230-B	W230-B	W230-A	W230-A	W230-A	W230-A	W230-A	W230-A	TRAINING RM	CONCOURSE	CONCOURSE 255C	CONCOURSE		RESTROOMS	PREE NOTIO	PREFUNCTION	TREFONCIO	CORRIDOR	CORRIDOR	CONTRICT	CORRIDOR		CORRIDOR	CORRIDOR	HA.	HALLE	HALL	HALLE	HALLE		RM BEING SERVERD	!		ľ			
LINE	MIC 2	MIC 1		LINE	MIC 3	MIC 2	MIC 1			LINE	MIC 3	MIC 2	300	NO.			NA.	MIC 3	MIC 2	MIC 1			LINE	MICS	MIC 2	MIC 1			CINE	MIC	MIC C	E 0	Mich			LINE	MIC	MIC 2	MIC 1			LINE	MICO	MIC	MIC 1	J.,	1007	2550	AACC7	36614		2 2	2 2				ŀ				-						ı	ERVERD TYPE			IO AL AM	1017	TOTAL CLIT	TOTAL INPUTS
H	H														t	1	1				1			_	-					1		1				1					-												l	l		l		-			+		+	-			RACK				ç	0	100	SIR
								_		_			1						1																					-									L								-	+		+					1	_	PP	LOCATI	_		8/	1		136
	<u> </u>	5	-	=	š	Z.	M1			11	Z.	3	3		-	5		Z :	ς:	Y.	-	-		N.	Z.	Z			5	M	8		5			2	2	Z.	Y.			-	N.	N.	Z.				-	 -			l					F	ļ	1	-												1	1
M1012 L1004	213	010		103	M1009	800	007			02	M1006	005	Ç	8		2	100	3	M1002	200			3	030	M1029	028			9	170	020	2000	300		l	L1008	024	023	022			007	021	020	M1019				ĺ	-																-		SOURCE/CABLE ID						
																							-																																-							1						BLE ID						
			CINE						LINE						LINE		l	İ	ı	1								LINE		ľ	İ	İ	t	-	Z					-	ENE.					-	ľ	l	Ī		İ		ľ		l			T		İ		1	İ					TYPE					Л.	-
	İ									-					Ī	Ì					1	ĺ							_		l	İ	Ī	1	1	1					1							l	-			l	T	İ		l	-	l	l			t	1	1	1		RACK	_						
	+	ļ	F										ľ	-	ŀ	-		1	1	+	1	+	+	+								+	-	+	+	+	1	1			1		_				-		L	ļ	+	 -	L	L	L			l			+		1		1		8	OCATION	OUTPUTS		_			
	+		L4003			-			L4002		L	L	-		1.4001		<u> </u>	1	+	+	10.0	1 4012		1				L4011			L	ŀ	1	54010	1 401	+	1		1	-	L4009									-											-		+	1			Ř	CAB	JTS	_				
	ı		3						2						-							3												1		ľ					٩																											CABLE ID						
\mathbb{H}	+	+			1	+			$\frac{1}{1}$							L	<u> </u>	+	1		1	+		1				+			-			<u> </u>	+	+		_	+	+	+						L		L	-				L						1	-		+			_		5		_				
		120						=	-	4				=					-	-							4		_				-													M	3	3	3	u		3	w	6	6	4	4	ü	G			1	2	h (n c	(n		LOCATION						
		2						103	İ					104						100	8					ľ	40						141							3						MISSING	9	310	97	8	8 8	12	2	77	72	8	7	=	3	73	3 8	3	2 8	8	8 8	88		SPEAKER CKT	AMP O					
	-	_					1																	1																																					_				+	+		외	JTPUT CH	1		VYEG	100	
		ဂ						D						۶						ļ	,					,	2					i	α	,						•																								Ī				CH AREA	ANNEL			2	2	
		Z2001C				-	-	720018						Z2001A				l		720000	720027			Ì	1	10000	250002			-			220038	-	l	T				VEUUCZ	1	1					309	310	307	306	308	312	304	677	672	48	47	311	305	0/3	282	28.	200	500	780	588		CABLEID				AMIL YOUN YOU AA		
CSEC-03	CSEC	CSEC	CSEC-	200	25.0	200	2000	CSEC	CSEC	CSEC	SEC	CSEC-	CSEC-	CSEC-	CSEC	CSEC	CSEC-	233	25.0	COEC	2000	2000	Sec	2000	200	0000	CSEC	SE	CSEC	CSEC.	CSEC	CSEC	CSEC	CSEC	315	200	200	200	2000	Conc	200	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC-05	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	COEC	2000	COEC	2000	CSEC	- 1	RACK				1707	2	
6 6 6	1	ш		4	4	4	4.	_[_	_	_					L	L	L	L	L	L	Ц.,	┸	Ш	Т	\perp	_	_	_)	ಜ	ឩ	2	12	1	3 8	3 8		П	П	П	П	1	- 1	- 1	- 1	- 1		Н	1	1		Ι.	ı			ΙI			ı		1	1	1		1	- 1		ı	NEW PP			ᅩ		
4 3 2			17	Ī	1		1	Ī		Ī	1					Г	Ī	2	Ī	T	T	3 2	Ì	T	Ţ	Ť	Ī	Ť	1		r	T	T	T	Ť	İ	Ť	T	4-	T	חב	1	23	2	1	Ī		17		Г		Ħ	П				8		6	T	T			,		2		PP JACK	OCATION	1	_	PHASE-4	2	
CSEC-02	CSEC	CSEC	CSEC	SES	200	200	200	200	3 5	200	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	SEC	CSEC	2000	200	200	200	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	Core	200	200	200	200	2000	200	200	CSF	CSEC	-	- 1						П	П		1	ı	CSE	CSE	CSE	CSE	CSE	CSE	200	200	Con	20	- 1	RACK		+			3	
	₩	\vdash		+	+	+	+	+	+	4	+	+	-		Н	Н	⊢	⊢	⊢	+-	+	╀	-	╄	+	+	+	+				⊢	₽.	1	+-	+	+	+	+	+	4	4	4	4	4	-4	_	ш		_	1		Ш	Ш	_	Щ			_		L	┖	L	_	⊥	- 1		1	۵					ĺ
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	П	3	1	3 =	Ť	T	Ť	,	Ť	†	7	7	1	۵			Г	T	_	T	1	T	T	t	10	Ť	3 1	Ť	1		Г	9	T	Z	t	5 ×	t	†	Ť	3 6	t	†	3	T	2	9	å	9	9	9	8	9	9	9	8	9	9	9	9	20	9	9	3 3	6 6	6 6	5	2	WP.	SC 1/0 CC	+	_			
H			ω	1	+			,	, ,	1	1	1	-		_			-	-		4	-				-		د		_				2	+	+	+	-	+	-	+			-	-					_	L	L				-		-	L				-		-	2	2	OUT	QSC I/O CONNECTION	+				
	H	ω	+	+	+	+	^	,	+	1	-		+	_	-					4	+			1	1	6	3		1	_			2			+	-		-	-	+	1		+	+	17	6	15	14	13	12	-	10	9	8	7	6	5	4	3	2				10	200	2	ĂMP (-				
	H	CSEC-06		+	+	ŀ	COEC-00	200	+	+	+			CSEC-06	-					CSEC-06	-				-	Cattoria	2000	1				ŀ	CSEC-06					-	COEC-00	2010	+	1	1	1	- [- 1		CSEC-06				1		- 1		CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	Conc	Car		RACK	NE V	-				
-	Н	8	+	1	_		8	+					+	8	-	-				9	╀		_	L		8	ł						95	H	_	1			ŝ	ł					+	+	-	22	8	8	8	6	8	8	8	8	8	8	86	88	8	8	8	8 8	8 8	3		AM	NEW AMP DESIGNATION	+				
$\parallel \parallel$	H	`` ن	$\frac{1}{1}$	+	+	F	_	╀	+	+	+	+	1		+	-				4	\vdash			-	ł		+	\dagger	+	-			2	-	-	1	l	-	- -	+	+	+	-	1	-	+	+	3	\dashv	_	H	3	Н	+	+	ω ω	-	Н		H	9	9	100	$^{+}$) A	0		#	GNATI	+	_			

W330-E W330-E	W330-D	W330-D	W330-D	W330-D	W330-C	W330-C	W330-C	W330-C	W330-C	W330-B	W330-B	W330-B	W330-B	D OCCAA	W330-A	W330-A	W330-A	W330-A	W330-A	W330-A	W240-D	W240-D	W240-D	WALL	W240-D	W240-C	W240-C	W240-C	W240-C	W240-C	0-0424A	W240-B	W240-B	W240-B	W240-B	W240-B	W240-A	W240-A	WOADA	WOADA	W240-A	W232-C	W232-C	W232-C	W232-C	W232-C	W232-B	W232-B	W232-B	W232-B	W232-B	W232-A	W232-A	יישי טבוויס טבויאבויס	DAI REING SERV			
MIC 1 MIC 2 MIC 3		LINE	MIC 3	MIC 1		5	MIC 3	MIC 2	MIC 1			LINE	MIC 2	MICT			LINE	MIC 3	MIC 2	Z C		E I	NE G	MIC Z	MIC 1			LNE.	MIC 3	MICO	5		LINE	MIC 3	MIC 2	MIC 1		r in	NIC 3	MICA	MIC 1			N C	MICZ	MIC 1			LINE C	MIC 2	MIC 1		-	RACK		TOTAL AMP CH	TOTAL OUTPUTS	TOTAL INPUTS
222			22	2				2	-								_	-		-																													-				1	COCK HOW	STV	87	4	136
M1055 M1056 M1057		1018	M1054	1052		71017	M1051	11050	11049			1016	M104/	11046			1015	1045	M1044	110/13	-	1014	1042	11047	M1040			L1013	11039	1103/			L1012	A1036	A1035	11034		1017	M1033	W1032	M1031		,1000	1006 11017	M1016	W1015		1000	11005	W1014	M1013	11700	- The same	SOURCE CABLE ID				
	ENE				CINE						E I					LNE					CN						LNE	1				LINE	j				CINC	Ž					T N					Z					LINE	1775		1		_
					1															-																	-	<u> </u>				1	-						<u> </u>			1	A PP JACK	LOCATION	OUTPUTS			
	4020				14018					4010	4018		***************************************			4017					14018						4015					L4014					L4013	1010					7007				CHOOO	3006				11000	14005	CABLEID				
676	216			100	213				1	214					215					596						595					594			1		583						98					100					101		LOCATION SPE				
							-																																															AKER CKT CH	AMP OUTPUT CHANNEL		MEST	
D Z2006A				250020	ı				000022						A Z2005A					D Z2004D						C Z2004C					B Z2004B					A ZZ004A	L					22002				1000000	BC0000					AC0002A		AREA CABLE ID	I L	1000	WEST AMP ROOM 2 021 AV	
CSEC-03 M CSEC-03 M		+	H		-	\vdash	+		+	╁	╀	⊢	Н	-+	+	+-	╀	╀	⊢	L	Н	CSEC-03	CSEC-03	CSEC-03	+	CSEC-05	+	CSEC-03	CSEC-03	Н	CSEC-05 01	+	CSEC-03	Concrete	CSEC-03	CSEC-05 01	H	CSEC-03	CSEC-03	CSEC-03	-	+	+		\vdash	+	+	╀	CSEC-03 G	4	4	+	3	RACK	NEW	۔	_	
w w - 호	23	3 2	20	19	17	16	5 7		3 2	=	6	8	œ	7	17 0	n 4		2	-	16	23	Ш	1	H	19	3	170	1		13	14	11		1	1	13	c ₀	П	1	- 1	-	-	6	15	7.	<u>ئ</u> د	3 =	10	9	8	7	0		ı	PP LOCATION	יווקטריב)	ころのロッ	
CSEC-02 07 CSEC-02 07 CSEC-02 07	8 8 8	88	8 8	8 8	8	8	8 8	8 8	8	⊢	8	06	8	8 8	+	8	8	6	8	-	S	05	S	ន	S	_	8 8	ន	95	8		_	┸	-1-	┺.	↓_	ш	ш	Lì.			┸	ш		_L	.1			ш	1	. П		ш	RACK I/O# If	QSC I/O			
ω Ν Δ	4	5	4	-	3	12	1 6	9		2		7	o l	מ	-		ω	2			4	16	15	4	13		+	3	10	9		2	•	10	Ch.		1	4	ω	2		ω	8	7	6	λ.	2		ω	2		-	H CH	VPUT OUTPUT A	CONNECTION			
1 CSEC-06				3 CSEC-06	Ц				2 CSEC-06					Coec-up	2000					4 CSEC-06					0000						2 CSEC-06					1 CSEC-06					SEC-06	L				Z CSEC-06					COEC-00	2000	CH CH CH	MP OUT RACK	NEW AMP			
88	H			8				┝	95 2	Н				5					Н	2					ç	+				+	2					2					3	t				03 2	H				8	3		AMP# CH	DESIGNATION			

MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE	MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE MEZZANINE	W340-C W340-C W340-C W340-D W340-D W340-D W340-D W340-D W340-D W340-D W340-D W340-D	W340-A W340-A W340-B W340-B W340-B W340-B W340-B W340-B W340-C W340-C W340-C	RM BEING SERVERD WG30-E WG30-E WG30-E WG30-F WG30-F WG30-F WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G WG30-G	101
MIC 2 MIC 1 MIC 1 MIC 2 MIC 2 MIC 2	MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2 MIC 2	MIC 1 MIC 2 MIC 3 LINE	MIC 3	D TYPE LINE LINE MIC 1 MIC 3	TOTAL INPUTS
M1083 WALLER M1081 WALLER M1085 WALLER M1085 WALLER WALLER WALLER WALLER	M1085 MATTENALE GO. M1081 MATTENALE GO. M1081 MATTENALE GO. M1081 MATTENALE GO. M1081 MATTENALE GO. M1081 MATTENALE GO. M1081 MATTENALE GO. M1081 MATTENALE GO. M1082 MATTENALE GO. M1083 MATTENALE GO. M1084 MATTENALE GO. M1085 MATTENALE GO. M1086 MATTENALE GO. M1087 MATTENALE GO. M1087 MATTENALE GO.	M1073 M1074 M1075 L1025	M1088 M1089 M1089 M1089 M1089 M1089 M1070 M1077	ACK PP JACK	S 136 S 41
ATE 09 ATE 09 ATE 10	ATE OF AT	ATE 01		N1059 N1069 N1069 N1060 N1060 N1060 N1063 N1063 N1063 N1064 N1064 N1065 N1065	
		LINE	LNE	UNE UNE	
				OUTPUTS LOCATION PP JACK PP JACK	
		L4027	L4025	S CABLE ID IL40221	
		<u> </u>	N N	LOCATION	
		262	260	AMP OUTPUT CHANNEL AREA 217 E 218 F	5
		р о	Φ >	CH ARE	WEST AMP ROOM 2.021 AV
		Z2007C	Z2007A Z2007B	Z2006B	ROOM 2
CSEC-03	860380 86		CSEC-03	New Confectors Confect	- 1
0 15 0 15 0 0 16 0 0 17 0 0 18		22 22 23 3 3 3 4 5 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	 	PP LOCATION PP AACK N 7 7 N 10 10 10 10 10 10 10 10 10 10 10 10 10	(PHASE-2)
		CSEC-22 CSEC-2	CSEC-02 CSEC	RACK RACK	
		888888888	 	0.00 ID 0.00 I	
		4 3	2 -	CH	
	 	CSEC-06	CSEC-06	TI, AMP OUT RACK GH 2 CSEC-06 3 CSEC-06 4 CSEC-06	
		97 3	07 1	P DESIGNATION AMP # CH AMP # CH 3	

W208-C W208-C W208-C W208-C W208-C W208-C W207A W207A W207A W207A W207A W207A W207A	W206-A W206-A W206-A W206-A W206-A W206-B W206-B W206-B W206-B W206-B W206-B W206-B	TIE-LINE TIE-LINE TIE-LINE TIE-LINE TIE-LINE TIE-LINE TIE-LINE TRUCK DOCK TRUCK DOCK TRUCK DOCK TRUCK DOCK TRUCK DOCK TRUCK DOCK	HETTER HE	TIE-LINE TIE
MIC 2 CSEC-05 A LUNE CSEC-05 A MIC 3 CSEC-05 A LUNE CSEC-05 C MIC 1 CSEC-05 C LUNE CSEC-05 C MIC 2 CSEC-05 C MIC 3 CSEC-05 C MIC 3 CSEC-05 C MIC 3 CSEC-05 C MIC 3 CSEC-05 C	MIC 1 CSEC-05 A MIC 2 CSEC-05 A LUNE 96/2850 MIN-311 200 96/2850 MIN-311 200 96/2850 MIN-311 200 96/2850 MIN-311 200 96/2850 MIN-311		TOTAL NAPUTS 76 TOTAL AMP CH 219 THE-LUNE (SEC-06 DD 9 10 THE-LUNE (SEC-06 DD 10 11 THE-LUNE (SEC-06 DD 10 11 THE-LUNE (SEC-06 DD 12 11	
0 0 1 4 0 N 1 0 0 0 A 0		υ		JESC / SOURCE ROM ALDITORIUM
UNE CSEC-05 B 18 TO	UNE CSECAS B 6 T	#132333	ITELLINE CSECOGO CO	OUTPUTS ATION PP JAC CC 8 8 9 9 9 9
	TO ROOM CSEC-09 A	O PHASE 4 O PHASE 4 O PHASE 4 O PHASE 4 O PHASE 4	TO AUDITORIUM TO AUDITORIUM TO AUDITORIUM TO VALENCIA TO VALENCIA TO VALENCIA TO VALENCIA TO VALENCIA TO VALENCIA TO VALENCIA TO VALENCIA TO VALENCIA TO PHASE 1 TO PHASE 1 TO PHASE 1 TO PHASE 1 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4 TO PHASE 4	LOCATION
7 3	AMPON 1 A			WEST MAIN CONTROL ROOM 1.0 AMPOUTPUT CHANNEL DESIGNATION CH AREA DESC RACK CSEC-05 CS
CSEC-045 CSEC-045		+++++++++	CSEC-05 B CSEC-05 B CSEC-05 B CSEC-05 A	B B B A A A A A B B B B B A A A A A B
13 (SSEC-02 02 11 (SSEC-02 02 11 (SSEC-02 02 11 (SSEC-02 02 02 11 (SSEC-02 02 02 11 (SSEC-02 02 02 02 (SSEC-02 02 02 02 02 02 (SSEC-02 02 02 02 02 02 02 02 (SSEC-02 02 02 02 02 02 02 (SSEC-02 02 02 02 02 02 (SSEC-02 02 02 02 02 02 (SSEC-02 02 02 02 02 02 (SSEC-02 02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 (SSEC-02 02 02 02 02 (SSEC-02 02 02 02 02 (SSEC-02 02 02 02 02 02 (SSEC-02 02 02 02 02 02 02 02 02 02 02 02 02 0	CSEC-02	16 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	1	SE-3)
3 2 2 4 4 5 CSE CSE CSE				CIO CONNECTION HINDUT OUTPUT AMP OUT FAIL CH CH CH CH
CSEC-08 01 2 CSEC-08 01 3 CSEC-08 01 4	2 9			NEW AMP DESIGNATION PACK AMP # CH

W221-C W221-C W221-D W221-D	W221-C W221-C	W221-B W221-B W221-B	W221-A W221-B	W221-A W221-A W221-A	W209-C W221-A W221-A	W209-C	W209-C	W209-C	W209-B	W209-B	W209-B	W209-A	W209-A	W209-A	W209-A	W208-C	W208-C	W208-C	W208-B	W208-B	W208-B	W208-B	W208-A	W208-A	W208-A	W207-C	W207-C	W207-C	W207-C	W207-B	W207-B	RM BEING SERVERD			
MIC 1	MIC 1	LINE 3	MIC	LINE	MIC 1		MIC 3	MIC		Mic	MIC 1		LINE	MIC	MIC		MIC 3	MIC	E .	LINE	MIC 2	MIC		LINE 3	MIC	MIC	LiNE	MIC 3	Mic		- 1 - 1	VERD TYPE	- ALA	TOTAL OUTPUTS	TOTAL
	CSEC-05	CSEC-05	111		1 CSEC-05		CSEC-05			3 CSEC-05			CSEC-05		Ш	П	3 CSEC-05				2 CSEC-05 3 CSEC-05	H	П	CSEC-05	Н	11		3 CSEC-05	11		RACK	m	AT CH	PUTS	NT III
88 8	9666		86	၈၈	၈၈	HH	ଜ ଜ ଜ	++	+	3 G	+		++-	3 G	+	++	n m	-	+	┰	# m	-	+	8 8 m m	$\overline{}$	-		8	+		o B	LOCATION	219	76	110
\$ t 5	887	4 0 4	3 -	22 21	19		6 5	± ω		5 0	8 7		4	2 22	-	l	5 5	1 2	1	10	ω ω	7		4 ω	2	. 	6	5	13	6	Š	STUE	+		-
																		ŀ														DESC / SOURCE			
LINE		CNE		LINE		LINE		\parallel	LINE			CNE				LNE		1			+		LINE				LINE			LINE		HAL	-		
CSEC-05		CSEC-05	Ш	CSECUE		CSEC-05	\parallel		CSEC-05			CSEC-05		\prod		CSEC-05		-	Coecas	Ш	+		CSEC-05								RACK	m	+		
, , ,		<u>-</u>	Н.	r r) E		╅┷	포 공			Ş	++			C-05			5	+			C-05	-		+	CSEC-05			CSEC-05 D	P	OCATION			
12		6 10		2		18	+		12 TO		+	ō	Ш		1	18 10			1	ш			6 10			Li	18			12 10	JACK	STUG	Ţ		
OROOM		TO ROOM	Com	TOROGN		TO ROOM			TO ROOM			CROOM				TO ROOM			CROOM	200			TO ROOM				TO ROOM			TO ROOM	1000	SG / SOI IBC			
CSEC-08	CSEC-08		CSEC-08		CSEC-08	CSEC-08		CSEC-08				CSEC-08			CSEC-08				CSEC-08			CSEC-08				CSEC-08			000	0000	000	ΠÌ			
AMP-05	AMP-06		AMP-06		AMP-03	AMP-03		AMP-03	+			AMP-03			AMP-03			\dagger	AMP-03			AMP-03				AMP-03			2017	11	3	1 1		5	
о	_		2		ω.	1		6				J.			4			-	ω			N			+						2	AMP OUTPUT CHANNEL		EST M	
n	æ		Þ		0	7		8				•			c				۵			>			1	n			3		3	HANNEL	T.	N CO	
IED 200W	IED 200W		IED 200W		IED 200W	WOOC CI		1ED 200W			1000	WOOC CIE			IED 200W			Ī	IED 200W			IED 200W				1ED 200W			ED ZOOA		DEGC	250		WEST MAIN CONTROL ROOM 1.	
CSEC-05 CSEC-05 CSEC-05 CSEC-05	CSEC-05 CSEC-05 CSEC-05	CSEC-05	CSEC-07	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-07	28-23-82 28-23-82	30-23S2	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-07	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-07	CSEC-05	CSEC-05	CSEC-05	CSEC-05	3	NEW		MOON :	
9	9		- 9 -	++	+		-	o 3		₩	₩.	+	<u> </u>	\perp	-[-]	_	Н.	1	\vdash	\perp	\perp		ш	1		ш	1	_L	ш		1 1	WPP LOCATION	П	059	
200000		1111			0000	11	!	111					1	ŧΙ				1	8 23 C C		11		ш			6 -			Ш	4 2	JACA	1 1		(PHASE-3)	
CSEC-02	+++		+	1-1-1	+++		+	+	_		11		\vdash	_	\perp		ш	\perp		ш			Ш.						l l	11	11	П		3)	
05 12 05 13	05 05 05 11 10 9	8 7 6	11	888	\prod	T	2 2 15 14	П	1	04 11	Ħ	T	04 7	T	11		2 2	П	\top		3 3	+	+	3 3	+	នន	Ħ	88	Ħ	88	C T	QSC 1/O CC			
ω		N	 -			4		+	w			2				-			4				3		1	2	\parallel				유	NNECTION			
ω	2		-		5) 2			u			,	,			-1				4		\parallel	ω		H	+	2					CH		$\ \cdot\ $		
CSEC-08	CSEC-08		CSEC-08		CSEC-09			CSEC-08			CSEC-U8				CSEC-08				CSEC-08			CSEC-08				CSEC-08			CSEC-08		RACK	NEW AM			
2	2		8		3.5			8			8			+	ස		+		92			ន				22			02		CH CH CH CH CH	PDESIGNA			
ω	2	Ш	-					ω			\ \ \	Ш			-				4			з				2			_		2	NO NO			

M811-4 A M81	W309-B W309-B W309-B W309-B W309-B W309-B W310-A W310-A	W308-D W308-D W308-D W308-D W308-A W309-A W309-A W309-A W309-A W309-A	W308-B W308-B W308-B W308-B W308-C W308-C W308-C W308-C W308-C W308-C W308-C	W221-E W221-E W221-E W221-E W221-E W221-E W208-A W308-A W308-A W308-A W308-A W308-A W308-B	TO TO TO TO TO TO TO TO TO TO TO TO TO T
MIC 2 MIC 3 MIC 2 MIC 3 MIC 2 MIC 3 MIC 2 MIC 2 MIC 2 MIC 2	MICO 1	MIC 3	MIC 2 MIC 3 LINE MIC 1 MIC 3 LINE MIC 1	MIC 1 MIC 3 MIC 1 MIC 1 MIC 1	
CSEC-05 CSEC-0	CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05	CSEC-045 CSE	CSEC-05 CSEC	CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05	SEO SEON
00 0000 8888 3	222 222	2 2 2 2 X X	X	 	
8 7 4 3 2 7 2 2 2 2 3 5 6	3,43, 6,98,7	3 2 4 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	7 4 3 2 4 2 2 8	111111111111111111111111111111111111111
					DESC / SOURCE
LINE	LINE	LINE		LINE	TYPE
CSEC-05	CSEC-05	CSEC-05	CSEC-05	CSEC-05	OSEO CK
95 95 95 95 P	05 N	2	6 6		OUTPUTS LOCATION PP JACK
6 70	12 10	6 10	18 12 10	6 10	PUTS V DE 18 TO
TO ROOM	TOROOM	TO ROOM	TO ROOM	TO ROOM	DESC / SOURCE
CSEC-09	CSEC-08	CSEC-08	CSEC-08	CSEC-08	LOCATION CSEC-08
AMP-01	АМР-06	AMP-06	AMP-06	AMP-05	AMP. DESI
4	00	7 6	4 0	ω α	T MAIN COI
		<u> </u>	(C) (B) (B) (C) (C) (C) (C) (C) (C) (C) (C) (C) (C	> m	CONT AREA D
ED 200W CS CS CS CS CS CS CS CS CS CS CS CS CS	ED 200W	ED 200W	IED 200W	IED 200W	WEST MAIN CONTROL ROOM 1 WEST MAIN CONTROL ROOM 1 NEW NEW CONTROL ROOM 1
CSEC-05 CSEC-0		SEC-05 SEC-05 SEC-05 SEC-05 SEC-05 SEC-05 SEC-05	CSEC-045	SEC-05	
008 700008 700008 z z		 		X 2 F X X X X 2 F X X X	1 1 1 1 1 1 1 1 1 1 1 1 1 1
1 1 1 1 1 1 1 1 1 1	1 1 1 1 1		- 8 2 2 2 8 6 6 7 6 6 4 5		(PHASE-3) CATION JACK RA 22 CS 23 CS 23 CS 16 CS
CSEC-02 CSE		SEC-02 SEC-02 SEC-02 SEC-02 SEC-02 SEC-02	SEC-02 SEC-02 SEC-02 SEC-02 SEC-02 SEC-02 SEC-02		RACK RACK CSEC-02 CSEC-02 CSEC-02 CSEC-02
6 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8					QSC 1/O 8
5 0 0 0 0 0 5 5 5 5 5 5 5 5 5 5 5 5 5 5	3 2 2 3 6 9	8705 482	1 6 5 4 3 2 10 4		DONNECTH PUT OU 15 16
N - L		,	ω 4	2	A CH ON ON ON ON ON ON ON ON ON ON ON ON ON
CSEC-08	CSEC-08		CSEC-08	1 CSEC-08	QSC JO CONNECTION NEWAMP OUT RACK HAPUT OUTPUT AMP OUT RACK OS 15 OS 15 A 4 CSEC-08
-08 06 -08 07 -08 07	8 8		05 05 05		VAMP DES
N 4	ω	3	4	05 1	AMP# CH

W612-6 W612-6 W612-6 W612-6 W612-6 W612-6 W613-6 W613-6 W613-1 W613-1 W613-1 W613-1 W613-1	W312-A W312-A W312-A W312-B W312-B W312-B W312-B W312-B W312-B	W311-G W311-G W311-G W311-G W311-H W311-H W311-H W311-H W311-H W311-H W311-H W311-H	W311-E W311-E W311-E W311-F W311-F W311-F W311-F W311-F W311-F W311-F W311-F	W311-C W311-C W311-C W311-C W311-C W311-D W311-D W311-D W311-D	10 10 10 10 10 10 10 10 10 10 10 10 10 1
MIC 1 MIC 2 MIC 32 MIC 32 MIC 32 MIC 33 LINE MIC 4 MIC 4 MIC 4 MIC 4 MIC 1	MIC 3. LINE MIC 1 MIC 2 MIC 2 MIC 3	MIC 1 MIC 2 MIC 3 MIC 3 MIC 3 MIC 3 MIC 3 MIC 3	MIC 2 MIC 2 MIC 3 LINE MIC 3 MIC 3 MIC 3 MIC 3 MIC 3 MIC 3	MIC 1 MIC 2 MIC 3 MIC 2 MIC 3 MIC 1 MIC 1 MIC 1 MIC 2 MIC 3	
CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05	CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05 CSEC-05				SEIGH
C S S S S S S S S S S S S S S S S S S S	000000000000000000000000000000000000000	S Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q Q	 	 	o o Provincia
					DESC / SOURCE
LINE	LINE	LINE	LINE	LINE	LINE
	CSEC-05	CSEC-05	CSEC-05	CSEC-05	
	T	7 7 7 7 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	70 70 70 70 70 70 70 70 70 70 70 70 70 7	7 P	OUTPUTS LOCATION RACK PP JACK PP JACK
TOROOM	TO ROOM	TO ROOM	TO ROOM	TO ROOM	DESC / SOURCE
CSEC-09 CSEC-09	OSEC-09	OSEC-09	CSEC-09	CSEC-09	RCE LOCATION CSEC-09
99 AMP-02 19 AMP-02 19 AMP-03		39 AMP-02 39 AMP-02	09 AMP-01		DESIGN A
22 - 4	o o	3 2	φ		WEST MAIN CONTROL ROOM 1.0 AMP OUTPUT CHANNE. DESIGNATION CH AREA DESC PARCK CSEC-05 CSEC-05 CSEC-05 CSEC-07 AMP-01 5 B SEC-07 SEC-07
0 0	>	л	m		ANNEL AREA
IED 200W		ED 200W			TROL RODESC
CSEC-045 CSEC-0					OOM 1.0 NEWP RACK CSEC-05 CSEC-05 CSEC-05 CSEC-07 CSEC-07
QQ 27 12 22 22 24 14 14 14 14 14 14 14 14 14 14 14 14 14					
Control Cont					
		╎╎╎╎┼╞ ┣┪╏┼┼┼	┡╶ ┠╌┞┈┆┈╏┈┋┈┋┈╟┈╏┈		
5 4 3 2 2 1 6 5 1 4 3	9 8 8 112 112 112 112 112 112 112 112 112	5 4 3 2 - 5 5 5	13 12 14 10 8 7 7 6 5	13 14 15 16 16	INPUT CH 11
	 	1			
	ω Ν		ω		CTION OUTPUT AMP CH C
N-1 4 5	2	- 4	ω N		N OH OUT
		4 4 CSEC-08 08	2 CSEC-08		ACK /

BALCONY BALCONY BALCONY BALCONY BALCONY BALGONY BEGISTRATION REGISTRAT			W015-8 W015-8 W015-8 W015-8 W015-8 W015-8 W016-A W016-A W016-A W016-A		TOTAL TOTAL TOTAL RM BEING SERVERD W314.A W314.A W314.A W314.A W314.B
MIC O O O O O O O O O O O O O O O O O O O		MIC 1 MIC 3 MIC 3 MIC 1 MIC 3 MIC 1 MIC 1 MIC 1 MIC 2 MIC 3	MIC 1 MIC 3 LINE MIC 1 MIC 3 MIC 1 MIC 1 MIC 2 MIC 2 MIC 3	MIC 2 MIC 3 LINE LINE MIC 1 MIC 2 LINE	
CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06	CSEC-46 CSEC-46 CSEC-46	CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06	CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06	CSEC-06 CSEC-06 CSEC-06 CSEC-06 CSEC-06	
Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y	Y W W W 219	W W W W W W W W W W W W W W W W W W W	W W U 220 19	CCCC CCC	410 219 INPUTS LOCATION COP JACK PP JACK 206 U 3 206 U 3 206 U 4
11-13 11-13 11-13 11-13 11-13 11-14 11-15 11-14 11-15 11-14 11-15 11-14 11-15 11-14 11-15 11-14 11-15 11-14 11-15 11-14					DESC/SOURCE
	EN	L L	EN	TYPE	
	CSEC-06	CSEC-06	CSE C-06	CSEC-06	CSEC-06
	×	×	<	< <	V PP
	1 3 1 1 3	12 TO ROOM		12 TO ROOM 18 TO ROOM	
	MO	ROOM	OM	MOX	DESC / SOURCE
	CSEC-10	CSEC-10	CSEC-09	CSEC.09	LOCATION CSEC-09
	AMP-01 3	AMP-01 1		AMP QA	AMP OUTPUT DESIGNATION AMP-04
	0 0	(a) (b)	ν (α α α α α α α α α α α α α α α α α α α	7	MAIN CC CHANNEL CH AREA CH AREA
	IED 200W	IED 200W		IED 200W	NTROL F
CSEC-08 CSEC				N	RAOK CSEC
3 3 2 2 7 7 7 7 7 113 113 113 115 115 115 115 115 115 115	21 21 21 22 22 23 22 23	23 23 24 11 11 11 11 11 11 11 11 11	23 22 23 23 24 3 3 3 3 3 3 3 3 3 3 3 3 3	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	059 (PHASE PP LOCATION PP JACK W 3 W 3 W 3 X 5
			CSEC-02	CSEC-02	RACK CSEC-02 CSEC-02 CSEC-02 CSEC-02
	╂╌┞╼┩╶╎╶╎╴╁┈╁╌╂╌╂	រស់លិលិសិសិសិសិសិសិសិសិ	┞╏╏╏┢╋┪╏ ┼┼┼┼	 	
	4 W N -	9 10 0 0 10 10 10 10 10 10 10 10 10 10 10	0 7 0 0 1 0 0 7 0	16 13 13 12 13 15 15 15 15 15 15 15 15 15 15 15 15 15	O CONNEC INPUT O CH
	4	ω ν		ω 4	QSC JO CONNECTION NEW AMP JOS INPUT OUTPUT AMP OUT RACK 11 6 OH CH 11 7 0 OH CH 11 8 2 3 CSEC-08
	2 CC CC CC	2 09		5	MP OUT RAN
	CSEC-08	CSEC-08			
	75 75	13 1 13		1 1 6	6

PREPARCTION AREA PREPAR	CONCOURSE CONCOU	BALCONY BALCONY CONCOURSE CONCOURSE LONCOURSE	PALCONY BALCON
MIC CSEC-06 A MIG CSEC-06 B MI	Cost Cost		TOTAL NAPUTS
17 16 35-66 17 16 35-66 18 35-66 18 35-66 18 35-66 18 35-66 18 35-66 18 35-33 12 22 35-14 12 35-14 15-66 15-	9 31-61 9 31-61 12 31-61 13 31-61 14 1-12 15 11-12 16 11-12 17 11-12 18 25-14 18 25-14 19 25-14	20 9903 20 9903 21 9903 22 9903 23 9903 24 9903 25 9903 26 9905 27	0150 / SOURCE 11 21-06 12 21-06 13 21-06 14 21-06 15 21-06 16 21-06 16 21-06 17 21-06 18 21-06 19 21-
			TYPE LOOK IN
			OUTPUTS API DESC / SOURCE PP JACK
			LOCATION DESIGNAL
			WEST MAIN CONTROL ROOM 1. AMP OUTPUT CHANNEL CSEC-08
GG RC C C C C C C C C C C C C C C C C C		CSEC As As As As As As As A	
		10 10 10 10 10 10 10 10	
			HO HO HO HO JOED HO JO
			QSC IO CONNECTION I/O # INPUT OUTPUT /AMP OUT RACK /AMP # CH
			DESIGNATION AMP # CH


HALL BT	HALL B1	5	HAT DA	HALL B4	HALL B4	HALL B4	TALL BO	200	LAI DO	HAI R3	HALL B3	HALL B3	HALL B2	HALL B2	HALL BZ	HALL BZ	1000	HAI RS	HALL B1	HALL B1	HALL B1	חאררםו		HAI I BI	ENTRY	ENTRY	ENTRY	ENTRY	ENTRY	ENIKY	PAGING	PAGING	DACING TOTAL	SHOW WANAGED	SHOW MANAGER	SHOW MANAGER	SHOW MANAGER	SHOW MANAGER	SHOW MANAGER	PREFUNCTION AF	PREFUNCTION AREA	PREFUNCTION AF	PREFUNCTION AF	PREFUNCTION AF	PREFUNCTION AF	PREFUNCTION AF	PREFUNCTION A	PREFUNCTION AF	TRETONCHON A	TREFORCION A	TAETONO TOWN	TALL CACHON A	DEED INCTION AS	DEED INCTION AS	DREE INCTION AS	PREFUNCTION AF	PREFUNCTION AREA	PREFUNCTION AF		KM BEING SERVERU					Γ															
MIC	MIC	Mo	S C	N C	MIC	M.O.	Mic	MIC	MIC	M C	-	45	MIC	MIC		CINC	INIC	MIC 3	MIC 2	MIC 1		CINE	100	MIC 3	MIC 3	MIC 1		LINE	MIC 3	MIC 2	MIC	M S	-	LINE	MIC 3	MICZ	-		MIC	M	MIC	MIC	MIC	Z.	MIC.	300	1		- [- 1	- 1		₹	MIC	MIC	Mic	MIC	Mic	MIC	MIC	MIC	N O	MIC	Z.	3	3	5	5 6	5	MIC	MIC	MIC		TYPE			TOTAL AMP C	TOTAL OUTPUT	I O AL INPUIS	A MILL
CSEC-06 II	CSEC-06	CSEC-06		CSECUS												+-	+	-	CSEC-06 EE	-		+	-	-	CSECTOR LL	-	_	-	⊢	CSEC-06 EE	+	4-	~	CSEC-06 EE	┝	COEC-US EE		200000	CSFC-06 D	CSEC-06 DE	CSEC-06 CC	CSEC-06 CC	CSEC-06	CSEC-06 CC	CSEC-UB	CSEC-US	2000		+	CSEC-06 AA	CSEC-06 A	CSEC-06 A	CSEC-06 A	CSEC-06 BE	CSEC-06 BB 23 4	CSEC-06 BE	CSEC-06 BE	CSEC-06 BE	CSEC-06 BE	CSEC-06 BE	CSEC-06 BE	CSEC-06 BE	CSEC-08	CSECOS	COECTO	Caccago	2000	Concord	COLOR	CSECLOS	CSEC-06 BE	CSEC-06 BI	RACK	LOCATI			219		410	I
2	1	2	1 0	Т	,	Т	7	o,	c'n	Г				-3		t	t	+	8	_		T.	T	†		1	1		Т		t	,		4	ü	_	,	- 6	5	5	24	23	23	21	9	-	1	t	1	4	3	œ	7	24	23	13	22	20	19	8	17	6	2	1	1	1	3 =	1	3	٥	30	3 7	JACK	Ş	NPUTS	-			r	1
																																	-												MIC 8	MIC /	NIC 7		9	31-64	31-64	31-10	31-10	45-11	45-11	45-11	45-11	45-08	45-09	45-08 (VALENCIA)	45-08 (VALENCIA)	45-08 (VALENCIA)	45-08 (VALENCIA)	45-08 (VALENCIA)	45-08 (VALENCIA)	45-00 (VALENCIA)	HO-00 (VALENCIA)	45 OB CAL PAGE	45.07	45-07	45-05	45-05		ESC / SOURCE						
							l					ı									LINE					i						-	200																																									TYPE			-			
														4	CSEC-05	⊢				_	CSEC-05 FF	L				4	CSEC OF FF					1	4										3						1																	-							RACK	LOCATIO	OUTPUTS	_				
Н	-	1		_										4	24	L				_	18 T	!	L		-	_	10 11						1					-										ļ		_															Ĺ								JACK	ő	PUTS					
				-											TOROOM						TO ROOM					0.1000	TO ROOM					CACOM																																										DESC / SOURCE						
																														_					_												L	Conce	ı																									LOCATION						
				-																																											AMP-04	AMP-03	3																									DESIGNATION	AMP OUTPUT CHANNEL			VVEST	1	
	1							+	-										1						-	Ŧ	1	-										<u> </u>	1			+		\vdash		L	- (c)	o Z	╁		+		-									_	-	_	L		L	l	ļ	1	+	1		유	CHANNE	L	-	MAIN		
																																				-												NOK H IEU ZOOW																										REA DESC	ı			WEST MAIN CONTROL ROOM 1.059 (PHASE		
CSEC-06	+	╀	H	H	-	-	╀	+	+	4		Ļ	╀	+	4	_	⊢	╀	+	4	_	_	L	╄	╀	1	+	4	4	4	_	Ł	+	4	4	_	┡	╀	+	4	4	4	_	_	<u> </u>	┞	CSEC-07	CSEC-07	S C S S S S S S S S S S S S S S S S S S	8 8	4	4	4	4	CSEC-06	4	Ц	Ц	4	_	_	Ц	L.		L	_	L	L	╀	4	4	4		RACK	NEW P			ROOM 1.C)	
8	88	8	ဓဓ	8	န	ଜ	G	3 8	3 8	8	9	G	8 8	3	Ħ	Ŧ	Ŧ	1	7	7	#	4	77	7	1	1	R :	7	H	뀌	FF	7	1	n :	7	뀨	7	A	A F		7	A	Ħ	A	A	R	8	8	8 8	8 8	8 1	# 1	A	H	R	A	A	몽	8	8	8	8	8	8	8	8	8	5	18	3 8	3 8	8	-	PP	NEW PP LOCATION			159 (P	,	
14	2 12	=	10	9	∞	1	, 0	1		4	ω	N	1	1	-		ı		ı	ı				ı	13	ı	1	-	1	ı		0	ı		-			ı	6 2	1	*	3	12	=					l		1	B .		4	ω	2		24	23	23	21	20	19	8	17	க்	5	14	٦	3	3	3	- [ı					
											i			0000	CSEC-03	CSEC-03	CSEC-03	CSEC-03		0.03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	2000	00000	CSEC 03	CSEC-03	CSEC-03	CSEC-03	CSEC-03	0000	CSEC-03	CSEC-03	CSEC-03	CSEC-03								CSEC-03	CSEC-03	CSEC-02	CSEC-UZ	Coecos	200	COLOR	CSEC-03	CSEC-03																			-		RACK				ن	,	
								ŀ		1		-		+	4	_	L	₽	+	4	4	_	_	H	14	+	4	4	4	-	_	L	+	+	4	_	L	╀							_	Щ	L	L	┸	1	┸	3 6	_1				-		-											+	+			I/O#	QSC					
														ŀ	4	6	15	4	٥	ام	3	12	2	6	9			»	1	6	U1	_		,	ω	N	_								14	13			٥		7	30 e	5																				요	INPUT	O CONN					
																															_																	T	Ī																						1	,	유	OUTPUT AMP	I/O CONNECTION NEW AMP DESIGNATION					
								l						-					-												_												-	-			8 CSEC	CSEC-09		I	+	+	-		$\frac{1}{1}$					-	1				-	-							ť	OUTRACK	NEW					
\parallel	-	Н					-		-	+	-	_			-				1	1								+	1					+					-	-	+		+			Н	┞	╀	ŀ	-	+	+	-	+	+						-						L			+		+	+	A	AMP DES	\parallel	-			
												_					_													_	_																4	3	╁																	L	_							P# CH	MGNATION		_			


HALL B4	HALL B4	HALL B4	HALL B4	HALL B4	HALL B4	TALL	יייייייייייייייייייייייייייייייייייייי	- PAIL 04			HA I	HALL B4	HALL B4	HALL B4	HALL B4	TALL B4	TALL D4		HAI DO	B	HAI I B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL BS	HALL BO	HAI CO	HALE BO	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B3	HALL B2	HALL BZ	EAL 02	1 P C C C	HALBO	HA I RO	HALL B2	HALL BO	HALL BY	HA I RO	HAI TO		DALL 02	LALL DZ	HALLES	HAI B	HAI BO	HAL B1	HALLBI	HALL B1	HALL B1	HALL B1	HALL B1		RM BEING SERVERD					T	7
MIC	M C	MiC	MIC	MIC	MiC	MIC	M.C	N.C	300	5 0	5	MIC	Mic	MIC	Mic	MIC	MIC	CIVIC		IN I	I I	N C	N C	MO	N C	Min	Mic	110	N C	200	MIC	MIC	M	Min.	Mic	MIC	MIC	MIC	Mic	Mic	MIC	Mic	MIC	MIC	LINE	LINE	CNE	LINE	T C	N	Mic	N. C	M. S.	O. C.	MIC	300	S S	S C	MIC	W. C	MIC	- IN	LINE	LNE	LINE	MIC	Mic		ERVERD TYPE			TOTAL AMP CH	TOTAL OUTP		TOTAL IND
CSEC-06	CSEC-06	CSEC-06	CSEC-06	_		_	_	1_	Concord	2000	20000	CSECUS	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	COLCAGO	0000	2000	CSECOS	CSECOS	CSECTOR	CSECOS	Concord	CSECOS	COECTO	00000	COEC-GO	COECUGO	CSECOS	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06	COECTO	COEC-OO	COLCUM	SCORE	CSECOR	CSECO	CSEC-96	Concord	00000	CSEC-08	COEC-S	00000	Concord	Concord	CSECOR	CSECOS	CSECLOR	CSEC-06	CSEC-06	CSEC-06	CSEC-06	RACK	LOCA		١	CH 219	l		
22	28	19	18	┰	± 24	± 23	t	t	2	2 2	6 6	Ė	표 17	16	15	14	13	1	5	1 6	5	0 5	= = 5 C	7 4	2 2	200	3 =	2 2	5 4	0 0	a	5	3	±	5	9	8	1	6	5	Ξ •	Ξ 3	王 22	王 -	8	7	10	. E	- G	3 2	3 6	3 5	2 2	3 4	3 6	3 3	16	5 5	7 7	3 6	13	= 1 -	اد	2	<u>د</u>	4	3	Š		S				 -	_
																																															-																						DESC / SOURCE						
H																										T	-																																									RACK	TYPE					_	
						_										_	_			-	-											+	-			+	1								_		-	-		-							-			-	-	1					1		LOCATION	OUTP					
															•••																																																						DESC / SOURCE	JTS					
																																					Ì															-																	LOCATION						
																																																																					DESIGNATION CH AREA	AMP OUTPUT			WEST	101	
			1																-												-			+												_													-										CH AREA	CHANNEL			WE'S MAIN CON ROL ROOM 1.0	::>>	
88	8	200	28	20	83	33	S	33	23	8	83	1 8	3 8	2	ß	33	S	8	S	Ω	12	38	38	33.2	2	3 8	Ω	S	ı Ω	S	3 5	3 2	2 5	2 5	2 2	38	2 5	3 2	2 5	2 5	2 5	2 2	2 5	Ω	Ω	Ω	Ω	Ω	202	2 2	2 2	2 2	2 2	Ω	Ω	Ω	Ω	Ω	Ω	S	2 5	2 5	2 5	2 5	2 5	2 5	Ω		DESC				T C T T C	1	
CSEC-06 JJ	-	+	+	+	4	-	-	4			⊢	╀	+	4	4			_	┡	╄	1.	1.	1.	┺	╄	╀	_	┺	╄	-	╄	1.	+	1	1	┸	1.	┺	4	_	1	4	4	4	_		┖	L	1_	1	1	┸	┸	┖	┖	┺	L	ļ.,	┸	┖	L	1	L	1	1	\perp		1	RACK PP JACK	NEW PP LOCA			OM 1.059 (F) · · · · · · · ·	
17 18	16	15 7	1	13 1	3	3	6	9	8	7	6		1	_	ω	2		24	23	22	21	20	19	8	17	ō	15	7.	13	12	3	10	5 4		,	10	, 0	4		۸ د	3 -	. !	24	23	6	15	14	13	12	=	1	9	8	7	o	c,	4	w	2	_	. 20	3	0		17	5 6	3		JACK RACK	TION			59 (PHASE-3))	
	1		+										-	1												-		_				-						ŀ			1		1						-																			0	I/O# INP	0SC 1/0 C					
		1		-								-		1													L		_			-					L				-	-	-																						1	1	9	2	I/O# INPUT OUTPUT AMP OUT RACK AMP # CH	NNECTION					
																-																																																			5	2	MP OUT RACK	NEW					
				+		+															_	-	-		-									1	-		-											_															-					2 100	AMP#	MP DESIGNATI	-				


HALL B SPEAKERS	HALL B STEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	TALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HAI B SPEAKERS	HAIL B SPEAKERS	HAII R SPEAKERS	HALL B SPEAKERS	HALL D OF CANERO	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS						HAI BA		RM BEING SERVERD			ТОТА	TOTAL	101/												
																																																									LINE CSEC-06 JJ 20	CSEC-06	CSEC-06 JJ	CSEC-06	C C C	250	THE LOCATION	INPUTS	H		TOTAL OUTPUTS 76	П
																																																															DESC / SOURCE TYPE					
																																																															LOCATION	OUTPUTS				
CSEC-12	- 1	- 1	- 1		1	1	1	1 1	1 3		- 1	- 1	J		- 1	- 1	1	- 1	- 1	- 1	1		CSEC-11	CSEC-11	CSEC-11	CSECTI	Control 1	Cont.	COEC	CSEC-11	0000-11	Concern	Concern	Conc-1	Conc.	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	SEC.	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	CSEC-11	Concern	Concert	Concern							DESC / SOURCE LOCATION					
AMP-03 3 G	3	- 0	20 ~	40	0	4	. 3	2	-	8	7	6	5	4	ا در	2	- 4	80	7	20 0	\pm	A (AMP-06 3 G	AMP-06	AMPAG	+	AME OF CO.	+	+	+	AMP OF A	AMD-05	AMP-U4	AMP-CA	AMP OF	AMT-04	AMT-04	AMP-04 3	AMP-04 2	AMP-04 1	AMP-03 8	AMP-03 7	AMP-03	AMP-03	AMP-U3	AMP-03	AMP-03	AMP-03	AMP-02 8	AMP-02 7	AMP-02 6	AMP-02	AMP-02	AMP-02	AMP-UZ	AMBOS							DESIGNATION CH A	AMP OUTPUT CHANNEL			WEST MAIN	
G-50 CSEC-07			SEC-07	+				CSEC	49 CSEC-07	CSEC	47 CSEC-07	CSEC	CSEC	CSEC	COEC						-			1		ļ	-	T			1		G-24 CSEC-0/			-	_											-			G-06 CSEC-07			G-02 CSEC-07			CSEC-06	CSEC-06	CSEC-06	CSEC-06	CSEC-06		AREA DESC RACK	IL NEW			WEST MAIN CONTROL ROOM 1.	
05 15 CSEC-03 05 16 CSEC-03	: 1	12	3 3	10	9	00	7	თ	S.	4	ω r	S	- !	24	3 1	2 5	24 25	2 9	2 9	2 9	2 2	2 4	4	2 5	2 5	5 =	2	2	2	2 2	ş	2 2	2	3	2	2 2	03 24	03 23	03 22	03 21	03 20	03	03	03 17	03	03	03	03 13	03 12	8	03	2 0	2 5	3 33	3	24		٤	٤	£	'n		PP JACK RACK	W PP LOCATION			1.059 (PHASE-3)	- 1
16 6	+	+	+	╁	⊢	Н	Н	-+	+	+	+	+	+	+	+	+	+	+	+	╀	+	+	╀	╀	┿	+	Ļ	╀	╀	+-	+	╀	╀	┡	╀	+	-	Н	-	_		_	┡	┖	┺		ļ	ш	4	4	4	+	1.	┺	╙	┖							I/O# INPUT OUTPUT A	QSC I/O CONNECTION				
14 CSEC-10 15 CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	╅	CSEC-10	CSEC-10	+	Concord	00000	Concorda	COEC-GO	0000	CSEC-69	0000	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09	├-	CSEC-09	CSEC-09	CSEC-09	CSEC-09	CSEC-09		CSEC-09	CSEC-09	_	CSEC-09	Н	Н	CSEC-09	Н	CSEC-09	+	CSEC-09	+	CSEC-09	CSEC-09	Н	H	╀						H CH	OUT AMP OUT RACK A	NEW AMP DESIGNATION				
28 28	28	27 4	27 3	27 2	27 1	4	ω	ж ⁸		× 0	3 1	, -	4	3	4 2	, -	4		23 2	1	4	t	2	t	21 4	t	21 2	H	4	3	20 2	20	19 4	19 3	19 2	19	18 4	18 3	18 2	18 1	17 4	17 3	17 2	17 1	16 4	Н	16 2	+	+	3 1	+	4	╁	┝	14								¥ CH	SIGNATION				


	7	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	TALL C SPEAKERS	HALL C SPEAKEDS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	TALL C OFTANTA	TALL C SEEAKERS	HALL C SEERKERS	HALL C SDEAKEDS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	HACL C SPEAKERS	HALL C SPEAKERS	HALL C SPEAKERS	TALL C OPERATERS	TALL C OFFICERS	TALL C OF BANEAS	HALL C OF DAKENG	HALL C SPEAKERS	HALL C SPEAKERS	HALLC	HALLC	HALLC	HALL C	١	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL 8 SPEAKERS	HALL B SPEAKERS	TALL B STEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	DALL D OF CAREAG	TOTAL DESCRIPTION	DALL D GODANENG	TALL D OF LOTE NO	HALL B SPEAKERS	HALL B SPEAKERS	HALL 8 SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS	HALL B SPEAKERS		RM BEING SERVERD			1015	TOTAL	IOTAL	101				
																								-					1																4	-	1	-1	MIC 2	-				L	-															_	70	JYPE			LAMPOH	ALI CIG	TOTAL CHIEFLE	NPUTS
	1		1	+	+																					-	-									L			Ĺ							4	-	-	CSEC-06	-																			-		RACK	LOCATION			219	2 6	7.0	410
	+	1	+	+	-			-	1		1								-	-	į					+			1	-											-						ξ.	1	Ω.	₹ -	+		_						H					1							PP JACK	Ş	INPUTS	-			+	┨
																***************************************																								-																																DESC / SOURCE					İ	
	+	-	-	-				+	+		ļ															-	-	-																	-			-	-															+					-									
	+				+					-	-						-	1								-	-	-			-											L		+	CINC				-														l									TYPE						
		L					-		-												-							-	-		_										_			-	CoEC-GG	+						-										_									RACK	LOCA						
-																							_	_					1				-									l.		_	6	+			1					-	-										+						PP JACK	NOI	OUTPUTS					
																																													CKOOM	TOPOOL																										DESC / SOURCE						
Conco	CSEC-11	CSEC-11	CSEC-11		1		1	4	1		4			- 1						- 1		- 1	- 1			1	CSEC-10	2010-10	200	2000	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-10	CSEC-70	2010							- 1	· f	CSEC-12			1	ı		ı		ł	F	1	1	1	- 1	- 4	- 1	3								
ZWT-G	AMP-01	AMP-01	AMP-01	AMP-01	AMP-01	AMP-06	AMP-06	AMP-06	AMP-06	AMP-06	AMP 06	AMT-00	AMID OF	AMP-OS	AMP-05	AMP-05	AMP-05	AMP-US	O. C.	AMPOS	AMP-05	AMP-05	AMP-05	AMP-04	AMP-04	AMP-04	AMP-04	WINIT-04	AMIT-ON	AMD O	ANGON	AMP-04	AMP-03	AMP-03	AMP-03	AMP-03	AMP-03	AMP-03	AMP-03	AMP-03	AMP-02	AMP-02	AMP-02	AMP-02						C. 100	AMPLOS	AMP-05	AMP-05	AMP-05	AMP-05	AMP-05	AMP-05	AMP-04	AMP-04	AMP-04	AMP-04	AMP-04	AMP-04	AMT-04	287-04	AMD 04	AMPOS	AMP-03	AMP-03	AMP-03		LOCATION DESIGNATION CHI AREA	AMP OUTPU			VVEG	TOTAL	
300	5	Н	ω	2	t	8	t	о П	t	t	3		t	1		H	H	t	t	<u> </u>	+	2		8	H	6	H	4		3 1	3		20	+	o	5	4	3	2		8 · F	7 1	r	0	t	ļ		1	1	t	t	7	+	4	+	_	Н	8		6	H	t	3	t	t	t	†	+	6	+		오	JT CHANN			5	2	
EN1.7 JEL	E F	H	1 1		1	1			(1			- 1	- 1				1	- 1	- 1	- 1	- 1				1	1		- 1	- 1	- 1	- 1	- 1	- 1	- 1	- 1		- 1	F-86		1	ı	F-01	1	-	_		-					G-76																	- !	- 1	F	-	_	CON	2017	
ZUUW C	IED 200W CSEC-07	200W C	200W C	200W C	200W C	200W C	200W C	200W C	200W C	200W C	200W C	COOM	20004	2000	200W	200W C	200W C	200W C	VACOUAL C	2000	NOOC C	WOOD C	200W C	200W C	200W C	200W C	200W C	ZUOW	ZUUVV	2000	200	O COLOR	MUUC	200W	200W C	200W C	200W C	200W C	200W C	200W C	200W C	200W (C	200W C	200W C		100)			_	0											DESC				AACC LANGE COM LYCH YOUR TO	2	
																																																																								RACX	NEW			CIVI I.	Š	
98	80	8	8	8	07	07	07	07	07	07	07	97	3	95	77	9	07	07	ç	35	9,5	3	07	07	07	07	07	70	۶	3 0	3 8	8	200	96	8	8	6	6	66	8	90	06	8	06	F	3	3	3	?	8	8 8	3 8	86	8	8	6	90	8	6	96	8	95	8	S	S	8 8	2	2 2	3 3	S	1	PP JACK	PP LOCAT					
	4		1		24 C							l	1	1	1	i		ı	ı		ſ		-	- 1					t		П			1	1	1		ı	1						ı	ı		1		2 5	ı	1	9	8	7	6 C	5	4	۵ 0	2 0				İ	ı	1	1	ı	à :	- {	- 1		일			DA LLHOE-9	2	
SEC-03	CSEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	350-03	0000	SECTO	SEC-03	SEC-03	SEC-03	SEC-03	2000	200	SEC D3	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	0EC-03	200	200	SEC DE	SECTOR	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SECOS	SEC-03	SEC-03	300	300	200	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	SEC-03	800	SEC 03	50-03 010 010 010	SEC-03	- 1	RACK				۷	•	
18	18	8	8	æ	18	18	18	8	6	18	18	18	1	1	17	17	17	17	1	1	1	17	17	77	17	17	17	17	17	1		1 :	17	17	17	17	17	17	17	17	17	17	17	17	13	12	=	ā	6		;	17	1,	6	6	6	16	6	6	16	16	16	16	6	đ	ā	ā	à	5 6	5	-	0 4	080100					
ŀ		+						_					-							l				-	-				-		+								-		-					24	23	1	3 2	2	+	+	1	+	1		-									-	-	1		- !	오	NPUT O	CONNECT					
L			_			-		+		1					-			L		-			$\frac{1}{2}$					L											+	$\frac{1}{1}$					2		L	L	ŀ	1	+	+			-					-									1		오	TPUT AM	QSC I/O CONNECTION NEW AMP DESIGNATION	+	_			
13	12	- -	6	9	8	7	đ	ch	4	ω	2	_	32	5	2 2	8	29	28	77	6	3 6	1	2 5	23	8	21	20	19	188	1	ā	6 0	1	1	ă li	3	3	ő	9	co	7	6	C)	4		-					Con	S -	Cal	37 CSF	31 CSE	30 CSE	29 CSE	28 CSE	27 CSE	26 CSE	25 CSE	24 CSE	23 CSE	22 CSE	Z1 CSE	CSI	200	200	200	17 CS	오	P OUT RAC	200	1	_			
		-	1				-														-	-	1									-			-	$\left \right $														╁	╁	5 6	5 6	CSEC-10	C-10	C-10	C-10	;; 10	C-10	С-16 С	10-10	C-10	C-10	10.10	-C-10	ic-i	100	5 6	5 6	ő		×	WAMPDE					
4	3	3	3	3	4	2	2	4	2	4	4	4	6	40	5	6	8	39	39	8	9	8	8	# 	8	38	37	37	37	37	8	8	8 8	8	8	3	5	3	3	2	¥	3	4	జ			l			8	8	3 8	3	3	3	8	23	4	3	3	3	ဗ	ၓ	8	8	12	3	3/0	3 8	8	1	Š	SIG					


												DIRECTIO	DIRECTIVO	DIRECT I/O	DIRECT I/O	DIRECT I/O	DIRECT I/O	CIXEC IO	Diput In	DIRECT IO	3	9	7	7	7	?		3	2	7	7		3	3	?	?	~				3	?	~	?	7	7	?	7		3	3	3	3	3	3	3	3	3	3	3	7	7	7	~	?				9	3	?		RM BEING SERVERD						
	1																																				-																					1										l							_	TOTAL AMP C	TOTAL OUTPUTS	I O I AL INFU	TOTAL MICH
																_				Ī								Ī	1				ĺ	l						İ								-			ľ	ľ	Ī		1	Ì							-				l					RACK	5		1		S 76		
							-	-	1	T			1	1	-				Ţ	1	ļ	1	-				ľ		1	-	-				1		_				-						_				ľ		+	1	1		ļ	1		1		1							İ			PP JACK	ATION	INPUTS		9	<u>.</u>	9	
																																																																									DESC / SOURCE	S					
																																																									1			ĺ	ľ									İ		-	TYPE				_	_	
												Ī											1				-														Ī			Ī	1																	1				_					3	BACK	OCATION		Ī				
						1	1	1						1	1						T		1						l	1				ļ	1				_	-	-	1	1		1	1			_						+			İ	ľ		†	1	1								77	100	PATON O	CUTPUT	†	_			l
																																																																								ער סטייים	DESC / SOLIDOE	8					
																																																							CSEC-08																	COCKLION	CONTINU						
														-								İ			ĺ						Ì				ļ													ĺ							AMP-04			AMP-02	AMP-02	AMP-02	AMP-UZ	AMP-02	AMD 03	AMP-03	AMP-01	AMP-01	AMP-01	AMP-01	AMP-01	AMP-01		DESIGNATION	AMP OUT OF S	AMP OF ITE			WEST		
ŀ		+		-		+	l		H				-	-						8 4.03	7 4.03	6 4.03	4.03	1	4 03	3 40	2 4.06	1 4.06	8 4.06	4.00	7 400	6 300	5 3.00	4 3.09	3 3.08		300	3 3.0	7 3.02	6 3.02	5 3.0	3.0	0.0	3 3.0/	20.0		200	5 216	4 2.16	3 2.1	2 2.1	1 2.1	8 2.1	7 21	6 2.116L	5 2.1	4	6 2.006C-6				2.00		3		7 1.0		4 1.0	3	2 80.		2	CHANNEL	CHANNE			MAN (
ŀ		1	+		+				-	-							1	1		2C-2	2C-1	50.3	2.2	3 5	5 6	870	4.78	8C-3	ec.2	2	5 6	S	<u>අ</u>	30-2	1-2	5,0	370	92C	70-2	70-1	290	020		ķ	200		Var	80.5	9C-1	386	151	171	18FS	Ē	161	10 00	_	နိုင်	96C-5	<u>آم</u>	SC.	2.5	5	5	830	820	050	030	?	SO.ENT.2		CEA DESC	1	-			SNIR		
L													_							CSEC	CSEC	CSEC	CSEC	COLC	Conc	Caro	CSEC	CSEC	CSEC	Coec	2000	CSEC	CSEC	CSEC	CSEC	Caro	COEC	CSEC	CSEC	CSEC	CSEC	CSEC	Conc	CSEC	CSEC	COLC	200	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC-07	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	200	200	CSEC	CSEC	CSEC	CSEC	CSEC	CSEC		KACK	١		-		WEST MAIN CONTROL ROOM 1		
-	-	+	-	-	1			ļ 				0	œ	6			, ,	A :			_	ـــ	١.	1.		_	_		_	L	ı				ᆫ					_ [L	J.,		- 1	i	- 1	- 1	- 1			ł	-07 08						1		1	1	- 1	- 1	- 1	- 1				l	É						
		İ	+								4	s	2	_	4		,	ه.	_	3	2		24		T	T	1				T	1	1	Г	Γ	ľ	Ť	1	1	1			T	Γ	0	Ī	Ī	2 1	Ì	1	7				20		П			-	Г	İ	t	t	Ť	1	1	1				JAC	PPLOCATION				059 (PHASE-3)		
_	-	1		-	l						CSEC	CSEC	CSEC	CSEC	CSEC	CSEC	2010	2000	CSEC	CSEC	CSEC	ı	i	L	1	1	1			ı	1	1	-		ı	l	П	П	- 1	-1		ı	ı	CSEC	CSEC	Sec	200	2000			- 1	- 1			CSEC-03	Ш				١,		ı	П	П	П	-[- 1	- 1		Ш		RACK		ŀ		100	(F-3)		
	+	+			-	L				Н	-		-		-	┿		+	\dashv	-	-	Н	⊢	┾	╁	+	+		-	⊢	ļ.	+	-1		⊢	⊢	+	+	+	+	_	⊢	⊢	⊢	+-	╀	+	+	+	8	ස් 18	ස් ස	ස ස	-03	-03	2	03	-03	-03	-03	-03 11	-03	ės.	3 8	3 8	3	03	2	ີ່ຜູ້ -	03	-	ı	1					i	
H						İ							N					1				_		-					_					_							_			_					1		1	3			8	<u>ت</u>	Ф	ω,	Φ.	8	8						2	8	8	8	오	# NPU	SC I/O CON						
	Ì	ľ		Ĺ											4	3	, N	,	-							l		1				l		_				1		i		_					l			1										_				Ì							.CH	OUTPU	NECTION	-					
						i												Ī		27	26	25	24	23	2	3 2	2 1	3	16	18	-	1	5	15	14	13	ž	3		5	9	8	7	o	5	4		3	١-	- 1	83	3	ၽ	29	28	27	26	25	24	23	ß	21	20	4	5 0	:	17	5	15	1	유	T AMP OU		-	l				
		ĺ																				_																İ	1								1		1		+				3 18 28 47 4		1				_						1					TRACK	NEWAM						
	1					1							+							ដ	55	55	2	22	2	ž		63	53	53	g	3 5	3	52	బ	52	9		2	2	51	50	50	50	50	49	48	t	40	À	45	46	8	48	47	47	47	47	46	46	46	46	45	đ	đ		7, 1		4	2		AMP#	DESIGNA	-					
		_													L					ω	2		4	ω	2	-	ľ	1	ω	2	-	1	1	ω	2	_	4	١	•	٠ -	-	4	3	N	_	4	٥	1	- اد	1	4	ام	N		4	ω	2	_	4	ω	2	_	4	6	-	<u>-</u>	٠.	1	ω	N		유	ğ						














TECNE MODEL PERSONNE LAST SAMED BY LOST SAMED BY LAST SAMED BY

